

Lecture 6

Instructor: Subrahmanyam Kalyanasundaram

26th August 2019

Plan

- ▶ Last class, we saw DELETE in Red-Black Trees

Plan

- ▶ Last class, we saw DELETE in Red-Black Trees
- ▶ Today, order of insertion in BST
- ▶ Randomized quicksort
- ▶ Traversals of Binary Trees

Course grading scheme

- ▶ 60% – Exams (2 or 3)
- ▶ 30% – Programming Assignments
- ▶ 10% – Attendance and Quizzes

Course grading scheme

- ▶ 60% – Exams (2 or 3)
- ▶ 30% – Programming Assignments
- ▶ 10% – Attendance and Quizzes

Exam on Thursday, 5 Sep

Traversals of a Binary Tree

Pre-order Traversal: $\text{PRE-ORDER}(v)$

Traverse v , then do $\text{PRE-ORDER}(\text{left}(v))$, and then do $\text{PRE-ORDER}(\text{right}(v))$.

Traversals of a Binary Tree

Pre-order Traversal: $\text{PRE-ORDER}(v)$

Traverse v , then do $\text{PRE-ORDER}(\text{left}(v))$, and then do $\text{PRE-ORDER}(\text{right}(v))$.

Post-order Traversal: $\text{POST-ORDER}(v)$

Do $\text{POST-ORDER}(\text{left}(v))$, then do $\text{POST-ORDER}(\text{right}(v))$, and then traverse v .

Traversals of a Binary Tree

Pre-order Traversal: $\text{PRE-ORDER}(v)$

Traverse v , then do $\text{PRE-ORDER}(\text{left}(v))$, and then do $\text{PRE-ORDER}(\text{right}(v))$.

Post-order Traversal: $\text{POST-ORDER}(v)$

Do $\text{POST-ORDER}(\text{left}(v))$, then do $\text{POST-ORDER}(\text{right}(v))$, and then traverse v .


In-order Traversal: $\text{IN-ORDER}(v)$

Do $\text{IN-ORDER}(\text{left}(v))$, then traverse v , and then do $\text{IN-ORDER}(\text{right}(v))$.

Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5



Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5



Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5



Traversals of a Binary Tree

Pre-order Traversal

18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5




Traversals of a Binary Tree

Pre-order Traversal

18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18




Traversals of a Binary Tree

Pre-order Traversal

18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18




Traversals of a Binary Tree

Pre-order Traversal

18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18




Traversals of a Binary Tree

Pre-order Traversal

18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18



Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18

In-order Traversal

23, 22, 7, 56, 8, 45, 10,
46, 18, 33, 28, 16, 5



Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18

In-order Traversal

23, 22, 7, 56, 8, 45, 10,
46, 18, 33, 28, 16, 5



Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18

In-order Traversal

23, 22, 7, 56, 8, 45, 10,
46, 18, 33, 28, 16, 5



Traversals of a Binary Tree

Pre-order Traversal


18, 7, 22, 23, 8, 56, 10,
45, 46, 16, 33, 28, 5

Post-order Traversal

23, 22, 56, 45, 46, 10,
8, 7, 28, 33, 5, 16, 18

In-order Traversal

23, 22, 7, 56, 8, 45, 10,
46, 18, 33, 28, 16, 5



Question

What does the in-order traversal of a BST look like?

Question

What does the in-order traversal of a BST look like?

BST Sorting Algorithm

- ▶ Insert the elements sequentially into a BST
- ▶ Do an in-order traversal of the BST

Time Complexity of BST Sort

- ▶ Insert the elements sequentially into a BST
- ▶ $n \cdot O(h) \leq n \cdot O(n) = O(n^2)$.

Time Complexity of BST Sort

- ▶ Insert the elements sequentially into a BST
- ▶ $n \cdot O(h) \leq n \cdot O(n) = O(n^2)$.
- ▶ Do an in-order traversal of the BST
- ▶ $O(n)$.
- ▶ Total time complexity is $O(n^2)$ in worst case.


An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5

3


An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




An example

Consider the sequence 3, 1, 8, 2, 6, 7, 5




12 Comparisons


Order 1: 5, 2, 7, 8, 3, 1, 6




Order 1: 5, 2, 7, 8, 3, 1, 6




Order 2: 1, 2, 3, 5, 6, 7, 8



Order 1: 5, 2, 7, 8, 3, 1, 6



Order 2: 1, 2, 3, 5, 6, 7, 8



Comparison Count

Order 1: 10

Order 2: 21

A detour: Quicksort

The Goal

Given an array A of n elements, arrange the elements in increasing order.

Quicksort(A, s, t)

1. If $s \geq t$, exit.
2. Choose pivot p from $\{s, s + 1, \dots, t\}$
3. $q = \text{Partition}(A, s, t, p)$. $\text{Partition}(A, s, t, p)$ partitions $A(s, t)$ **in place** into less than pivot, pivot and greater than pivot. It also returns the correct index of p .
4. Quicksort($A, s, q - 1$)
5. Quicksort($A, q + 1, t$)

Deterministic Quicksort

Quicksort(A, s, t)

- ▶ If $s \geq t$, exit.
- ▶ **Deterministically** choose pivot p from $\{s, s + 1, \dots, t\}$
- ▶ $q = \text{Partition}(A, s, t, p)$.
- ▶ Quicksort($A, s, q - 1$)
- ▶ Quicksort($A, q + 1, t$)

Deterministic Quicksort

Quicksort(A, s, t)

- ▶ If $s \geq t$, exit.
 - ▶ **Deterministically** choose pivot p from $\{s, s + 1, \dots, t\}$
 - ▶ $q = \text{Partition}(A, s, t, p)$.
 - ▶ Quicksort($A, s, q - 1$)
 - ▶ Quicksort($A, q + 1, t$)
- ▶ For instance, pivot p is always the first element.

Deterministic Quicksort

Quicksort(A, s, t)

- ▶ If $s \geq t$, exit.
 - ▶ **Deterministically** choose pivot p from $\{s, s + 1, \dots, t\}$
 - ▶ $q = \text{Partition}(A, s, t, p)$.
 - ▶ Quicksort($A, s, q - 1$)
 - ▶ Quicksort($A, q + 1, t$)
-
- ▶ For instance, pivot p is always the first element.
 - ▶ The running time is determined by the number of comparisons.

Deterministic Quicksort

Quicksort(A, s, t)

- ▶ If $s \geq t$, exit.
 - ▶ **Deterministically** choose pivot p from $\{s, s + 1, \dots, t\}$
 - ▶ $q = \text{Partition}(A, s, t, p)$.
 - ▶ Quicksort($A, s, q - 1$)
 - ▶ Quicksort($A, q + 1, t$)
-
- ▶ For instance, pivot p is always the first element.
 - ▶ The running time is determined by the number of comparisons.
 - ▶ Any deterministic pivot rule requires worst case $\Omega(n^2)$ comparisons.
 - ▶ One can come up with a bad input order for any deterministic pivot rule.

Deterministic Quicksort

Quicksort(A, s, t)

- ▶ If $s \geq t$, exit.
 - ▶ **Deterministically** choose pivot p from $\{s, s + 1, \dots, t\}$
 - ▶ $q = \text{Partition}(A, s, t, p)$.
 - ▶ Quicksort($A, s, q - 1$)
 - ▶ Quicksort($A, q + 1, t$)
-
- ▶ For instance, pivot p is always the first element.
 - ▶ The running time is determined by the number of comparisons.
 - ▶ Any deterministic pivot rule requires worst case $\Omega(n^2)$ comparisons.
 - ▶ One can come up with a bad input order for any deterministic pivot rule.
 - ▶ Can randomization help?

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.
- ▶ If we choose the median as the pivot, the recurrence for number of comparisons is

$$T(n) = 2T(n/2) + (n - 1)$$

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.
- ▶ If we choose the median as the pivot, the recurrence for number of comparisons is

$$T(n) = 2T(n/2) + (n - 1)$$

- ▶ This solves to $\Theta(n \log n)$

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.
- ▶ If pivot gives a $[n/10, 9n/10]$ -split, we get the recurrence.

$$T(n) = T(n/10) + T(9n/10) + (n - 1)$$

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.
- ▶ If pivot gives a $[n/10, 9n/10]$ -split, we get the recurrence.

$$T(n) = T(n/10) + T(9n/10) + (n - 1)$$

- ▶ Even this gives us $\Theta(n \log n)$ number of comparisons.

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.
- ▶ If pivot gives a $[n/10, 9n/10]$ -split, we get the recurrence.

$$T(n) = T(n/10) + T(9n/10) + (n - 1)$$

- ▶ Even this gives us $\Theta(n \log n)$ number of comparisons.
- ▶ A random pivot is likely to work with probability 0.8.

Why randomize?

- ▶ Worst case occurs when we repeatedly choose the smallest/largest number as pivot.
- ▶ A good pivot separates the array into two (roughly) equal parts.
- ▶ If pivot gives a $[n/10, 9n/10]$ -split, we get the recurrence.

$$T(n) = T(n/10) + T(9n/10) + (n - 1)$$

- ▶ Even this gives us $\Theta(n \log n)$ number of comparisons.
- ▶ A random pivot is likely to work with probability 0.8.
- ▶ This is still an intuition.

Randomized Quicksort

Quicksort(A, s, t)

- ▶ If $s \geq t$, exit.
- ▶ Choose pivot p **uniformly at random** from $\{s, s + 1, \dots, t\}$
- ▶ $q = \text{Partition}(A, s, t, p)$.
- ▶ Quicksort($A, s, q - 1$)
- ▶ Quicksort($A, q + 1, t$)

Analysis of Randomized Quicksort

- Let the numbers in A be $z_1 < z_2 < \dots < z_n$.

Analysis of Randomized Quicksort

- ▶ Let the numbers in A be $z_1 < z_2 < \dots < z_n$.
- ▶ Let $X_{i,j}$ denote an indicator random variable for all $1 \leq i < j \leq n$.
- ▶ If z_i is compared to z_j during the execution of the algorithm, $X_{i,j} = 1$.
- ▶ Otherwise $X_{i,j} = 0$

Analysis of Randomized Quicksort

- ▶ Let the numbers in A be $z_1 < z_2 < \dots < z_n$.
- ▶ Let $X_{i,j}$ denote an indicator random variable for all $1 \leq i < j \leq n$.
- ▶ If z_i is compared to z_j during the execution of the algorithm, $X_{i,j} = 1$.
- ▶ Otherwise $X_{i,j} = 0$

The total no. of comparisons X is given by

$$X = \sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{i,j}$$

Analysis of Randomized Quicksort

- ▶ Let the numbers in A be $z_1 < z_2 < \dots < z_n$.
- ▶ Let $X_{i,j}$ denote an indicator random variable for all $1 \leq i < j \leq n$.
- ▶ If z_i is compared to z_j during the execution of the algorithm, $X_{i,j} = 1$.
- ▶ Otherwise $X_{i,j} = 0$

The total no. of comparisons X is given by

$$X = \sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{i,j}$$

- ▶ Correct because $X_{i,j}$ takes only values from $\{0, 1\}$.
- ▶ Also because no two z_i and z_j are compared more than once.

Analysis of Randomized Quicksort

- Need to calculate expected number of comparisons $E(X)$.

Analysis of Randomized Quicksort

- Need to calculate expected number of comparisons $E(X)$.

Linearity of Expectations

$$E(X) = E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{i,j} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E(X_{i,j})$$

Analysis of Randomized Quicksort

- Need to calculate expected number of comparisons $E(X)$.

Linearity of Expectations

$$E(X) = E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{i,j} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E(X_{i,j})$$

- For indicator random variable, $E(X_{i,j}) = \Pr(X_{i,j} = 1)$

Analysis of Randomized Quicksort

- Need to calculate expected number of comparisons $E(X)$.

Linearity of Expectations

$$E(X) = E \left[\sum_{i=1}^{n-1} \sum_{j=i+1}^n X_{i,j} \right] = \sum_{i=1}^{n-1} \sum_{j=i+1}^n E(X_{i,j})$$

- For indicator random variable, $E(X_{i,j}) = \Pr(X_{i,j} = 1)$
- What is the probability that z_i was compared to z_j ?

Analysis of Randomized Quicksort

- Let $Z_{i,j} = \{z_i, z_{i+1}, \dots, z_j\}$

Analysis of Randomized Quicksort

- ▶ Let $Z_{i,j} = \{z_i, z_{i+1}, \dots, z_j\}$
- ▶ z_i is compared to z_j if and only if one of them is chosen as pivot.

Analysis of Randomized Quicksort

- ▶ Let $Z_{i,j} = \{z_i, z_{i+1}, \dots, z_j\}$
- ▶ z_i is compared to z_j if and only if one of them is chosen as pivot.

Claim

$X_{i,j} = 1$ (z_i is compared to z_j) if and only if the first pivot chosen from $Z_{i,j}$ is z_i or z_j .

Analysis of Randomized Quicksort

- ▶ Let $Z_{i,j} = \{z_i, z_{i+1}, \dots, z_j\}$
- ▶ z_i is compared to z_j if and only if one of them is chosen as pivot.

Claim

$X_{i,j} = 1$ (z_i is compared to z_j) if and only if the first pivot chosen from $Z_{i,j}$ is z_i or z_j .

- ▶ As long as pivots in $Z_{i,j}$ are not chosen, z_i and z_j are never separated by the algorithm.

Analysis of Randomized Quicksort

- ▶ Let $Z_{i,j} = \{z_i, z_{i+1}, \dots, z_j\}$
- ▶ z_i is compared to z_j if and only if one of them is chosen as pivot.

Claim

$X_{i,j} = 1$ (z_i is compared to z_j) if and only if the first pivot chosen from $Z_{i,j}$ is z_i or z_j .

- ▶ As long as pivots in $Z_{i,j}$ are not chosen, z_i and z_j are never separated by the algorithm.
- ▶ If z_i or z_j is the first pivot chosen from $Z_{i,j}$, then z_i is compared to z_j .

Analysis of Randomized Quicksort

- ▶ Let $Z_{i,j} = \{z_i, z_{i+1}, \dots, z_j\}$
- ▶ z_i is compared to z_j if and only if one of them is chosen as pivot.

Claim

$X_{i,j} = 1$ (z_i is compared to z_j) if and only if the first pivot chosen from $Z_{i,j}$ is z_i or z_j .

- ▶ As long as pivots in $Z_{i,j}$ are not chosen, z_i and z_j are never separated by the algorithm.
- ▶ If z_i or z_j is the first pivot chosen from $Z_{i,j}$, then z_i is compared to z_j .
- ▶ If the first pivot is from $Z_{i,j} \setminus \{z_i, z_j\}$, then z_i and z_j are never compared.

Analysis of Randomized Quicksort

- ▶ What is the probability that z_i was compared to z_j ?

Analysis of Randomized Quicksort

- ▶ What is the probability that z_i was compared to z_j ?
- ▶ What is the probability that z_i or z_j is the first chosen pivot from $Z_{i,j}$?

Analysis of Randomized Quicksort

- ▶ What is the probability that z_i was compared to z_j ?
- ▶ What is the probability that z_i or z_j is the first chosen pivot from $Z_{i,j}$?
- ▶ Since $|Z_{i,j}| = j - i + 1$,

$$E(X_{i,j}) = \Pr(X_{i,j} = 1) = 2/(j - i + 1).$$

Analysis of Randomized Quicksort

$$\begin{aligned}E(X) &= \sum_{i=1}^{n-1} \sum_{j=i+1}^n E(X_{i,j}) \\&= \sum_{i=1}^{n-1} \sum_{j=i+1}^n 2/(j-i+1) \\&= 2 \cdot \sum_{i=1}^{n-1} \left(\frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n-i+1} \right) \\&\leq 2 \cdot \sum_{i=1}^{n-1} \left(\frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n} \right) = 2(n-1)H_n.\end{aligned}$$

Analysis of Randomized Quicksort

$$\begin{aligned}H_n &= \frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n} \\&\leq \int_1^n \frac{1}{y} dy \\&= \ln n - \ln 1 = \ln n\end{aligned}$$

Analysis of Randomized Quicksort

$$\begin{aligned}H_n &= \frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n} \\&\leq \int_1^n \frac{1}{y} dy \\&= \ln n - \ln 1 = \ln n\end{aligned}$$

- ▶ $1 + \frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n}$ is the harmonic series.
- ▶ H_n is $\Theta(\log n)$.

Analysis of Randomized Quicksort

$$\begin{aligned}H_n &= \frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n} \\&\leq \int_1^n \frac{1}{y} dy \\&= \ln n - \ln 1 = \ln n\end{aligned}$$

- ▶ $1 + \frac{1}{2} + \frac{1}{3} + \cdots + \frac{1}{n}$ is the harmonic series.
- ▶ H_n is $\Theta(\log n)$.

$$E(X) = 2(n-1)H_n = \Theta(n \log n).$$

Randomized Quicksort

Theorem

Randomized Quicksort correctly sorts the input array in-place and requires $\Theta(n \log n)$ comparisons **in expectation**.

Randomized Quicksort

Theorem

Randomized Quicksort correctly sorts the input array in-place and requires $\Theta(n \log n)$ comparisons **in expectation**.

- ▶ Can still take $\Theta(n^2)$ time in worst case.
- ▶ But with low probability.

Randomized Quicksort


Theorem

Randomized Quicksort correctly sorts the input array in-place and requires $\Theta(n \log n)$ comparisons **in expectation**.

- ▶ Can still take $\Theta(n^2)$ time in worst case.
- ▶ But with low probability.
- ▶ Instead of random pivot choice each time, we could also permute the input in a random order at the beginning and then choose first element as pivot.
- ▶ These two processes are equivalent.


Back to BST Sort: What is the connection?

Consider the sequence 3, 1, 8, 2, 6, 7, 5



Back to BST Sort: What is the connection?


Consider the sequence 3, 1, 8, 2, 6, 7, 5



What are the comparisons if we ran det. quicksort with the first element as pivot?

Back to BST Sort: What is the connection?

Consider the sequence 3, 1, 8, 2, 6, 7, 5



What are the comparisons if we ran det. quicksort with the first element as pivot?

Exactly the same!

Randomize!

- ▶ The comparisons for BST sort are the same comparisons that happen in quicksort!
- ▶ In worst case, we can have $O(n^2)$ comparisons
- ▶ What if we randomize?

Randomize!

- ▶ The comparisons for BST sort are the same comparisons that happen in quicksort!
 - ▶ In worst case, we can have $O(n^2)$ comparisons
 - ▶ What if we randomize?
-
- ▶ We randomly permute the input sequence before insertion
 - ▶ The total no. of comparisons are the same as that of randomized quicksort
 - ▶ The running time of random BST Sort is thus $O(n \log n)$

What does this tell us about the randomly built BST?

- Depth of a node = No. of comparisons while INSERT.

$$\begin{aligned}\text{Average node depth} &= \frac{1}{n} \sum_{\text{node } i} \text{Depth of node } i \\ &= \frac{1}{n} \sum_{\text{node } i} \text{No. of comp. while inserting node } i \\ E(\text{Avg. node depth}) &= \frac{1}{n} E \left(\sum_{\text{node } i} \text{No. of comp. while inserting node } i \right) \\ &= \frac{1}{n} O(n \log n) \\ &= O(\log n)\end{aligned}$$

By quicksort

Randomly built BST

- ▶ Expected average node depth = $O(\log n)$
- ▶ What about about expected height?
- ▶ Does $O(\log n)$ average depth imply $O(\log n)$ height?

Randomly built BST

- ▶ Expected average node depth = $O(\log n)$
- ▶ What about about expected height?
- ▶ Does $O(\log n)$ average depth imply $O(\log n)$ height?
- ▶ No!

Relation between average depth and height

- ▶ Consider a BST in which $n - \sqrt{n}$ nodes form a complete binary tree and the remaining \sqrt{n} nodes form a chain
- ▶ Height is \sqrt{n}
- ▶ Average node depth is


$$\leq \frac{1}{n} \left(n \log n + \frac{\sqrt{n} \cdot \sqrt{n}}{2} \right) = \frac{n \log n}{n} \approx O(\log n)$$

Relation between average depth and height

- ▶ Consider a BST in which $n - \sqrt{n}$ nodes form a complete binary tree and the remaining \sqrt{n} nodes form a chain
- ▶ Height is \sqrt{n}
- ▶ Average node depth is

$$\leq \frac{1}{n} \left(n \log n + \frac{\sqrt{n} \cdot \sqrt{n}}{2} \right) = \frac{n \log n}{n} \approx O(\log n)$$

- ▶ Low average depth does not imply low height.



Complete binary tree with $n - \sqrt{n}$ nodes

Height = \sqrt{n}

Expected height of randomly built BST

- ▶ We saw that in general, low average depth does not imply low height.
- ▶ However, in the case of randomly built BSTs, we can show that the expected height is also $O(\log n)$.
- ▶ This proof is more involved, and can be found in CLRS.
- ▶ If anyone is interested, you can meet me.