

Deep Q Networks

Easwar Subramanian

TCS Innovation Labs, Hyderabad

Email : easwar.subramanian@tcs.com / cs5500.2020@iith.ac.in


October 11, 2021

- 1 Review
- 2 Convergence of Approximation Methods
- 3 Towards a Stable Deep Q Network Algorithm
- 4 Efficacy of DQN Algorithm

Review

- ▶ Value function evaluation in tabular RL methods have been basically lookup tables.
- ▶ Solution for large MDP's is to use function approximators
 - ★ Generalize from seen to unseen states
- ▶ Function approximators could be
 - ★ Linear function approximator
 - ★ Neural networks
 - ★ Decision tree
 - ★ ...

Neural Network Approximators



The value of a policy π is given by

$$\begin{aligned} V^\pi(s) &= \mathbb{E}_\pi \left(\sum_{k=0}^{\infty} \gamma^k r_{t+k+1} | s_t = s \right) \\ &= \mathbb{E}_\pi [r_{t+1} + \gamma V^\pi(s_{t+1}) | s_t = s] \end{aligned}$$

We collect training data by evaluating the experiences using samples

- ▶ Value function fitting using Monte Carlo
- ▶ Fitted V Iteration

- ▶ For transitions (s, a, r, s') we can compute targets as $r + \gamma \max_{a'} Q(s', a')$
- ▶ Does not require simulating over actions
- ▶ Use the previous fitted optimal Q function Q_ϕ^* like in fitted V iteration
- ▶ Collect training data,

$$\left(\begin{array}{c} s_i, \underbrace{r + \gamma \max_{a'} Q_\phi(s'_i, a'_i)}_{=y_i} \end{array} \right)$$

- ▶ Perform supervised regression

$$L(\phi) = \frac{1}{2} \sum_{i=1}^N [Q_\phi(s_i, a_i) - y_i]^2$$

Algorithm Fitted Q Iteration

- 1: Initialize number of iterations N
- 2: **for** $j = 1$ to N **do**
- 3: Sample K transitions (s, a, r, s') using any behaviour policy μ
- 4: **for** $i = 1$ to K **do**
- 5: Calculate targets y_i using one step TD approximation

$$y_i = \left[r + \gamma \max_{a'} Q_{\phi_j}(s'_i, a') \right]$$

- 6: Form input-output pairs (s_i, y_i) (K Datapoints in total)
- 7: **end for**
- 8: Perform supervised regression (Optimizer : RProp) using loss function

$$L(\phi_j) = \frac{1}{2} \sum_{i=1}^K \left[Q_{\phi_j}(s_i, a_i) - y_i \right]^2$$

and get a new function approximator with new weights ϕ_{j+1}

- 9: **end for**

Convergence of Approximation Methods

On the Convergence of Fitted Iterations

Question : What can we say about the convergence of fitted iteration methods ?

- ▶ Does fitted V iteration converge to V^π ?
- ▶ Does neural fitted iteration converge to Q_* ?

Convergence in DP setup


- ▶ Use the fixed point equation below to define a **contraction** operator \mathcal{L} (contraction in L_∞ norm)

$$Q_*(s, a) \leftarrow \left[\sum_{s' \in \mathcal{S}} \mathcal{P}_{ss'}^a \left(\mathcal{R}_{ss'}^a + \gamma \max_{a'} Q_*(s', a') \right) \right]$$

Convergence in TD setup

- ▶ State and action spaces are finite
- ▶ All state-action pairs are visited infinitely often
- ▶ Robbins-Monroe condition: $\sum_t \alpha_t = \infty, \sum_t \alpha_t^2 < \infty$

Space of Q Functions



- Define operator $\mathcal{L} : \mathcal{Q} \rightarrow \mathcal{Q}$ such that

$$\mathcal{L}Q = r + \gamma \max_{a'} Q(s', a')$$

- Backup operator \mathcal{L} is a contraction in L_∞ norm
- Projection operator (Π) are contractions in L_2 norm
- What about the composition $(\Pi \circ \mathcal{L})Q$?
 - ★ Need not be a contraction with respect to any norm

Sad Corollary

No guarantees on convergence to optimal value functions (on the manifold) exist for fitted iteration methods

Algorithm Monte Carlo Based Value Function Fitting

- 1: Initialize number of iterations N
- 2: **for** $i = 1$ to N **do**
- 3: Perform a roll-out from an initial state s_i (could be any state from \mathcal{S})
- 4: Calculate targets y_i using Monte-Carlo roll outs

$$y_i = \left[\sum_{k=0}^H \left(\gamma^k r_{t+k+1}^i | s_t = s_i \right) \right]$$

- 5: Form input-output pairs (s_i, y_i) (N datapoints in total)
- 6: **end for**
- 7: Perform supervised regression with loss function

$$L(\phi) = \frac{1}{2} \sum_{i=1}^N [V_{\phi}^{\pi}(s_i) - y_i]^2$$

- ▶ Step 7 is gradient descent and it will converge at least local optimum
- ▶ Important : **Convergence guarantee is in the parameter space (ϕ) and not in value function space**

Algorithm Fitted Q Iteration

- 1: Initialize number of iterations N
- 2: **for** $j = 1$ to N **do**
- 3: Sample K transitions (s, a, r, s') using any behaviour policy μ
- 4: **for** $i = 1$ to K **do**
- 5: Calculate targets y_i using one step TD approximation

$$y_i = \left[r + \gamma \max_{a'} Q_{\phi_j}(s'_i, a') \right]$$

- 6: Form input-output pairs (s_i, y_i) (K Datapoints in total)
- 7: **end for**
- 8: Perform supervised regression (Optimizer : RProp) using loss function

$$L(\phi_j) = \frac{1}{2} \sum_{i=1}^K \left[Q_{\phi_j}(s_i, a_i) - y_i \right]^2$$

and get a new function approximator with new weights ϕ_{j+1}

- 9: **end for**

Question : Can we do the gradient update for every transition (s, a, r, s') ?

- ▶ We use the fitted Q iteration and set $K = 1$
- ▶ This is also the Watkins Q-learning update (used with function approximators)

Algorithm Online Q Learning

- 1: **for** $n = 1$ to N **do**
- 2: Take an action a and obtain the transition (s, a, r, s') using ϵ -greedy policy
- 3: Calculate target y using one step TD approximation

$$y = \left[r + \gamma \max_{a'} Q_{\phi_n}(s', a') \right]$$

- 4: Compute $g^{(n)} = \nabla_{\phi} (Q_{\phi_n}(s, a) - y)^2$
 - 5: Set $\phi_{n+1} = \phi_n - \alpha g^{(n)}$
 - 6: **end for**
-

Algorithm Online Q Learning

- 1: **for** $n = 1$ to N **do**
- 2: Take an action a and obtain the transition (s, a, r, s') using ϵ -greedy policy
- 3: Calculate target y using one step TD approximation

$$y = \left[r + \gamma \max_{a'} Q_{\phi_n}(s', a') \right]$$

- 4: Compute $g^{(n)} = \nabla_{\phi}(Q_{\phi_n}(s, a) - y)$
 - 5: Set $\phi_{n+1} \leftarrow \underbrace{\phi_n - \alpha g^{(n)}}_{\text{Is this GD ?}}$
 - 6: **end for**
-


- Take a closer look at the one step gradient

$$g^{(n)} \leftarrow \phi_n - \alpha \nabla_{\phi} \left(Q_{\phi}(s, a) - \underbrace{r + \gamma \max_{a'} Q_{\phi}(s', a')}_{\text{moving target}} \right)$$

- ▶ Projection (Π) of the backup operator (\mathcal{L}) of optimal Q function need not be a contraction in any norm
- ▶ Fitted V iteration or fitted Q iteration need not converge because of the moving target problem
- ▶ In online Q learning algorithm,
 - ★ Samples obtained are sequentially correlated
 - ★ Moving target problem
- ▶ **Convergence guarantees exist only in tabular case**


Towards a Stable Deep Q Network Algorithm

- ▶ Online algorithm like Q-learning in tabular case
- ▶ No sequential correlation in data samples
- ▶ Some stability with respect to gradient updates




- Correlated samples will overestimate segments and will eventually be a bad fit to the regression problem

- Use the idea from fitted Q-iteration to collect and store transitions (s, a, s', r)



- Stored transition dataset is called **Replay Buffer** denoted by D
- Replay buffers are of fixed size (N)



- ▶ In an online setting, use ϵ -greedy policy to periodically feed the buffer with newer experiences
- ▶ Use FIFO like mechanism to maintain size
- ▶ Sample a random minibatch of transitions (B transitions) to perform gradient descent (random sampling ensure samples for SGD are no longer correlated)
- ▶ Variance of the gradient estimate is also low compared to gradient computed using one sample


- ▶ Use an older set of weights to compute the targets
- ▶ Called **Target Network**
- ▶ Loss term is given by

$$L_i(\phi_i) = \left[\mathbb{E}_{(s,a,r,s') \in D} \left(Q_{\phi_i}(s,a) - \underbrace{r + \max_{a'} Q_{\phi'_i}(s',a')}_{\text{target}} \right)^2 \right]$$

- ▶ Target network is kept constant for a while (every C steps) before being changed
 - ★ Every C steps the weights of the original network is copied to target network

Algorithm DQN Algorithm

- 1: Initialize replay memory D to capacity N
 - 2: Initialize action value function Q with parameters ϕ
 - 3: Initialize target action value function \hat{Q} with parameters $\phi' = \phi$
 - 4: **for** episodes = 1 to M **do**
 - 5: Initialize start state s_1
 - 6: **for** steps $t = 1$ to T **do**
 - 7: Select action a_t using ϵ -greedy policy
 - 8: Execute action a_t and store transition (s_t, a_t, r_t, s_{t+1}) in D
 - 9: Sample random minibatch (size B) of transitions from D
 - 10: **for** $b = 1$ to B **do**
 - 11: Calculate targets for each transitions (Bellman backup or reward)
 - 12: **end for**
 - 13: Perform a gradient descent step on $(y_i - Q_\phi(s_t, a_t))^2$ w.r.t ϕ
 - 14: Every C steps set $\hat{Q} = Q$
 - 15: **end for**
 - 16: **end for**
-



Polyak Averaging

- Replace target network update step (Step 14) by

$$\phi' : \phi' \leftarrow \tau \phi' + (1 - \tau) \phi$$


- Typical value for $\tau = 0.99$

Efficacy of DQN Algorithm

- ▶ Mnih et al. introduced Deep Q-Network (DQN) algorithm, applied it to ATARI games
- ▶ Used deep learning / ConvNets, published in early stages of deep learning craze (one year after AlexNet)
- ▶ Popularized ATARI (Bellemare et al., 2013) as RL benchmark
- ▶ Outperformed baseline methods, which used hand-crafted features

²Slide content from Schulman

DQN on Atari ²




Pong



Enduro




Beamrider



Q*bert


- ▶ 49 ATARI 2600 games
- ▶ From pixels to actions
- ▶ The change in score is the reward
- ▶ Same algorithm
- ▶ Same function approximator
- ▶ Same hyperparameters
- ▶ Roughly human-level performance on 29 out of 49 games

²Slide content from Minh



- Convolutional neural network architecture
- History of 4 frames as input
- One output per action ($Q(s, a)$) – expected reward for action a

Profile of Q Function Approximator



Demonstration - Ping Pong

Random Policy


After 5.2 Millon Epochs

Demonstration - Ping Pong

After 8 Million Epochs

After 9.5 Millon Epochs

Are the Q-Values Meaningful ?



On Tracking the Training Process

