

Code1:

```
#define GreenLed 13
```

```
#define Sensor A0
```

```
void setup()
```

```
{
```

```
    pinMode(13, OUTPUT);
```

```
    pinMode(12, OUTPUT);
```

```
    pinMode(A0, INPUT);
```

```
    Serial.begin(9600);
```

```
}
```

```
void loop()
```

```
{
```

```
    int value = analogRead(A0);
```

```
    Serial.print("Analogic Value coming from the sensor : ");
```

```
    Serial.println(value);
```

```
    delay(100);
```

```
    if (value > 600)
```

```
    {
```

```
        digitalWrite(13, HIGH);
```

```
    }
```

```
else
{
    digitalWrite(13, LOW);
}

    delay(20);
}
```

Code 2:

```
int mq6Pin = A0; // MQ6 analog pin connected to A0
```

```
void setup()
{
    Serial.begin(9600);
}
```

```
void loop()
{
    int sensorValue = analogRead(mq6Pin);

    Serial.print("MQ6 Sensor Value: ");
    Serial.println(sensorValue);

    delay(1000); // 1-second delay
}
```

The screenshot displays the Proteus 8 Professional interface. The main workspace shows a schematic diagram of an Arduino Uno microcontroller board connected to an MQ-6 gas sensor module. The sensor module includes a blue PCB with a circular sensor element, labeled 'GAS1 MQ-6 GAS SENSOR'. It is powered by a 5V regulator (RV1) and its output is connected to Arduino pin A0. A virtual terminal window in the top right corner displays a list of analog values from the sensor, ranging from 77 to 1008. The status bar at the bottom indicates 'ANIMATING: 00:00:23.806403 (CPU load 64%)'.