

Assignment 1

1. Create 'spj' database'. (Database for suppliers, parts and Jobs.
2. use spj database;
3. Create following tables in spj database.

```
D5_96444_Mahesh> show databases;
+-----+
| Database |
+-----+
| classwork |
| hr        |
| information_schema |
| joins     |
| performance_schema |
| sales     |
| spj       |
+-----+
7 rows in set (0.15 sec)
```

```
D5_96444_Mahesh> INSERT INTO P VALUES
-> ('P1', 'Nut', 'Red', 12, 'London'),
-> ('P2', 'Bolt', 'Green', 17, 'Paris'),
-> ('P3', 'Screw', 'Blue', 17, 'Rome'),
-> ('P4', 'Screw', 'Red', 14, 'London'),
-> ('P5', 'Cam', 'Blue', 12, 'Paris'),
-> ('P6', 'Cog', 'Red', 19, 'London');
Query OK, 6 rows affected (0.08 sec)
Records: 6  Duplicates: 0  Warnings: 0
```

```
D5_96444_Mahesh> INSERT INTO J VALUES
-> ('J1', 'Sorter', 'Paris'),
-> ('J2', 'Punch', 'Rome'),
-> ('J3', 'Reader', 'Athens'),
-> ('J4', 'Console', 'Athens'),
-> ('J5', 'Collator', 'London'),
-> ('J6', 'Terminal', 'Oslo'),
-> ('J7', 'Tape', 'London');
Query OK, 7 rows affected (0.02 sec)
Records: 7  Duplicates: 0  Warnings: 0
```

```
D5_96444_Mahesh> INSERT INTO S VALUES
-> ('S1', 'Smith', 20, 'London'),
-> ('S2', 'Jones', 10, 'Paris'),
-> ('S3', 'Blake', 30, 'Paris'),
-> ('S4', 'Clark', 20, 'London'),
-> ('S5', 'Adams', 30, 'Athens');
Query OK, 5 rows affected (0.02 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
D5_96444_Mahesh>
```

```
D5_96444_Mahesh> show tables;
```

```
+-----+
```

```
| Tables_in_spj |
```

```
+-----+
```

```
| j |
```

```
| p |
```

```
| s |
```

```
+-----+
```

```
3 rows in set (0.14 sec)
```

```
D5_96444_Mahesh>
```