bddd-automation master TestRunner Unlock Ultimate

Project BaseTest.java TestContext.java log4j2.xml TestDataBuilder.java UserSteps.java crossendpoint.feature inventory.feature Cross

Terminal Local

```
PS C:\Users\akula\IdeaProjects\bddd-automation> mvn clean test
[INFO] Scanning for projects...
[INFO]
[INFO] --------------------< api.automation:bdd-framework >--------------------
[INFO] Building bdd-framework 1.0
[INFO]   from pom.xml
[INFO] --------------------------------[ jar ]---------------------------------
[INFO]
[INFO] --- clean:3.2.0:clean (default-clean) @ bdd-framework ---
[INFO] Deleting C:\Users\akula\IdeaProjects\bddd-automation\target
[INFO]
[INFO] --- resources:3.4.0:resources (default-resources) @ bdd-framework ---
[INFO] skip non existing resourceDirectory C:\Users\akula\IdeaProjects\bddd-automation\src\main\resources
[INFO]
[INFO] --- compiler:3.15.0:compile (default-compile) @ bdd-framework ---
[INFO] Nothing to compile - all classes are up to date.
[INFO]
[INFO] --- resources:3.4.0:testResources (default-testResources) @ bdd-framework ---
[INFO] Copying 7 resources from src\test\resources to target\test-classes
[INFO]
[INFO] --- compiler:3.15.0:testCompile (default-testCompile) @ bdd-framework ---
[INFO] Recompiling the module because of changed source code.
[INFO] Compiling 10 source files with javac [debug target 11] to target\test-classes
[WARNING] system modules path not set in conjunction with -source 11
[INFO]
[INFO] --- surefire:3.0.0:test (default-test) @ bdd-framework ---
[INFO] Using auto detected provider org.apache.maven.surefire.testng.TestNGProvider
[INFO]
[INFO] -------------------------------------------------------
[INFO]  T E S T S
[INFO] -------------------------------------------------------
[INFO] Running TestSuite
SLF4J: Failed to load class "org.slf4j.impl.StaticLoggerBinder".
SLF4J: Defaulting to no-operation (NOP) logger implementation
SLF4J: See http://www.slf4j.org/codes.html#StaticLoggerBinder for further details.

Scenario: Validate pet exists in sold list                    # src/test/resources/features/crossendpoint.feature:3
```

bddd-automation master TestRunner Unlock Ultimate

Project BaseTest.java TestContext.java log4j2.xml TestDataBuilder.java UserSteps.java crossendpoint.feature inventory.feature

Terminal Local

```
[INFO] -------------------------------------------------------
[INFO] Running TestSuite
SLF4J: Failed to load class "org.slf4j.impl.StaticLoggerBinder".
SLF4J: Defaulting to no-operation (NOP) logger implementation
SLF4J: See http://www.slf4j.org/codes.html#StaticLoggerBinder for further details.

Scenario: Validate pet exists in sold list                          # src/test/resources/features/crossendpoint.feature:3
[INFO] 11:33:02 - Creating Pet: pet_1776405782642
  Given I create a pet with name "pet_<timestamp>" and status "available" # stepdefinitions.PetSteps.createPet(java.lang.String,java.lang.String)
[INFO] 11:33:06 - Status Code: 200
  Then API response should be successful                            # stepdefinitions.PetSteps.validateSuccess()
[INFO] 11:33:07 - Stored Pet ID: 1776405782642
  And I store pet id from response                                  # stepdefinitions.PetSteps.storeId()
[INFO] 11:33:07 - Updating Pet ID: 1776405782642 -> sold
  When I update pet status to "sold"                                # stepdefinitions.PetSteps.updatePet(java.lang.String)
[INFO] 11:33:09 - Status Code: 200
  Then API response should be successful                            # stepdefinitions.PetSteps.validateSuccess()
[INFO] 11:33:09 - Fetching pets with status: sold
  When I fetch pets with status "sold"                              # stepdefinitions.InventorySteps.fetchPets(java.lang.String)
[INFO] 11:33:10 - Pet List Status: 200
  Then pet list response should be successful                       # stepdefinitions.InventorySteps.validatePetList()
[INFO] 11:33:10 - Searching for Pet ID: 1776405782642
  When I search for stored pet id in list                           # stepdefinitions.CrossEndPointSteps.searchPet()
[INFO] 11:33:10 - Pet found in sold list
  Then pet should exist in the list                                 # stepdefinitions.CrossEndPointSteps.validateFound()

Scenario: Compare inventory and API list       # src/test/resources/features/inventory.feature:3
[INFO] 11:33:11 - Fetching inventory...
  Given I fetch inventory                      # stepdefinitions.InventorySteps.fetchInventory()
[INFO] 11:33:12 - Inventory Status: 200
  Then inventory response should be successful # stepdefinitions.InventorySteps.validateInventory()
[INFO] 11:33:12 - Inventory Available Count: 572
  And I extract available count                # stepdefinitions.InventorySteps.extractAvailable()
[INFO] 11:33:12 - Fetching pets with status: available
  When I fetch pets with status "available"    # stepdefinitions.InventorySteps.fetchPets(java.lang.String)
[INFO] 11:33:14 - Pet List Status: 200
  Then pet list response should be successful  # stepdefinitions.InventorySteps.validatePetList()
```

bddd-automation master TestRunner Unlock Ultimate

Project BaseTest.java TestContext.java log4j2.xml TestDataBuilder.java UserSteps.java crossendpoint.feature inventory.feature Cross

Terminal Local

```
[INFO] 11:33:12 - Fetching pets with status: available
  When I fetch pets with status "available"    # stepdefinitions.InventorySteps.fetchPets(java.lang.String)
[INFO] 11:33:14 - Pet List Status: 200
  Then pet list response should be successful  # stepdefinitions.InventorySteps.validatePetList()
[INFO] 11:33:14 - Pet List Count: 572
  And I count pets in list                     # stepdefinitions.InventorySteps.countPets()
[INFO] 11:33:14 - Comparing counts -> Inventory: 572 | List: 572
  Then both counts should match                # stepdefinitions.InventorySteps.validateCounts()

Scenario: Create Pet                                                # src/test/resources/features/pet.feature:3
[INFO] 11:33:14 - Creating Pet: pet_1776405794786
  Given I create a pet with name "pet_<timestamp>" and status "available" # stepdefinitions.PetSteps.createPet(java.lang.String,java.lang.String)
[INFO] 11:33:16 - Status Code: 200
  Then API response should be successful                            # stepdefinitions.PetSteps.validateSuccess()
[INFO] 11:33:16 - Stored Pet ID: 1776405794786
  And I store pet id from response                                  # stepdefinitions.PetSteps.storeId()

Scenario: Get Pet                                                   # src/test/resources/features/pet.feature:8
[INFO] 11:33:16 - Creating Pet: pet_1776405796087
  Given I create a pet with name "pet_<timestamp>" and status "available" # stepdefinitions.PetSteps.createPet(java.lang.String,java.lang.String)
[INFO] 11:33:17 - Stored Pet ID: 1776405796087
  And I store pet id from response                                  # stepdefinitions.PetSteps.storeId()
[INFO] 11:33:17 - Fetching Pet ID: 1776405796087
  When I get the pet by stored id                                   # stepdefinitions.PetSteps.getPet()
[INFO] 11:33:18 - Expected Name: pet_1776405796087
[INFO] 11:33:18 - Actual Name: pet_1776405796087
  Then pet name should match stored name                            # stepdefinitions.PetSteps.validateName()
[INFO] 11:33:18 - Expected Status: available
[INFO] 11:33:18 - Actual Status: available
  And pet status should be "available"                              # stepdefinitions.PetSteps.validateStatus(java.lang.String)

Scenario: Update Pet                                                # src/test/resources/features/pet.feature:16
[INFO] 11:33:18 - Creating Pet: pet_1776405798738
  Given I create a pet with name "pet_<timestamp>" and status "available" # stepdefinitions.PetSteps.createPet(java.lang.String,java.lang.String)
[INFO] 11:33:20 - Stored Pet ID: 1776405798738
  And I store pet id from response                                  # stepdefinitions.PetSteps.storeId()
[INFO] 11:33:20 - Updating Pet ID: 1776405798738 -> sold
```

bddd-automation master TestRunner Unlock Ultimate

Project BaseTest.java TestContext.java log4j2.xml TestDataBuilder.java UserSteps.java crossendpoint.feature inventory.feature Cross

Terminal Local

```
  Given I create a pet with name "pet_<timestamp>" and status "available" # stepdefinitions.PetSteps.createPet(java.lang.String,java.lang.String)
[INFO] 11:33:20 - Stored Pet ID: 1776405798738
  And I store pet id from response                                        # stepdefinitions.PetSteps.storeId()
[INFO] 11:33:20 - Updating Pet ID: 1776405798738 -> sold
  When I update pet status to "sold"                                      # stepdefinitions.PetSteps.updatePet(java.lang.String)
[INFO] 11:33:21 - Status Code: 200
  Then API response should be successful                                  # stepdefinitions.PetSteps.validateSuccess()

Scenario: Delete Pet                                                      # src/test/resources/features/pet.feature:22
[INFO] 11:33:21 - Creating Pet: pet_1776405801421
  Given I create a pet with name "pet_<timestamp>" and status "available" # stepdefinitions.PetSteps.createPet(java.lang.String,java.lang.String)
[INFO] 11:33:22 - Stored Pet ID: 1776405801422
  And I store pet id from response                                        # stepdefinitions.PetSteps.storeId()
[INFO] 11:33:22 - Deleting Pet ID: 1776405801422
  When I delete the pet                                                   # stepdefinitions.PetSteps.deletePet()
[INFO] 11:33:24 - Status Code: 200
  Then API response should be successful                                  # stepdefinitions.PetSteps.validateSuccess()

Scenario: Invalid user creation (logical validation) # src/test/resources/features/user.feature:4
[INFO] 11:33:24 - Creating user: user_1776405804226
  When I create user with email "invalid_email"      # stepdefinitions.UserSteps.createInvalidUser(java.lang.String)
[INFO] 11:33:25 - User creation status: 200
  Then response should contain created username      # stepdefinitions.UserSteps.validateUserCreated()
[INFO] 11:33:25 - Validating email format behavior
  And response should not validate email format      # stepdefinitions.UserSteps.validateEmailNotChecked()

Scenario: Fetch non-existent user                   # src/test/resources/features/user.feature:9
[INFO] 11:33:25 - Fetching user: user_1776405805854
  When I fetch user "user_<timestamp>"              # stepdefinitions.UserSteps.fetchUser(java.lang.String)
[INFO] 11:33:27 - Fetch Status: 404
  Then user should not be found                     # stepdefinitions.UserSteps.userNotFound()
[INFO] 11:33:27 - Error response: {"code":1,"type":"error","message":"User not found"}
  And error message should contain "User not found" # stepdefinitions.UserSteps.errorMessage(java.lang.String)

Scenario: Invalid login                                           # src/test/resources/features/user.feature:14
[INFO] 11:33:27 - Attempting login for: wrong_1776405807351
  When I login with username "wrong_<timestamp>" and password "wrong" # stepdefinitions.UserSteps.invalidLogin(java.lang.String,java.lang.String)
```

bddd-automation master TestRunner Unlock Ultimate

Project BaseTest.java TestContext.java log4j2.xml TestDataBuilder.java UserSteps.java crossendpoint.feature inventory.feature Cross

Terminal Local

```
[INFO] 11:33:24 - Status Code: 200
  Then API response should be successful                                # stepdefinitions.PetSteps.validateSuccess()

Scenario: Invalid user creation (logical validation) # src/test/resources/features/user.feature:4
[INFO] 11:33:24 - Creating user: user_1776405804226
  When I create user with email "invalid_email"      # stepdefinitions.UserSteps.createInvalidUser(java.lang.String)
[INFO] 11:33:25 - User creation status: 200
  Then response should contain created username      # stepdefinitions.UserSteps.validateUserCreated()
[INFO] 11:33:25 - Validating email format behavior
  And response should not validate email format      # stepdefinitions.UserSteps.validateEmailNotChecked()

Scenario: Fetch non-existent user                   # src/test/resources/features/user.feature:9
[INFO] 11:33:25 - Fetching user: user_1776405805854
  When I fetch user "user_<timestamp>"               # stepdefinitions.UserSteps.fetchUser(java.lang.String)
[INFO] 11:33:27 - Fetch Status: 404
  Then user should not be found                      # stepdefinitions.UserSteps.userNotFound()
[INFO] 11:33:27 - Error response: {"code":1,"type":"error","message":"User not found"}
  And error message should contain "User not found" # stepdefinitions.UserSteps.errorMessage(java.lang.String)

Scenario: Invalid login                                             # src/test/resources/features/user.feature:14
[INFO] 11:33:27 - Attempting login for: wrong_1776405807351
  When I login with username "wrong_<timestamp>" and password "wrong" # stepdefinitions.UserSteps.invalidLogin(java.lang.String,java.lang.String)
[INFO] 11:33:27 - Login Status: 401
  Then login should fail logically                                  # stepdefinitions.UserSteps.loginFailLogical()
[INFO] Tests run: 9, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 26.988 s - in TestSuite
[INFO]
[INFO] Results:
[INFO]
[INFO] Tests run: 9, Failures: 0, Errors: 0, Skipped: 0
[INFO]
[INFO] ------------------------------------------------------------------------
[INFO] BUILD SUCCESS
[INFO] ------------------------------------------------------------------------
[INFO] Total time:  33.090 s
[INFO] Finished at: 2026-04-17T11:33:28+05:30
[INFO] ------------------------------------------------------------------------
PS C:\Users\akula\IdeaProjects\bddd-automation>
```

bddd-automation > src > test > resources > log4j2.xml 16:17 CRLF UTF-8 4 spaces