

## Conditional Visibility:

### Important notes:

1. Conditional logic applicable for **blocks, pages, and fields**.
2. Conditional Operators are:

| Control Type                  | Recommended Operators                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Textbox / Text Area           | Equals, Not Equals, Contains, Does Not Contain, Starts With, Ends With, Is Empty, Is Not Empty                  |
| Number Field                  | Equals, Not Equals, Greater Than, Less Than, Greater Than or Equal To, Less Than or Equal To, Between, Is Empty |
| Date Picker                   | Equals, Before, After, Between, Is Empty                                                                        |
| Dropdown (Single Select)      | Equals, Not Equals, In List, Not In List, Is Empty                                                              |
| Dropdown (Multi Select)       | Contains, Does Not Contain, Includes Any, Includes All, Is Empty                                                |
| Radio Button                  | Equals, Not Equals                                                                                              |
| Checkbox (Single)             | Checked, Unchecked                                                                                              |
| Checkbox Group                | Contains, Does Not Contain, Includes Any, Includes All                                                          |
| Slider                        | Equals, Greater Than, Less Than, Between                                                                        |
| Toggle / Switch               | On, Off                                                                                                         |
| Time Picker                   | Equals, Before, After, Between                                                                                  |
| File Upload                   | Uploaded, Not Uploaded                                                                                          |
| Signature Field               | Signed, Not Signed                                                                                              |
| Email Field                   | Equals, Contains, Ends With, Is Empty                                                                           |
| Phone Number Field            | Equals, Contains, Starts With, Is Empty                                                                         |
| Auto Complete / Search Select | Equals, Not Equals, Contains                                                                                    |
| Calculated Field              | Equals, Greater Than, Less Than, Between                                                                        |

### Conditional Visibility for Blocks

3. For a Block, choose **Conditional Visibility**
  - a. To apply conditional logic at least one block with pages and fields should exists.
  - b. In window there are 3 options (Block, Page, Fields). Default
  - c. Select the visible criteria (Show, Hide, Read-only)
  - d. Configure a condition by choosing a Block, Page, and Field. Ability to configure multiple conditions with AND, OR operators
  - e. Click on Save
4. **Expected Result:** In study workspace, when the configured option is chosen then the block is either show/ hide/ read-only.

---

### • Configure Conditional Logic – Show / Hide / Read-Only

#### Objective

The system shall allow users to configure conditional logic for fields, pages, and blocks based on selected criteria and field values.

#### Functionalities

| Functionality | Description                                                      |
|---------------|------------------------------------------------------------------|
| Show          | Display a field/page/block when condition is satisfied           |
| Hide          | Hide a field/page/block when condition is satisfied              |
| Read-Only     | Make a field/page/block non-editable when condition is satisfied |

#### Configuration Flow

##### Step 1 – Select Block

User selects the Block Name.

Example:  
Block: Adverse Events

### Step 2 – Select Page under Block

System displays pages available under the selected block.

Example:  
Page: Serious Adverse Event Form

### Step 3 – Select Field under Page

System displays fields available under the selected page.

Example:  
Field: Hospitalization Required

### Step 4 – Configure Condition

User defines:

- Source field
- Condition operator
- Expected value
- Action

#### Example – Show Logic

| Configuration Item | Value                      |
|--------------------|----------------------------|
| Block              | Adverse Events             |
| Page               | Serious Adverse Event Form |
| Source Field       | Serious Event              |
| Condition          | Equals                     |
| Value              | Yes                        |
| Action             | Show                       |
| Target Field       | Hospitalization Details    |

#### Behaviour

- If:
- Serious Event = Yes
- Then:
- Show "Hospitalization Details" field

#### Example – Hide Logic

| Configuration Item | Value             |
|--------------------|-------------------|
| Source Field       | Pregnancy Status  |
| Condition          | Equals            |
| Value              | No                |
| Action             | Hide              |
| Target Field       | Pregnancy Details |

#### Behaviour

- If Pregnancy Status = No  
→ Hide Pregnancy Details field

#### Example – Read-Only Logic

| Configuration Item | Value          |
|--------------------|----------------|
| Source Field       | Subject Status |

|                    |                |
|--------------------|----------------|
| <b>Condition</b>   | Equals         |
| <b>Value</b>       | Completed      |
| <b>Action</b>      | Read-Only      |
| <b>Target Page</b> | Follow-Up Form |

#### **Behaviour**

- If Subject Status = Completed  
→ Follow-Up Form becomes Read-Only

#### **Recommended Business Rules**

1. This is a reusable component for all type of controls
2. Conditional logic should support:
  - Field level
  - Page level
  - Block level
3. Supported actions:
  - Show
  - Hide
  - Read-Only
4. Multiple conditions should be supported optionally.
5. Conditional logic evaluation should occur:
  - On field change
  - On form load
  - On save/submit
6. Hidden fields should optionally:
  - Clear data automatically
  - Retain existing data (configurable).