

# Movie Chatbot Development Process

## Demo:



## 1. Domain Selection

**Application:** Movie Chatbot

### Scope and Data Type:

- The application will handle data related to movies, including movie overview, genres, release dates, and ratings.
- The chatbot will respond to user queries about movies, provide recommendations, and offer information about movie details.

## 2. Data Collection and Preprocessing

**Data Source:** Kaggle dataset on movies, Prompt Engineering to get mock data

### Steps:

1. **Acquire Data:** Download the movie dataset from [Kaggle](#).
2. **Data Cleaning:**
  - Remove any irrelevant columns or information not needed for the chatbot.
  - Handle missing data by filling in defaults or removing incomplete entries.

- Generate missing plots of movies using LLM.
3. **Text Preparation:**
- Remove special characters and unnecessary whitespace.
  - Address missing by prompt - engineering.

### 3. Vector Database Implementation

**Chosen Database: Pinecone**

**Steps:**

1. **Setup Pinecone:**
  - Create an account and set up an index in Pinecone.
2. **Data Indexing:**
  - Use sentence transformer to Transform movie descriptions and relevant textual data into embedded vectors.
  - Store these vectors in Pinecone, ensuring efficient indexing for quick retrieval.
3. **Configuration:**
  - Configure the index to support semantic similarity searches, which will allow the chatbot to retrieve relevant movie data based on user queries.

### 4. Upload Data to Vector DB

Upload cleaned data into pinecone vector db. We uploaded around 26k movies

The screenshot shows the Pinecone dashboard for an index named 'movies-index'. The index is configured with a cosine metric, 1024 dimensions, and is hosted on AWS in the us-east-1 region. The vector count is 26,035. Below the index details, there is a 'Namespaces' section with a search bar and a table listing namespaces. The table has columns for Name, Number of Vectors, and Actions. One namespace, 'movie-desc', is listed with 26035 vectors.

Metric	Dimensions	Host
cosine	1024	https://movies-index-7fjipiw.svc.aped-4627-b74a.pinecone.io

  

Cloud	Region	Type	Vector Count
AWS	us-east-1	Serverless	26,035

  

Namespaces

Namespaces let you partition an index into groupings for multi-tenancy or query speed. [Learn more](#)

Name	Number of Vectors	Actions
movie-desc	26035	...

### 5. Application Development

**Frameworks Used: FastAPI for backend, Streamlit for frontend**

## Steps:

### 1. User Interface:

- Designed a simple, user-friendly interface in Streamlit where users can input natural language queries.

### 2. Backend Logic:

- Implemented a FastAPI backend to handle incoming queries
- Based on chat history, refine latest user question to standalone question based on chat history. Use a GPT-3.5 instruct to understand user intent and extract relevant information.
- Use the Pinecone vector database to retrieve the most relevant movie data based on the processed query
- Embed the retrieved context and refined query into prompt in langchain and send the content to user.

3. **Orchestration:** orchestrated frontend and backend using docker-compose.

## 5. Evaluation and Testing

- Conduct extensive testing with a variety of queries to ensure the chatbot understands and responds accurately.
- Include edge cases and unusual queries to evaluate robustness.

## Testing whether bot can chat without losing context:

**Queries:** Recommend Animated Movies, Should have Sci-Fi as well, Add drama

## Hallucination test:

**Queries:** what is plot of movie 'ksk', changed release year of titanic in vector db and tested asking year

## Complex queries:

**Queries:** any movies you know involving gang dramas story origin from india

I am going to India for holidays, i want to watch movies on the way that shows the country heritage

I am going to Florida for vacation, show me some movies involving catastrophic situations that can happen there

## Confusing Queries:

any bollywood movies where good wins over bad  
any bollywood movies where good wins over bad

Refer to Video for results from our chatbot

## **Steps to Run Application :**

- CD to Web-Service
- Place your pinecone\_api\_key and openai\_key.
- “docker-compose build” build requirements
- “docker-compose up” to start the app.

## **Challenges Faced**

### **Data Quality:**

**Challenge:** The Kaggle dataset contained incomplete or inconsistent entries.

**Solution:** Implemented robust data cleaning procedures, including filling missing values and removing irrelevant information.

### **Vector Database Configuration:**

**Challenge:** Ensuring efficient and accurate indexing in Pinecone.

**Solution:** Experimented with different indexing parameters and configurations to optimize performance for semantic similarity searches.

### **Query Understanding:**

**Challenge:** Ensuring the LLM accurately understands and processes diverse natural language queries.

**Solution:** Tuned prompt of LLM using a variety of techniques learnt in class to improve understanding and accuracy.

### **Performance Optimization:**

**Challenge:** Maintaining fast response times while handling complex queries.

**Solution:** Tested latency against different retrieval mechanisms cosine, dot product and euclidian for latency