B. Mahashwar
192411195

SAVEETHA
INSTITUTE OF MEDICAL AND TECHNICAL SCIENCES
(Declared as Deemed to be University under Section 3 of UGC Act 1956)

Programme: **B.E / B.Tech**
Course Code: **MLA02**
Course Name: **FUNDAMENTALS OF MACHINE LEARNING**
Duration: **1:30 Hr**
Date : 2/11/2026
Max Marks: **50 Marks**

ASSIGNMENT – II
UNIT II – SUPERVISED LEARNING

Topics: *Linear regression and classification, naïve Bayes, discriminant functions, logistic regression, decision trees and pruning, neural networks and back-propagation, SVM, ensembles (bagging, boosting)*

Course Outcome

On successful completion of this assignment, students will be able to:

CO	Course Outcome Statement
CO2	Apply supervised learning algorithms for regression, classification, and predictive modeling tasks to solve structured data problems in practical applications.

Answer all the Tasks

Task 1. The following data relate the number of training epochs x to a validation score y.

x	1	2	3	4	5
y	2.1	3.9	6.2	7.8	10.1

(a) Fit $y = w_0 + w_1x$ by ordinary least squares using the normal equations. (b) Predict y at $x = 6$. (c) Compute the residual sum of squares, MSE and R^2. (d) Analyse the reliability of predicting at $x = 6$.

(5) (CO2) (BL4)

Task 2. For mean-centred data with $Sxx = \Sigma x^2 = 10$ and $Sxy = \Sigma xy = 19.9$ (single feature, no intercept needed), compute the ridge-regression slope for $\lambda = 5$. Calculate the percentage shrinkage relative to the least-squares slope and explain the bias–variance effect of increasing λ.

(2) (CO2) (BL4)

Task 3. An e-mail filter uses two binary features: Offer (contains the word 'offer') and Link (contains a hyperlink). Ten labelled e-mails are available.

#	Offer	Link	Class
1	Y	Y	Spam
2	Y	N	Spam
3	Y	Y	Spam
4	N	Y	Spam
5	Y	Y	Spam

#	Offer	Link	Class
6	N	N	Ham
7	N	Y	Ham
8	Y	N	Ham
9	N	N	Ham
10	N	N	Ham

(a) Estimate the priors and the class-conditional probabilities without smoothing. (b) Classify an e-mail with Offer = Y, Link = Y and report the posterior P(Spam | x). (c) Repeat (b) with Laplace smoothing (α = 1). (d) Classify an e-mail with Offer = N, Link = N (with smoothing) and analyse the effect of the conditional-independence assumption and of smoothing.

(6) (CO2) (BL4)

Task 4. A logistic-regression classifier $p = \sigma(w_1x_1 + w_2x_2 + b)$ is initialised with $w = (0, 0)$, $b = 0$ and trained on two samples: $x^{(1)} = (1, 2)$ with $y = 1$, and $x^{(2)} = (2, 1)$ with $y = 0$. Perform one batch gradient-descent step with learning rate $\eta = 0.5$ on the mean cross-entropy loss. Report the gradient, the updated parameters, the predicted probabilities and the loss before and after the update, and analyse the result.

(4) (CO2) (BL4)

Task 5. A node contains 10 training samples (6 Yes, 4 No). A candidate attribute A splits it into $A = a_1$ (4 samples: 4 Yes, 0 No) and $A = a_2$ (6 samples: 2 Yes, 4 No). Calculate the entropy of the node, the information gain of the split and the Gini-impurity decrease, and evaluate whether the split is worthwhile.

(3) (CO2) (BL4)

Task 6. In a decision tree trained on 100 samples, an internal node t with a four-leaf subtree T_t makes 3 training errors, whereas collapsing t into a single leaf would make 8 errors. Using cost-complexity pruning with $R_\alpha(T) = R(T) + \alpha|\text{leaves}|$, compute the critical value α at which the subtree and the single leaf have equal cost, and evaluate whether the subtree should be pruned for $\alpha = 0.01$ and $\alpha = 0.02$.

(3) (CO2) (BL5)

Task 7. A network has two inputs, one sigmoid hidden unit and one sigmoid output unit (no biases): $h = \sigma(w_1x_1 + w_2x_2)$, $\hat{y} = \sigma(vh)$, with $w_1 = 0.4$, $w_2 = 0.3$, $v = 0.5$. For the input $x = (1, 2)$ with target $t = 1$ and squared-error loss $E = \frac{1}{2}(t - \hat{y})^2$, perform one forward pass and one back-propagation update with $\eta = 0.5$. Report h, $\hat{y}$, E, the error terms δ, the gradients, the updated weights and the new loss.

(4) (CO2) (BL4)

Task 8. A linear SVM in two dimensions has $w = (0.5, 0.5)$ and $b = -2$, with the support vectors (3, 3) (class +1) and (1, 1) (class −1). (a) Verify that the support vectors lie on the margin hyperplanes and compute the geometric margin width. (b) Classify the points (4, 2) and (1, 2) and compute their distances from the decision boundary. (c) Compute the hinge loss for (1, 2) with true label −1 and for (2, 2) with true label +1, and state which points violate the margin.

(4) (CO2) (BL4)

Task 9. Independent classifiers, each with accuracy 0.70, are combined by majority voting. Calculate the ensemble accuracy for 3 and 5 classifiers, comment on the gain from adding more classifiers, and analyse what happens to this gain if the classifiers' errors are strongly correlated.

(3) (CO2) (BL4)

Task 10. AdaBoost starts with five training samples of equal weight. The first weak learner misclassifies samples 2 and 5. Compute the weighted error, the learner weight α, the un-normalised and normalised weights after the update, and analyse how boosting changes the focus of the next learner.

(4) (CO2) (BL4)

Task 11. Two classes share the covariance matrix $\Sigma = [[2, 0.5],[0.5, 1]]$ and have means $\mu_1 = (1, 2)^T$ and $\mu_2 = (3, 1)^T$. (a) Derive the discriminant direction $w = \Sigma^{-1}(\mu_2 - \mu_1)$ and the decision threshold for equal priors. (b) Classify $x = (2.5, 1)$. (c) Evaluate whether the decision changes if the priors are $P(\omega_1) = 0.8$ and $P(\omega_2) = 0.2$.

(4) (CO2) (BL4)

Task 12. A bank evaluates three classifiers on 1,000 test loans (100 actual defaulters). Default is the positive class.

Model	TP	FN	FP	TN
A	70	30	90	810
B	85	15	180	720
C	60	40	30	870

A missed defaulter (FN) costs ₹50,000 and a wrongly rejected good applicant (FP) costs ₹5,000.

(a) Compute accuracy, precision, recall and F1-score for each model. [3]

(b) Compute the total expected cost of each model. [2]

(c) Critically evaluate which model should be deployed and explain why accuracy and F1 lead to a different choice than cost. [2]

(d) Propose two modelling or threshold-tuning steps to improve the chosen model and one validation safeguard against over-fitting. [1]

(8) (CO2) (BL6)

SAVEETHA INSTITUTE OF MEDICAL AND TECHNICAL SCIENCES

(Declared as Deemed to be University under Section 3 of UGC Act 1956)

ANSWER SCRIPT EVALUATION SHEET

ASSIGNMENT - II

Programme	B.E / B.Tech	**Course Code**	**MLA02**
Course Name	**Fundamentals of Machine learning.**	**Date**	02/11/2026
Duration	1 Hr 30 Min	**Max Marks**	50

Register No.: B. Mahesh war (192411195)

TASK 1	Max Marks	Marks Awarded
Task 1	5	5
Task 2	2	2
Task 3	6	6
Task 4	4	4
Task 5	3	3
Task 6	3	3
Task 7	4	3
Task 8	4	4
Task 9	3	2
Task 10	4	4
Task 11	4	4
Task 12	8	6
TOTAL	**50**	46

46/50

Total in words:

Task 1: Linear Regression

given,

$x = (1, 2, 3, 4, 5)$

$y = (2.1, 3.9, 6.2, 7.8, 10.1)$

(a) Find regression equation

$w_1 = \frac{5(110.2) - 15(30.1)}{5(55) - 225} = 1.99$

$w_0 = 6.02 - (1.99)(3) = 0.05$

$y = 0.05 + 1.99x$

(b) prediction at $x = 6$

$y = 0.05 + 1.99x = 11.99$

(c) SSR, R calculations

$RSS = \Sigma(y - \hat{y})^2 = 0.107$

$MSE = \frac{0.107}{5} = 0.0214$

$R^2 = \frac{1 - 0.107}{39.708} = 0.9973$

(d) prediction at $x=6$ is extrapolation, so reliability may be lower

Task 2: Ridge Regression

$S_{xx} = 10, \quad S_{xy} = 19.9, \quad \lambda = 5$

$w = \frac{S_{xy}}{S_{xx} + \lambda} = \frac{19.9}{15}$

$w = 1.3267$

$$W_{LS} = \frac{19.9}{10} = 1.99$$

$$\text{shrinkage} = \frac{1.99 - 1.327}{1.99} \times 100$$

$$= 33.33\%$$

Conclusion:

Increasing λ increases bias and reduces variance

Task 3. Naive Bayes

given, 5 spam and 5 Ham emails

a) priors & probabilities

$$P(\text{spam}) = P(\text{Ham}) = 0.5$$

Feature	Spam	Ham
offer Y	4/5	1/5
offer N	1/5	4/5
link Y	4/5	1/5
link N	1/5	4/5

b) offer. Y, Link Y

$$P(\text{spam} \mid YY) = \frac{0.5\,(0.8)(0.8)}{0.5(0.8)(0.8) + 0.5\,(0.2)(0.2)}$$

$$= 94.12\%$$

c) Laplace smoothing

$$P(\text{spam} \mid YY) = \frac{25}{25+4} = 86.21\%$$

(d) offer N, Link N (smoothed)

$$P(\text{Spam} \mid NN) = \frac{4}{4+25}$$

$$= 13.79\%$$

Conclusion: Independence simplifies classification; smoothing prevents zero probabilities

Task 4. Logistic Regression

$$w = (0,0),\ b = 0,\ \eta = 0.5$$

a) initial probability:

$$p = \sigma(0) = 0.5$$

b) Gradients

$$\nabla w = \frac{1}{2}[(-0.5)(1,4) + (0.5)(2,1)]$$

$$\nabla w = (0.25, -0.25),\ \nabla b = 0$$

(c) Updated parameters

$$w_{new} = w - \eta \nabla w$$

$$w = (-0.125, 0.125),\ b = 0$$

(d) New probabilities and loss

$$p_1 = 0.5312,\quad p_2 = 0.4688$$

$$\text{Loss}_{\text{before}} = 0.6931$$

$$\text{Loss}_{\text{after}} = 0.6326$$

Conclusion: Gradient descent reduces loss.

Task 5. Decision Tree

given: 6 Yes, 4 NO

parent entropy:

$$H = -0.6 \log_2 0.6 - 0.4 \log_2 0.4$$

$$H = 0.971$$

child entropy:

$$H(a_1) = 0, \quad H(a_2) = 0.9183$$

Information gain:

$$IG = 0.971 - 0.6(0.9183)$$

$$\boxed{IG = 0.420}$$

Gini decreases:

$$0.48 - 0.6(0.4444) = 0.2183$$

Conclusion: split is worthwhile because impurity decreases

Task 6. Cost-complexity pruning

given, subtree errors = 3, leaves = 4, single leaf error = 8

$$3 + 4\alpha = 8 + \alpha$$

$$\alpha = 1.667$$

- $\alpha = 0.01$: keep subtree
- $\alpha = 0.02$: keep subtree.

Conclusion: Prune when α exceeds 1.667.

Task 7:- Neural Networks

given,

$w_1 = 0.4, w_2 = 0.3, w_v = 0.5, \eta = 0.5$

forward pass:

$h = \sigma(1) = 0.7311$

$\hat{y} = \sigma(0.5h) = 0.5904$

initial loss:

$\epsilon = \frac{1}{2}(1 - 0.5904)^2 = 0.0839$

Back propagation:

$\delta_o = 0.0991, \quad \delta_h = 0.00974$

$\nabla v = -0.07242$

$\nabla w_1 = -0.00974, \quad \nabla w_2 = -0.0194$

updated weights

$v = 0.5362$

$w_1 = 0.4097, \quad w_2 = 0.3097$

$\epsilon_{new} \approx 0.0811$

Task 8: Support vector machine:

given, $w = (0.5, 0.5), b = -2$

(a) support vectors

$f(x) = 0.5x_1 + 0.5x_2 - 2$

$f(3,3) = 1, \quad f(1,1) = -1$

$\text{margin} = \frac{2}{\sqrt{0.5}} = 2.828$

(b) classification:

point	class	Distance
(4,1)	+1	1.414
(1,2)	-1	0.707

4

(c) Hinge loss

$$L = \max(0, 1 - y f(x))$$

- (1,2), $y = -1$; $L = 0.5$
- (2,2) $y = +1$; $L = 1$

Both violate the margin

Task 9: Ensemble Learning

Classifier accuracy = 0.70

3 classifiers:

$$P = 3(0.7)^2(0.3) + (0.7)^3$$

$$= 78.4\%$$

2

5 classifiers:

$$P = 10(0.7)^3(0.3)^2 + 5(0.7)^4(0.3) + (0.7)^5$$

$$= 83.69\%$$

Conclusion: More independent classifiers improve accuracy. Correlated errors reduce the gain

Task 10: AdaBoost

given: 5 samples, equal initial weights

$w_i = 1/5 = 0.2$

weighted error:

$\epsilon = 2(0.2) = 0.4$ ✓

learner weight:

$\alpha = \frac{1}{2} \ln \frac{0.6}{0.4} = 0.2027$ ✓

updated weights:

- Correct samples: 0.1633 each (un normalised)
- Incorrect samples: 0.2449 each (unnormalised) ✓

after normalisation:

- Correct: 0.1667 each
- Incorrect: 0.25 each ✓

Conclusion: Boosting gives more weight to misclassified samples

Task 11:- Linear Discriminant Analysis

$\Sigma = \begin{bmatrix} 2 & 0.5 \\ 0.5 & 1 \end{bmatrix}$ $\mu_2 = (4,1)$, $\mu_1 = (2,1)$

(a) discriminant direction

$w = \Sigma^{-1}(\mu_2 - \mu_1)$

$w = (1.4286, -0.7143)$ ✓

equal prior threshold

$c = w^T \frac{\mu_1 + \mu_2}{2} = 0.2857$ ✓

b) classify (2, 5, 1)

$w^T x = 1.872$

since $1.8572 > 0.2857$

μ_1

4

c) unequal priors

$c = 0.2857 + \ln(0.8/0.2)$

$c = 1.6719$

remain μ_2

Task 12. classified evaluation

model	TP	FN	FP	TN
A	70	30	90	810
B	85	15	180	720
C	60	40	30	870

6

a) performance metric

$$\text{Accuracy} = \frac{TP + TN}{2000}$$

$$\text{precision} = \frac{TP}{TP + FP}$$

$$\text{Recall} = \frac{TP}{TP + FN}$$

$$f_1 = \frac{2PR}{P + R}$$

metric	A	B	C
Accuracy	88%	80.5%	93%
precision	43.75%	32.08%	68.57%
Recall	70%	85%	60%
F1	85.3%	46.67%	63.16%

(b) Total cost

$$cost = FN(50000) + FP(5000)$$

model	Total cost
A	19,50,000
B	16,50,000
C	21,50,000

(c) model

Best: Model B

Reason: Lowest total cost because missed defaulters are expensive

(d) Improvements.

1. Use class weighted and threshold tuning
2. Apply cross-validation to prevent overfitting.