RAJALAKSHMI ENGINEERING COLLEGE

Maheshwaran S 251801170-2025-AIDS

M2

Started on	Thursday, 17 September 2026, 8:18 AM
State	Finished
Completed on	Thursday, 17 September 2026, 8:27 AM
Time taken	8 mins 48 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b) {
    int valA = *(const int *)a;
    int valB = *(const int *)b;
    if (valA < valB) return -1;
    if (valA > valB) return 1;
    return 0;
}

int main() {
    int n;

    if (scanf("%d", &n) != 1) return 0;

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    qsort(arr, n, sizeof(int), compare);

    long long max_sum = 0;
    for (int i = 0; i < n; i++) {
        max_sum += (long long)arr[i] * i;
    }

    printf("%lld\n", max_sum);

    free(arr);
    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course