



IdentityIQ Breaking Glass

Terminate Identity Access

Red Button **Terminate Identity Access** under **Break Glass Operations** is used to shut down an **Identity or Service Account Cube** access right away, without approvals. Application access is disconnected based on lever options that are selected during application onboarding. This Quick Link is packaged to be accessed by Operations workgroup. An email is sent out to reporting manager on Identity termination.

Activate Identity Access

Green Button **Activate Identity Access** under **Break Glass Operations** is added to assign firefighter access or emergency access. This is used to activate an **Identity or Service Account Cube** access right away without approvals. This Quick Link will be used by Security Officers for pre-approved identities. **Sunset date** is required for these kinds of access request. Requestor cannot be the requestee for these kind of access requests

Security Officer needs to have **FireFighterAdmin** capability and pre-approved identities needs to have **FireFighter** capability for this functionality to work. Focused Certifications or Advanced Certifications can be used to certify a pre-approved Identity's **FireFighter** capability and the Security Officer's **FireFighterAdmin** capability.

Example Use Case: During emergency situation a doctor needs to perform a surgery and some access to Epic needs to be provided immediately. The fire fighter administration can process this request for a pre-approved doctor. In SAP, this is called Fire Fighter Access.

Process Identity Access

Lifecycle events can be processed manually using **Process Identity Access** under **Break Glass Operations**. Manual launched lifecycle events use application configuration options to build a provisioning plan. This Quick Link is packaged to be accessed by the Operations workgroup. All the processing options that are displayed on the form are shown only if a corresponding Lifecycle Event is enabled. Here is the mapping of Processes and Lifecycle Events.

Process	Lifecycle Event
Operations Launch SER Linking	SER LINK FEATURE
Operations Launch SER UnLinking	SER LINK FEATURE
Operations Launch Native Change	NATIVE CHANGE DETECTION FEATURE
Operations Launch Mover	MOVER FEATURE

Operations Launch Mitigation Expiration	MANAGER CERTIFICATION ALLOW EXCEPTION FEATURE
Operations Launch Leaver - LOA	LEAVER LOA FEATURE
Operations Launch Leaver - LTD	LEAVER LTD FEATURE
Operations Launch Joiner	JOINER FEATURE
Operations Launch Joiner - Rehire	JOINER REHIRE FEATURE
Operations Launch Leaver - RTW - LTD	JOINER LTD FEATURE
Operations Launch Leaver - RTW - LOA	JOINER LOA FEATURE
Operations Launch Reverse Leaver	REVERSE LEAVER FEATURE
Operations Launch Attribute Synchronization	ATTRIBUTE SYNCHRONIZATION FEATURE

Recover Identity Access

Identity access can be recovered using access requests and the latest snapshot using **Recover Identity Access** under **Break Glass Operations**. This process uses the Identity Request Id to reverse the provisioning action. Also, it uses Identity latest snapshot to get values of the attributes that are replaced during provisioning. This Quick Link is packaged to be accessed by the Operations workgroup.

Emergency Operations

Emergency operations can be used to either restore or suspend access of identities in bulk. It can also be used as a tool to shut down access of certain population during a security breach, with the exception of the administrative population. This allows administrators to investigate and perform breach analysis. It is added as an **Emergency Operations** quicklink under **Break Glass Operations**. This Quick Link is packaged to be accessed by the Admins workgroup.