

Table of Contents

1	Overview	2
2	Installation Steps	2
3	Upgrade Steps.....	3

Document Revision History

Version	Date	Status	Author	Summary of Changes
Version 1	6/5/18		Rohit Gupta	

1 Overview

The purpose of this document is to lay out steps for an Accelerator Pack Installation.

2 Installation Steps

1. Download Accelerator Pack Zip from Compass
2. Copy all hibernate files “web/WEB-INF/classes/sailpoint/object/*.hbm.xml” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/classes/sailpoint/object/” folder
 - a. Merge hibernate files for existing IdentityIQ Installations
3. Copy “web/WEB-INF/lib/ AcceleratorPack.jar” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/lib” folder
4. Copy everything under “web/WEB-INF/config/*” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/config/” folder
5. Copy everything “web/images/*” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/images/icons/” folder
6. Copy “web/WEB-INF/classes/sailpoint/web/messages/iiqCustom.properties” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/classes/sailpoint/web/messages” folder
 - a. Merge properties file for existing IdentityIQ Installations
7. Copy “web/define/applications/IdentityIQLoopback.xhtml” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/define/applications” folder
8. Extend your DB schema using IdentityIQ console command “extendedSchema”
9. Apply DDL Changes from “<Server Web Application Location>/WEB-INF/database” to your database
10. Deploy and Start Server
11. Initialize Accelerator Pack GA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack.xml”
12. **Optional** Uncomment Service Account, Persona, Create, Edit, and Contractor Plugin Extended Attributes from IdentityExtended, CertificationExtended, and LinkExtended Hibernate Files
13. **Optional** Stop the server
14. **Optional** Apply Hibernate Changes
15. **Optional** Extend your DB schema using IdentityIQ console command “extendedSchema”
16. **Optional** Apply DDL Changes from “<Server Web Application Location>/WEB-INF/database” to your database
17. **Optional** Deploy and Start Server
18. **Optional** Initialize Accelerator Pack BETA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack-BETA.xml”
19. **Optional** Initialize Accelerator Pack BETA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack-persona-BETA.xml”
20. **Optional** Initialize Accelerator Pack BETA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack-epic-BETA.xml”

21. Go to QuickLink Administrative Tasks “Installed Accelerator Pack” and make sure all features are displayed

3 Upgrade Steps

1. Download Accelerator Pack Zip from Compass
2. Copy all hibernate files “web/WEB-INF/classes/sailpoint/object/*.hbm.xml” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/classes/sailpoint/object/” folder
 - a. Merge hibernate files for existing IdentityIQ Installations
3. Copy “web/WEB-INF/lib/ AcceleratorPack.jar” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/lib” folder
4. Copy everything under “web/WEB-INF/config/*” from extracted zip to a temporary folder, merge Accelerator Pack Configurations (all files under web/WEB-INF/config/Accelerator Pack/*/Configure folders) as per release notes, and deploy files to IdentityIQ “<Server Web Application Location>/WEB-INF/config/” folder
5. Copy everything “web/images/*” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/images/icons/” folder
6. Copy “web/WEB-INF/classes/sailpoint/web/messages/iiqCustom.properties” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/WEB-INF/classes/sailpoint/web/messages” folder
 - a. Merge properties file for existing IdentityIQ Installations
7. Copy “web/define/applications/IdentityIQLoopback.xhtml” from extracted zip to deployed IdentityIQ “<Server Web Application Location>/define/applications” folder
8. Extend your DB schema using IdentityIQ console command “extendedSchema”
9. Apply DDL Changes from “<Server Web Application Location>/WEB-INF/database” to your database
10. Deploy and Start Server
11. Initialize Accelerator Pack GA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack.xml”
12. **Optional** Uncomment Service Account, Persona, Create, Edit, and Contractor Plugin Extended Attributes from IdentityExtended, CertificationExtended, and LinkExtended Hibernate Files
13. **Optional** Stop the server
14. **Optional** Apply Hibernate Changes
15. **Optional** Extend your DB schema using IdentityIQ console command “extendedSchema”
16. **Optional** Apply DDL Changes from “<Server Web Application Location>/WEB-INF/database” to your database
17. **Optional** Deploy and Start Server
18. **Optional** Initialize Accelerator Pack BETA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack-BETA.xml”
19. **Optional** Initialize Accelerator Pack BETA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack-persona-BETA.xml”
20. **Optional** Initialize Accelerator Pack BETA file by importing it from IdentityIQ console command or from UI “Global Settings ->Import From File”. Location of initialization file would be “<Server Web Application Location>/WEB-INF/config/init-acceleratorpack-epic-BETA.xml”
21. Remove Deprecated Objects as per Release Notes
22. Go to QuickLink Administrative Tasks “Installed Accelerator Pack” and make sure all features are displayed