Hands-on Lab: Working with Joins in MySQL using phpMyAdmin



Estimated time needed: 20 minutes

SQL JOIN is a clause that combines rows from two or more tables based on a related column between them. The table's relationship is established by comparing the values in the columns. The purpose of using JOINs is to retrieve data from multiple tables in a single query. There are four types of JOINs in SQL: INNER JOIN, LEFT JOIN, RIGHT JOIN, and FULL OUTER JOIN.

- INNER JOIN: Returns only the rows with matching values in both tables.
- LEFT JOIN: Returns all the rows from the left table and matching rows from the right table.
- RIGHT JOIN: Returns all the rows from the right table and matching rows from the left table.
- FULL OUTER JOIN: Returns all the rows when a match in the left or right table.

Objectives

By the end of this lab, you'll be able to:

- Write SQL queries on multiple tables using INNER JOINS
- Write SQL queries on multiple tables using OUTER JOINS

Software Used in this Lab

In this lab, you will use MySQL. MySQL is a Relational Database Management System (RDBMS) designed to efficiently store, manipulate, and retrieve data.



To complete this lab, you will utilize MySQL relational database service available as part of IBM Skills Network Labs (SN Labs) Cloud IDE. SN Labs is a virtual lab environment used in this course.

Database Used in this Lab

The database used in this lab is internal. You will be working on a sample HR database. This HR database schema consists of five tables: **EMPLOYEES**, **JOB_HISTORY**, **JOBS**, **DEPARTMENTS**, and **LOCATIONS**. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

about:blank 1/5

SAMPLE HR DATABASE TABLES

EMPLOYEES F_NAME L_NAME SSN B_DATE ADDRESS JOB_ID SALARY MANAGER_ID DEP_ID EMP_ID 5631 Rice, OakPark,IL E1001 John **Thomas** 123456 1976-01-09 100 100000 30001 980 Berry In, Elgin, IL E1002 Alice James 123457 1972-07-31 200 80000 30002 5 291 Springs, Gary, IL F1003 Steve Wells 123458 1980-08-10 300 50000 30002 5

JOB_HISTORY				JOBS				
EMPL_ID	START_DATE	JOBS_ID	DEPT_ID	JOB_IDENT	JOB_TITLE	MIN_SALARY	MAX_SALARY	
E1001	2000-01-30	100	2	100	Sr. Architect	60000	100000	
E1002	2010-08-16	200	5	200	Sr.SoftwareDeveloper	60000	80000	
E1003	2016-08-10	300	5	300	Jr.SoftwareDeveloper	40000	60000	

DEPARTMEN	ITS	LOCATIONS			
DEPT_ID_DEP	DEP_NAME	MANAGER_ID	LOC_ID	LOCT_ID	DEP_ID_LOC
2	Architect Group	30001	L0001	L0001	2
5	Software Development	30002	L0002	L0002	5
7	Design Team	30003	L0003	L0003	7

In this lab, you will run through some SQL practice problems that will provide hands-on experience with the different kinds of join operations.

NOTE: This lab requires you to have all five of these tables of the HR database populated with sample data on MySQL.

Load the database

Using the skills acquired in the previous modules, you should first create the database in MySQL. Follow the steps below:

- 1. Open the phpMyAdmin interface from the Skills Network Toolbox in Cloud IDE.
- 2. Create a blank database named 'HR'. Use the script shared in the link below to create the required tables.

Script Create Tables.sql

3. Download the files in the links below to your local machine (if not already done in previous labs).

Departments.csv

Jobs.csv

JobsHistory.csv

Locations.csv

Employees.csv

4. Use these files to the interface as data for respective tables in the 'HR' database.

JOINS

Let us see some examples of JOINS being used to query the data.

1. Retrieve the names and job start dates of all employees who work for department number 5.

about:blank 2/5

We need to use the Inner join operation with the EMPLOYEES table as the left table and the JOB_HISTORY table as the right table. The join will be made over employee ID, and the query response will be filtered for the Department ID value 5.

The query for this question will be as shown below.

```
    1. 1
    2. 2
    3. 3
    4. 4
    5. 5
    SELECT E.F_NAME, E.L_NAME, JH.START_DATE
    FROM EMPLOYEES as E
    INNER JOIN JOB_HISTORY as JH
    ON E.EMP_ID=JH.EMPL_ID
    WHERE E.DEP_ID ='5';
```

Copied!

2. Retrieve employee ID, last name, department ID, and department name for all employees.

For this, you must use the Left Outer Join operation with the EMPLOYEES table as the left table and the DEPARTMENTS table as the right table. The join will happen on the Department ID. The query will be written as follows:

```
1. 1
2. 2
3. 3
4. 4

1. SELECT E.EMP_ID, E.L_NAME, E.DEP_ID, D.DEP_NAME
2. FROM EMPLOYEES AS E
3. LEFT OUTER JOIN DEPARTMENTS AS D
4. ON E.DEP_ID=D.DEPT_ID_DEP;
```

Copied!

3. Retrieve the First name, Last name, and Department name of all employees.

For this, you will use the Full Outer Join operation with the EMPLOYEES table as the left table and the DEPARTMENTS table as the right table. A full outer join in MySQL is implemented as a UNION of left and right outer joins. The query will be written as shown below.

```
1. 1
2. 2
3. 3
4. 4
5.5
6.6
7.7
8.8
9.9
10. 10
11. 11
1. SELECT E.F NAME, E.L NAME, D.DEP NAME
2. FROM EMPLOYEES AS E
3. LEFT OUTER JOIN DEPARTMENTS AS D
4. ON E.DEP ID = D.DEPT ID DEP
6. UNION
7.
8. SELECT E.F NAME, E.L NAME, D.DEP NAME
9. FROM EMPLOYEES AS E
10. RIGHT OUTER JOIN DEPARTMENTS AS D
11. ON E.DEP ID=D.DEPT ID DEP
```

about:blank 3/5

Copied!

Practice Problems

1. Retrieve the names, job start dates, and job titles of all employees who work for department number 5.

▼ Hint

Perform an INNER JOIN with 3 tables: EMPLOYEES, JOB HISTORY, JOBS.

▼ Solution

```
1. 1
 2. 2
 3. 3
 4. 4
 5.5
 1. select E.F_NAME, E.L_NAME, JH.START_DATE, J.JOB_TITLE
 2. from EMPLOYEES as E
 3. INNER JOIN JOB_HISTORY as JH on E.EMP_ID=JH.EMPL_ID
 4. INNER JOIN JOBS as J on E.JOB_ID=J.JOB_IDENT
 5. where E.DEP_ID ='5';
Copied!
```

2. Retrieve employee ID, last name, and department ID for all employees but department names for only those born before 1980.

▼ Hint

Use an AND in the LEFT OUTER JOIN clause.

▼ Solution

```
1. 1
 2. 2
 3. 3
 4. 4
 5.5
 1. SELECT E.EMP_ID, E.L_NAME, E.DEP_ID, D.DEP_NAME
 2. FROM EMPLOYEES AS E
 3. LEFT OUTER JOIN DEPARTMENTS AS D
 4. ON E.DEP ID = D.DEPT ID DEP
 5. AND YEAR(E.B DATE) < 1980;
Copied!
```

3. Retrieve the first name and last name of all employees but department ID and department names only for male employees.

▼ Hint

Add an AND in Query 3A to filter on male employees in the ON clause. Alternatively, you can also use Left Outer Join.

▼ Solution

- 1. 1
- 2. 2
- 3. 3
- 4. 4
- 5.5
- 6.6 7. 7
- 8.8

about:blank 4/5

```
9. 9
10. 10
11. 11
1. SELECT E.F_NAME, E.L_NAME, D.DEPT_ID_DEP, D.DEP_NAME
2. FROM EMPLOYEES AS E
3. LEFT OUTER JOIN DEPARTMENTS AS D
4. ON E.DEP_ID=D.DEPT_ID_DEP AND E.SEX = 'M'
5.
6. UNION
7.
8. SELECT E.F_NAME, E.L_NAME, D.DEPT_ID_DEP, D.DEP_NAME
9. from EMPLOYEES AS E
10. RIGHT OUTER JOIN DEPARTMENTS AS D
11. ON E.DEP_ID=D.DEPT_ID_DEP AND E.SEX = 'M';
Copied!
```

Conclusion

Congratulations! You have completed this lab and you are ready for the next topic.

You now can:

- Query multiple tables using INNER JOINS
- Query multiple tables using LEFT/RIGHT OUTER JOINS
- Query multiple tables using FULL OUTER JOINS

Author(s)

Lakshmi Holla

Malika Singla

Abhishek Gagneja

Changelog

Date	Version	Changed by	Change Description
2023-10-13	0.7	Steve Hord	QA pass
2023-10-13	0.6	Misty Taylor	ID Check
2023-10-12	0.5	Abhishek Gagneja	Instructions updated
2023-05-05	0.4	Rahul Jaideep	Updated Markdown file
2022-10-28	0.3	Appalabhaktula Hema	Updated image links
2021-08-09	0.2	Sathya Priya	Updated SQL link
2021-11-01	0.1	Lakshmi Holla, Malika Singla	Initial Version

© IBM Corporation 2023. All rights reserved.

about:blank 5/5