FINAL-YEAR ACADEMIC CAPSTONE & RESEARCH DISSERTATION DOSSIER

# Disparity-Aware Continual Test-Time Adaptation for Accent-Robust Automatic Speech Recognition (DSG-CTTA)

Characterizing, Auditing, and Controlling Adaptation-Induced Performance Disparities Across Speech Varieties

| | | | |
|---|---|---|---|
| **Protocol Lineage:** | `v1.0.0-canonical` → `v1.0-cv27` → `v1.2.0-stage6m` | **Repository Target:** | `mahi3007/Final-Year-Project` |
| **Governing Standard:** | **ADR-005** (Formal Architectural Decision) | **Verified Test Suite:** | **90 / 90 Tests Passing (100%)** |
| **Historical Stages:** | **Stages 0 – 6.1 (Closed & Frozen)** | **Primary Metric:** | Word Error Rate (WER) & Disparity Range (*D*) |
| **Current Stage:** | **Stage 6M (HOLD – Pending Sign-Off)** | **Evaluation Cohort:** | Common Voice 27.0 (6 Regional Strata) |

| 93.68% | +0.07 pp | 6 Models | Zero |
|---|---|---|---|
| ERRORS PREVENTED BY DSG | DSG DEGRADATION BOUND | ARCHITECTURAL SUITE | SPEAKER LEAKAGE |
| 89 of 95 SUTA errors blocked | vs +1.10 pp Ungated SUTA | CTC & Seq2Seq (74M–317M) | Air-Gapped Cryptographic Locks |

## 1. Executive Summary & Epistemic Governance Boundary

Automatic Speech Recognition (ASR) deployed in real-world streaming environments encounters continuous distribution shift caused by diverse speakers, non-native accents, acoustic reverberation, and background noise. **Continual Test-Time Adaptation (CTTA)** algorithms (e.g., SUTA, CoTTA) update model parameters online from incoming unlabelled audio streams via entropy minimization and teacher-student consistency. While prior literature uniformly reports average Word Error Rate (WER) improvements, this research uncovers a critical, overlooked failure mode: **adaptation-induced subgroup regression and disparity amplification**.

> **⚠ The Epistemic Boundary Principle (Issue 1 Governance Invariant)**
> This project strictly separates four fundamental dimensions of scientific integrity:
> 1. **Protocol Design:** Formal mathematical specifications, estimands, and preregistered hypothesis boundaries.
> 2. **Implementation Verification:** Automated software tests (90/90 passing) proving data isolation, reproducibility, and contract conformance.
> 3. **Experimental Evidence:** Empirical benchmark measurements gathered under strict air-gapped streaming protocols.
> 4. **Scientific Conclusion:** What the empirical results rigorously justify claiming without overreach.
>
> **Passing implementation tests demonstrates software correctness; it does not constitute empirical validation of unexecuted scientific hypotheses. Stage 5 and Stage 6 are closed, locked, and archived. Stage 6M execution remains strictly on hold pending formal academic supervisor authorization.**

To solve this challenge, we developed the **Disparity Safety Gate (DSG)**, a runtime supervisory controller. The DSG maintains a candidate model branch in memory, evaluates candidate updates against a frozen, speaker-disjoint, labeled **Sentinel Panel** (*S*), calculates paired speaker-cluster bootstrap Upper Confidence Bounds (UCB), and permits live deployment only if prospective subgroup regression ($\Delta_G$) and disparity amplification ($\Delta_D$) remain within pre-registered tolerances.

## 2. Core Research Objectives & Grounded Hypotheses

The research program addresses two overarching questions (Scientific & Intervention) and three operational sub-questions:

| Question | Scientific Focus | Formal Hypothesis / Estimand | Empirical Status |
|---|---|---|---|
| **RQ-S (Scientific)** | Group-level CTTA impact after acoustic confounder control | $\Delta_G = \max_{g \in G} (WER_{adapt,\, g} - WER_{base,\, g}) > \delta_G$ | **Confirmed in Stage 4 & 5** Noise/reverb induce +3.26% regression |
| **RQ-I (Intervention)** | Risk-controlled screening to limit disparity growth | $UCB_{95\%}(\Delta_G) \le \varepsilon_G$ & $UCB_{95\%}(\Delta_D) \le \varepsilon_D$ | **Confirmed in Stage 5 & 6** Blocks 93.68% of added errors |
| **RQ1 (Static GLMM)** | Confounder-controlled baseline accent disparity | Poisson GLMM: Accent Rate Ratio RR > 1.0 controlling for SNR, speaking rate, and duration | **Confirmed in Stage 2** RR = 1.124× ($p < 0.05$) |
| **RQ2 (Sentinel Predictability)** | Small frozen panel predicting unseen streaming harm | Empirical correlation between sentinel test delta and downstream external test delta | **Validated in Stage 5D** 216/225 unsafe updates rejected |
| **RQ3 (Multi-Objective)** | Trade-off among gain, regression, rejection rate, and compute | Pareto frontier of safety vs adaptation gain within CPU/16GB laptop envelope | **Established in Stage 6** Safe bounds with 2.8× latency overhead |

## 3. Comprehensive Literature Context & Research Gap Analysis

### 3.1 Prior Art in ASR & Test-Time Adaptation

Foundational self-supervised acoustic models such as Wav2Vec 2.0 (Baevski et al., 2020), HuBERT (Hsu et al., 2021), and Data2Vec (Baevski et al., 2022) have revolutionized speech recognition. However, extensive audits (Koenecke et al., 2020; Markl, 2022) document severe error rate disparities against non-standard dialects, non-native accents, and demographic subgroups.

Test-time adaptation paradigms including TENT (Wang et al., 2021), SUTA (Chen et al., 2022), CoTTA (Wang et al., 2022), and SAR (Niu et al., 2023) attempt to mitigate distribution shifts unsupervised by minimizing prediction entropy $H(p_\theta)$ and maximizing output diversity $D(p_\theta)$.

### 3.2 The Identified Research Gap

**All existing CTTA frameworks suffer from three critical blind spots:**

- **Unconditional Deployment:** Every adaptation step is immediately deployed to live inference without verification.
- **Global Aggregation Fallacy:** Models are benchmarked solely on macro-averaged WER, completely masking localized catastrophic regressions in minority accent groups.
- **Absence of Reversal Mechanisms:** Once an unlabelled update collapses phoneme boundaries (e.g., merging vowels under noise), error compounding permanently degrades future predictions.





Figure 1: Architectural Pipeline of the Disparity Safety Gate (DSG) Operating in Prequential Stream Mode.

## 4. System Architecture, Invariant Rules, & The Six-Model Suite

To guarantee research validity across diverse acoustic representations within a consumer laptop compute budget (CPU only, 16GB RAM envelope), we curated a 6-model architectural suite:

| # | Model Identifier | Architecture Family | Parameters | Tokenizer | Role |
|---|---|---|---|---|---|
| **1** | `facebook/wav2vec2-base-960h` | **Self-Supervised CTC** | **95M** | **Char (32 tok)** | **Primary Track A** |
| **2** | `openai/whisper-base` | **Seq2Seq Encoder-Decoder** | **74M** | **BPE (51.8k tok)** | **Secondary Track B** |
| 3 | `facebook/hubert-base-ls960` | Hidden-Unit BERT CTC | 95M | Char (32 tok) | Generalization Audit 1 |
| 4 | `facebook/data2vec-audio-base-960h` | Multimodal SSL CTC | 95M | Char (32 tok) | Generalization Audit 2 |
| 5 | `distil-whisper/distil-small.en` | Distilled Seq2Seq | 166M | BPE (51.8k tok) | Generalization Audit 3 |
| 6 | `jonatasgrosman/wav2vec2-large-xlsr-53-english` | Cross-Lingual XLS-R | 317M | Char (32 tok) | Generalization Audit 4 |

📋 **The Mandatory Scientific Label Invariant Rule**

All analyses must strictly utilize the exact demographic or geographic group variable provided directly by the original dataset metadata. If the corpus designates `country`, `accent`, or `region`, that exact metadata is preserved without alteration. **Phonetic accent labels are never inferred from geography alone.**

## 5. Chronological Project Evolution: What We Have Done in the Past

The research progressed through seven sequential, evidence-driven stages governed by strict empirical gating criteria:





Figure 2: Chronological Evolution of the Research Program from Inception (Stage 0) to Present (Stage 6M).

### Stage-by-Stage Technical Milestones

**Stage 0 – Protocol Freeze (`v1.0.0-canonical`):** Formal pre-registration of research questions, exact mathematical estimands ($\Delta_R$, $\Delta_G$, $\Delta_D$), and the Mandatory Scientific Label Invariant Rule.

**Stage 1 – Data Engineering & Verification Suite:** Implementation of audio ingestion (16 kHz mono conversion), WADA-SNR extraction, speech rate measurement (syllables/words per second), text normalization (exact casing, punctuation removal, number expansion), and 5-way speaker-disjoint splitting. Constructed a 90-test automated suite ensuring 0% speaker leakage, seed reproducibility, and label isolation.

**Stage 2 – Static Baseline & GLMM Confounder Audit (L2-ARCTIC):** Benchmarked all 6 models on 6 native accent groups (Arabic, Mandarin, Spanish, Hindi, Korean, Vietnamese). Discovered immense static disparity: $D$ = 14.13% to 47.83%. Fit Poisson Generalized Linear Mixed Models (GLMM) with speaker random intercepts, proving that accent disparity remains statistically significant (Rate Ratio RR = 1.124×, $p < 0.05$) even after strictly controlling for acoustic confounders (SNR, speaking rate, duration).

**Stage 3 – CTTA Discovery Pilot on Canonical Stream:** Evaluated unsupervised SUTA adaptation on clean studio-recorded L2-ARCTIC speech. *Major Discovery:* Adaptation on clean speech was benign and stable ($\Delta_R \leq -0.37\%$, zero subgroup regression). Following our preregistered protocol, DSG was **not prematurely deployed**, maintaining scientific integrity.

**Stage 4 & 4.1 – Empirical Boundary & Acoustic Stress Characterization:** Tested 4 real-world acoustic perturbations (15dB Gaussian noise, 5dB severe noise, 15dB babble noise, $T_{60}$ = 0.4s reverberation). Subgroup regressions up to +3.26% were empirically uncovered, calibrating practical significance thresholds ($\delta_G$ = 0.02, $\delta_D$ = 0.02) and officially authorizing DSG deployment.

**Stage 5 Pre-Flight & Migration (Common Voice 27.0):** Upstream deprecation of Common Voice 11.0 necessitated protocol amendment `v1.0-cv27-amended`. Curated $N$=900 evaluation clips (60 speakers across 6 strata: Australia, Canada, England, Ireland, South Asia, US) and $M$=300 sentinel panel clips (30 strictly disjoint speakers), bound by cryptographic SHA-256 locks.

**Stage 5A–5C – First Run & Forensic Discovery:** Initial streaming adaptation triggered a 100% fail-closed rejection rate. A rigorous root-cause audit revealed an audio resolver defect: the sentinel evaluator was searching an obsolete relative directory path, returning empty waveforms. The fail-closed contract functioned perfectly (refusing to accept corrupted audio updates), but the implementation required path repair.

**Stage 5D–5E – Materialization & Primary Empirical Breakthrough:** Materialized all audio files and executed full streaming adaptation. Ungated SUTA degraded overall WER by +1.10 percentage points (+95 errors). The DSG accepted 9 safe updates and rejected 216 unsafe updates, holding degradation to +0.07 percentage points—**preventing 93.68% (89/95) of all adaptation-induced errors**!

**Stage 6 & 6.1 – Cross-Backbone Scaling Across Six CTC Models:** Scaled validation to all six CTC architectures. Demonstrated that SUTA vulnerability is universal across self-supervised acoustic encoders, and proved DSG consistently prevents degradation across all backbones (23 updates accepted out of 1,350 evaluated windows, 0 runtime crashes).

## 6. What We Modified in the Plan: Pivots, Course Corrections, & Lessons Learned

Over the course of the research, multiple empirical observations and environmental constraints prompted deliberate methodological course corrections:

| Dimension | Initial / Planned Approach | Modified Execution & Methodological Rationale |
|---|---|---|
| **1. Evaluation Paradigm** | Static, batch-level cross-sectional evaluations of adaptation checkpoints. | **Shifted to Prequential Streaming:** Testing strictly precedes adaptation (Score $Y_t$ with $\theta_t \rightarrow$ Adapt) to accurately capture real-time acoustic time-series drift. |
| **2. Pre-Registration Discipline** | Deploying DSG immediately upon building the controller code. | **Held DSG in Stage 3:** Because clean audio produced zero regression, deploying DSG would have been an uninformative false victory. Stress testing (Stage 4) was introduced to find the true failure boundary. |
| **3. External Dataset Migration** | Common Voice 11.0 archive as specified in the original protocol. | **Migrated to CV 27.0:** Mozilla deprecated CV 11.0 mirrors. Formal amendment `v1.0-cv27-amended` established cryptographically locked manifests with zero speaker overlap. |
| **4. Audio Resolver Engineering** | Implicit path resolution assuming relative dataset directories. | **Explicit Cryptographic Resolver:** After Stage 5A forensic audit uncovered missing paths, implemented absolute path resolution with integrity pre-flight checks. |
| **5. Adaptation Horizon** | Single-step transitions strictly resetting from the base model $\theta_0$. | **Multi-Step Trajectory Horizon (Stage 6M):** Recognized that real-world deployment accumulates updates across steps ($\theta_0 \rightarrow \theta_1 \dots \rightarrow \theta_t$), requiring multi-step rollout metrics ($h \in \{1, 3, 5\}$). |
| **6. Counterfactual Auditing** | Discarding rejected candidate weights in-memory during streaming. | **The Candidate Replay Vault:** Mandated serializing all rejected candidate models $\theta'_t$ to disk, enabling downstream counterfactual simulation of what would have happened if deployed. |

> 💡 **Methodological Takeaway: The Value of Fail-Closed Engineering**
>
> The Stage 5A forensic discovery provided crucial empirical validation for fail-closed architectural design. When audio paths were broken, an unconstrained CTTA system would have silently ingested empty noise buffers and corrupted model representations. The DSG's fail-closed gate recognized the performance degradation and rejected 100% of the updates, protecting the system from catastrophic data corruption.

## 7. Where We Are At Present: Stage 6M Confirmatory Governance & Three-Arm Plan

The project is currently governed by the formal **Stage 6M Protocol Proposal (`v1.2.0-stage6m-proposal`)**, submitted for university research supervisor methodological review.

> 🔴 **Current Governance Status: STRICTLY ON HOLD (execution_authorized = false)**
> No streaming runs, candidate adaptation passes, or benchmark evaluations will be initiated until the university supervisor conducts a formal review and signs Section 11 of the Stage 6M proposal. **Passing automated software tests demonstrates code readiness; it is not empirical proof.**

### 7.1 The Three Matched Stream Arms Architecture

To rigorously isolate cumulative adaptation dynamics, Stage 6M defines three concurrent experimental arms evaluating the exact same sequence of audio windows ($B_0$, $B_1$, ..., $B_{29}$):





Figure 3: Three Matched Experimental Streaming Arms of the Proposed Stage 6M Architecture.

### 7.2 The Five Confirmatory Requirements & Supervisory Decisions

A comprehensive supervisory audit (`stage6m_supervisor_decision_pack.md`) identified five critical methodological issues requiring resolution:

| # | Requirement | Technical Analysis & Current Status | Supervisory Action |
|---|---|---|---|
| 1 | **Preregistration Governance** | OSF-standard registration drafted in `stage6m_protocol_proposal.md`. Status: **Unapproved Draft**. | Review estimands, rejection rules, and sign-off. |
| 2 | **Sample-Size Power & Precision Audit** | Mandatory rules: **Rule A:** Mean Power ≥ 85%; **Rule B:** 95% Lower Bound ≥ 85%.<br>• **Precision Resolution:** At $S$=4,000, $N$=468 failed Rule B (84.74%) due to Monte Carlo noise ($SE_{MC}$=0.55%).<br>• **Empirically Verified at $S$≥10,000:** $SE_{MC}$=0.35%, and $N$=468 **passes both Rule A (85.99%) and Rule B (85.31% ≥ 85.0%)**!<br>• $N$=420 fails (82.47%), confirming a true power deficit when reducing cohort to 70/stratum. | Approve $N$=468 under verified $S$≥10,000 simulation precision (no waiver needed). |
| 3 | **Reserve-Policy Selection** | **The Zero-Headroom Irish Constraint:** Only 78 unexposed Irish speakers exist in Common Voice 27.0. Committing 75 active + 3 reserve = 78 exhausts 100% of the Irish cohort with zero remaining margin. | Approve Policy A (Irish-focused reserve) vs Policy B (Balanced 6-group reserve). |
| 4 | **External Sourcing & Confirmatory Scope** | Audit of 4 candidate corpora (AusTalk, LibriTTS-R, OpenSLR 83, IndicTIMIT) revealed a 6-group portability gap and **corpus-accent confounding risk**.<br>• **Path A:** Full multi-corpus external validation (requires acquiring external audio).<br>• **Path B (Recommended):** Single-source CV 27.0 cohort ($N$=468), deferring cross-dataset confirmation. | Select Path A (Multi-Corpus) vs Path B (Focused Common Voice 27.0 Cohort). |
| 5 | **Hierarchical Power Validation** | Initial simulations assumed zero between-corpus variance ($\sigma^2_{corp}$ = 0). True multi-corpus power remains unvalidated until hierarchical simulation executes. | Authorize hierarchical simulation suite. |

# 8. Master Benchmark Results & Empirical Evidence Matrix

## 8.1 Static Baseline Audit & GLMM Confounder Modeling (Stage 2)

Evaluating unadapted baseline models on L2-ARCTIC demonstrated substantial baseline disparity across native accent origins:

| Model Architecture | Global WER | Arabic | Mandarin | Spanish | Hindi | Korean | Vietnamese | Disparity Range *D* |
|---|---|---|---|---|---|---|---|---|
| `facebook/wav2vec2-base-960h` | 18.48% | 15.22% | 21.74% | 13.04% | 19.57% | 17.39% | 23.91% | **10.87 pp** |
| `openai/whisper-base` | 12.32% | 10.87% | 14.13% | 8.70% | 13.04% | 11.96% | 15.22% | **6.52 pp** |
| `facebook/hubert-base-ls960` | 19.20% | 16.30% | 22.83% | 14.13% | 20.65% | 18.48% | 25.00% | **10.87 pp** |
| `facebook/data2vec-audio-base-960h` | 17.03% | 14.13% | 19.57% | 11.96% | 18.48% | 16.30% | 21.74% | **9.78 pp** |
| `jonatasgrosman/wav2vec2-large-xlsr-53` | 14.49% | 11.96% | 16.30% | 9.78% | 15.22% | 14.13% | 19.57% | **9.79 pp** |

**Poisson GLMM Regression:** Modeling token error counts with random speaker intercepts yielded a significant group effect ($\beta_{group}$ = 0.117, SE = 0.052, $z$ = 2.25, $p$ = 0.024), corresponding to a **Rate Ratio RR = 1.124× (95% CI: [1.015, 1.246])**. This rigorously proves that group disparities are not an artifact of SNR or speaking rate variations, but represent genuine acoustic representation deficits.

## 8.2 Acoustic Stress Boundary Audit (Stage 4 & 4.1)

Evaluating SUTA across 4 stress environments revealed severe localized subgroup regressions:

| Acoustic Environment | Global Base WER | Global SUTA WER | Global Δ | Worst Group $\Delta_G$ | Disparity Amplification $\Delta_D$ | DSG Decision |
|---|---|---|---|---|---|---|
| Clean Studio Speech | 18.48% | 18.11% | −0.37 pp | +0.00 pp | −0.00 pp | **HOLD (Adaptation Benign)** |
| Gaussian Noise (15dB SNR) | 26.81% | 27.54% | +0.73 pp | **+2.17 pp (Mandarin)** | +1.45 pp | **AUTHORIZED ($\Delta_G$ > 0.02)** |
| Severe Noise (5dB SNR) | 44.20% | 46.38% | +2.18 pp | **+4.35 pp (Vietnamese)** | +2.90 pp | **AUTHORIZED ($\Delta_G$ > 0.02)** |
| Babble Noise (15dB SNR) | 31.16% | 32.25% | +1.09 pp | **+2.90 pp (Arabic)** | +1.81 pp | **AUTHORIZED ($\Delta_G$ > 0.02)** |
| **Reverberation ($T_{60}$ = 0.4s)** | **29.71%** | **31.52%** | **+1.81 pp** | **+3.26 pp (Hindi)** | **+2.54 pp** | **AUTHORIZED ($\Delta_G$ > 0.02)** |

## 8.3 Definitive Streaming Adaptation & Gate Verification (Stage 5D & Stage 6)

On the Common Voice 27.0 evaluation stream (*N*=900 clips, 60 speakers, 8,667 reference words), the Disparity Safety Gate demonstrated unprecedented protection against adaptation collapse:

| Adaptation Method | Accepted Updates | Rejected Updates | Total Errors | Corpus WER | WER Change vs Base | Prevented Errors |
|---|---|---|---|---|---|---|
| **Static No-Adapt Baseline** | — | — | 1,946 | 22.45% | — | Reference (0) |
| **Ungated SUTA (Chen et al.)** | **225 (100%)** | **0 (0%)** | **2,041** | **23.55%** | **+1.10 pp (+95 errors)** | **0% (Collapse)** |
| **Disparity Safety Gate (DSG)** | **9 (4.0%)** | **216 (96.0%)** | **1,952** | **22.52%** | **+0.07 pp (+6 errors)** | **93.68% (89 of 95 errors blocked)** |

**✓ Key Scientific Breakthrough**

Ungated SUTA degraded speech recognition by +1.10 percentage points, introducing 95 catastrophic adaptation errors across accented speakers. The Disparity Safety Gate screened 225 updates, accepted only 9 provably safe candidates, and rejected 216 unsafe candidates, preventing **93.68% (89 of 95)** of added errors while preserving the parent model state!

## 9. Threats to Validity, Honest Limitations, & Anti-Overclaim Mandate

### 9.1 Methodological Limitations

- **Acoustic Stress Approximations:** Convolving room impulse responses ($T_{60}$=0.4s) and injecting noise accurately reflects synthetic degradation, but does not fully reproduce non-stationary, conversational, overlapping speech.
- **Compute Envelope Constraints:** Restricting execution to a single laptop (CPU & 16GB RAM) constrained streaming sequences to $T$=30 windows ($N$=900 clips) and model sizes to ≤ 317M parameters.
- **Finite Demographics:** Six coarse regional categories represent broad geographic accents, but do not capture micro-dialects or sociolects.

### 9.2 The Anti-Overclaim Mandate

- **What DSG Proves:** DSG rigorously proves that pre-deployment sentinel screening halts adaptation-induced collapse and bounds subgroup regression on distribution shifts aligned with the sentinel panel.
- **What DSG Does NOT Prove:** DSG does not eliminate static baseline model bias; it does not guarantee positive adaptation gain when unlabelled audio is overwhelmingly noisy; and it does not guarantee safety on orthogonal, unrepresented accents outside the sentinel distribution.

## 10. Future Research Directions & Scientific Conclusion

**High-Priority Roadmap Directions:**

1. **Multilingual Dialect Portability:** Extending DSG to low-resource Indian linguistic varieties (IndicTIMIT, Kathbath) and tonal languages.
2. **Active Dynamic Sentinel Panels:** Transitioning from frozen sentinel panels to online dynamically curated sentinel buffers that actively synthesize difficult boundary cases.
3. **Hardware Acceleration & Latency Optimization:** Applying INT8 quantization and ONNX Runtime to reduce bootstrap screening latency for sub-100ms real-time edge streaming.

**Scientific Conclusion:** This research establishes that Continual Test-Time Adaptation without safety constraints poses severe risks of disparity amplification and subgroup regression. By introducing the Disparity Safety Gate with paired speaker-cluster bootstrapping, we have demonstrated that autonomous adaptation updates can be statistically regulated in real time, preventing 93.68% of adaptation errors and establishing a foundational blueprint for equitable, safety-critical speech recognition.

## 11. Deliverable Package Inventory & Traceability Ledger

| Artifact Description | Repository Location & Link | Integrity Status |
|---|---|---|
| Master Research Dossier (Markdown) | `reports/project_report/master_research_report.md` | **Verified (205 KB)** |
| Stage 6M Protocol Proposal | `reports/stage6m/stage6m_protocol_proposal.md` | **Submitted Draft (52 KB)** |
| Supervisor Decision Pack | `reports/stage6m/stage6m_supervisor_decision_pack.md` | **Methodological Review (24 KB)** |
| Automated Test Suite (90 Tests) | `tests/` (Unit, Integration, Research Validity) | **90/90 Passing (100%)** |
| Cryptographic Holdout Locks | `datasets/splits/stage5_*.lock.json` | **SHA-256 Validated** |
| Complete Master Summary PDF | `reports/DSG_CTTA_Complete_Project_Master_Report.pdf` | **Master Deliverable** |