


TacZombie

(a tactical Pacman clone)



Developed by Lars Eckervogt, Manuel Hieke and Stefan Junker for
the course "Moderne Programmiersprachen"
in MS11 in WS13/14 at HTWG Konstanz

Content


- Game Principle
- Worth a Word
- Tests
- Demo
- Summary

Game Principle

- 🍄 Round-based
- 🍄 Two Players
 - 🍄 **One Human:** can have multiple tokens
 - 🍄 **One Zombie:** can have multiple tokens
- 🍄 Goal
 - 🍄 **Zombie:** kill Human
 - 🍄 **Human:** survive and collect all coins
- 🍄 Map
 - 🍄 Pacman-like

Structure


Click to maximize



Model

🍄 Case classes

🍄 Easy access of subsets



Model

- Build to be extensible
- Multiple Players (Zombie/Humans)

Views

🍄 WUI

🍄 TUI

🍄 GUI



🍄 Communication through web sockets

• 🍄 Library: just.ws (<https://github.com/stasimus/just.ws>)

🍄 Transport format: JSON

• 🍄 Library: io.spray (<https://github.com/spray/spray-json>)

Controller


🍄 Server-side: Play

- 🍄 Manages web socket connections
- 🍄 Manages the game
- 🍄 Handles incoming client requests
- 🍄 Servers game data to th

Click to maximize

🍄 Client-side:

- 🍄 GUI: Swing
- 🍄 WUI: JavaScript/Play



Use of Traits

Example: Logger

```
5 trait Logger {  
6   object logger {  
7  
8     private var printOnGet : Boolean = false  
9  
10    private val data : ListBuffer[String] = ListBuffer[String]()  
11  
12    def clear = data.clear()  
13  
14    def +=(s : String, print : Boolean = false) = {  
15      data += s  
16      if(print) println(s)  
17    }  
18  
19    def init(s : String, print : Boolean = false, printOnGet : Boolean = false) = {  
20      clear  
21      this.printOnGet = printOnGet  
22      +=(s, print)  
23    }  
}
```

Use of Traits

Example: Logger

```
24
25 def get : List[String] = {
26     if(printOnGet) print
27     data.toList
28 }
29
30 def merge(l : Logger) = {
31     data.+=(l.logger.get)
32     l
33 }
34
35 def print = {
36     if(data.size > 0) {
37         println(data.apply(0))
38         for(s <- data.tail)
39             println("\t" + s)
40     } else println("Empty logger")
41 }
42 }
43 }
```

Use of Dependency Injection

• Main Method GUI / TUI with scala-juice

```
8 class UiModule(ui: Array[String]) extends AbstractModule {  
9 def configure {  
10   ui.toList match {  
11     case "tui" :: Nil => bind(classOf[IView]).to(classOf[Tui])  
12     case _ => bind(classOf[IView]).to(classOf[Gui])  
13   }  
14 }  
15 }  
16  
17 object Main {  
18 def main(args: Array[String]) {  
19   var restart = true  
20   val viewInjector = Guice.createInjector(new UiModule(args))  
21  
22   while (restart) {  
23     val view = viewInjector.getInstance(classOf[IView])  
24     view.open  
25     restart = view.runBlocking  
26   }  
27 }  
28 }
```

Use of Implicit Conversions

🍄 Example: CoordinateHelper

```
3 import scala.collection.mutable.ListBuffer
4 import scala.language.implicitConversions
5 import taczombie.model.Game
6 import taczombie.model.GameFieldCell
7 import taczombie.model.GameField
8
9 object CoordinateHelper {
10
11   implicit def intIntTuple2Wrapper(tuple: (Int,Int)) =
12     new IntIntTuple2Helper(tuple)
13
14   class IntIntTuple2Helper(tuple : (Int,Int)) {
15     def leftOf : (Int,Int) = (tuple._1, tuple._2 - 1)
16     def rightOf : (Int,Int) = (tuple._1, tuple._2 + 1)
17     def aboveOf : (Int,Int) = (tuple._1 - 1, tuple._2)
18     def belowOf : (Int,Int) = (tuple._1 + 1, tuple._2)
19   }
20 }
```

Use of Higher Order Function

🍄 Example: JsonHelperSpec

```
16  val -- = (a:Int,b:Int) => a - b
17  val ++ = (a:Int,b:Int) => a + b
18
19  private def upperLeftFor5StepsInBothDimensions(coord : (Int,Int))
20    (y : Int, fn1 : (Int,Int) => Int)
21    (x : Int, fn2 : (Int,Int) => Int) = {
22    for {
23      i <- 0 until 5
24      j <- 0 until 5
25    } yield coord.isUpperLeftOf(fn1(y,i),fn2(x,j))
26  }.toList
27  ...
60  upperLeftFor5StepsInBothDimensions(testCoord1)(10, --)(11, ++)
61  .exists(_ == true) must be_!(true)
```


Tests

🍄 200 fully automated Tests

🍄 Code Coverage scct

🍄 Model 100%

🍄 GUI / TUI: Utils 100%

🍄 Controller 76%

🍄 Coverage Report as html

Generate Standalone Game

• Server/WUI

- sbt “project wui” dist
- Generates zip file
- Extract and execute Skript wui in bin/ to run server

• GUI/TUI

- sbt assembly
- Generates TacZombieClient.jar
- Execute java -jar TacZombieClient.jar for GUI
- Add parameter “tui” for TUI

Demo

🍄 Lean back and enjoy :-)

Summary

- 🍄 GUI & TUI & WUI usable
 - 🍄 at the *same* time
 - 🍄 on the *same* model
- 🍄 Model fully automated tested
- 🍄 Controller automated tested
- 🍄 SBT Multi-project
- 🍄 Scala is awesome!
- 🍄 Swing is ok
- 🍄 ScalaFx lacks of support and examples