


# TacZombie

(a tactical Pacman clone)



Developed by Lars Eckervogt, Manuel Hieke and Stefan Junker for  
the course "Moderne Programmiersprachen"  
in MS11 in WS13/14 at HTWG Konstanz

# Content


- Game Principle
- Worth a Word
- Tests
- Demo
- Summary

# Game Principle

- 🍄 Round-based
- 🍄 Two Players
  - 🍄 **One Human:** can have multiple tokens
  - 🍄 **One Zombie:** can have multiple tokens
- 🍄 Goal
  - 🍄 **Zombie:** kill Human
  - 🍄 **Human:** survive and collect all coins
- 🍄 Map
  - 🍄 Pacman-like

# Structure


Click to maximize



# Model

🍄 Case classes

🍄 Easy access of subsets





# Model

- Build to be extensible
- Multiple Players (Zombie/Humans)

# Views

🍄 WUI

🍄 TUI

🍄 GUI



🍄 Communication through web sockets

- 🍄 Library: just.ws (<https://github.com/stasimus/just.ws>)

🍄 Transport format: JSON

- 🍄 Library: io.spray (<https://github.com/spray/spray-json>)

# Controller


## 🍄 Server-side: Play

- 🍄 Manages web socket connections
- 🍄 Manages the game
- 🍄 Handles incoming client requests
- 🍄 Servers game data to th

Click to maximize

## 🍄 Client-side:

- 🍄 GUI: Swing
- 🍄 WUI: JavaScript/Play





# Use of Traits

## Example: Logger

```
5 trait Logger {  
6   object logger {  
7  
8     private var printOnGet : Boolean = false  
9  
10    private val data : ListBuffer[String] = ListBuffer[String]()  
11  
12    def clear = data.clear()  
13  
14    def +=(s : String, print : Boolean = false) = {  
15      data += s  
16      if(print) println(s)  
17    }  
18  
19    def init(s : String, print : Boolean = false, printOnGet : Boolean = false) = {  
20      clear  
21      this.printOnGet = printOnGet  
22      +=(s, print)  
23    }
```

# Use of Traits

## Example: Logger

```
24
25 def get : List[String] = {
26     if(printOnGet) print
27     data.toList
28 }
29
30 def merge(l : Logger) = {
31     data.+=(l.logger.get)
32     l
33 }
34
35 def print = {
36     if(data.size > 0) {
37         println(data.apply(0))
38         for(s <- data.tail)
39             println("\t" + s)
40     } else println("Empty logger")
41 }
42 }
43 }
```

# Use of Dependency Injection

## • Main Method GUI / TUI with scala-juice

```
8 class UiModule(ui: Array[String]) extends AbstractModule {
9   def configure {
10     ui.toList match {
11       case "tui" :: Nil => bind(classOf[IView]).to(classOf[Tui])
12       case _ => bind(classOf[IView]).to(classOf[Gui])
13     }
14   }
15 }
16
17 object Main {
18   def main(args: Array[String]) {
19     var restart = true
20     val viewInjector = Guice.createInjector(new UiModule(args))
21
22     while (restart) {
23       val view = viewInjector.getInstance(classOf[IView])
24       view.open
25       restart = view.runBlocking
26     }
27   }
28 }
```

# Use of Implicit Conversions

## 🍄 Example: CoordinateHelper

```
3 import scala.collection.mutable.ListBuffer
4 import scala.language.implicitConversions
5 import taczombie.model.Game
6 import taczombie.model.GameFieldCell
7 import taczombie.model.GameField
8
9 object CoordinateHelper {
10
11   implicit def intIntTuple2Wrapper(tuple: (Int,Int)) =
12     new IntIntTuple2Helper(tuple)
13
14   class IntIntTuple2Helper(tuple : (Int,Int)) {
15     def leftOf : (Int,Int) = (tuple._1, tuple._2 - 1)
16     def rightOf : (Int,Int) = (tuple._1, tuple._2 + 1)
17     def aboveOf : (Int,Int) = (tuple._1 - 1, tuple._2)
18     def belowOf : (Int,Int) = (tuple._1 + 1, tuple._2)
19   }
20 }
```

# Use of Higher Order Function

## 🍄 Example: JsonHelperSpec

```
16  val -- = (a:Int,b:Int) => a - b
17  val ++ = (a:Int,b:Int) => a + b
18
19  private def upperLeftFor5StepsInBothDimensions(coord : (Int,Int))
20    (y : Int, fn1 : (Int,Int) => Int)
21    (x : Int, fn2 : (Int,Int) => Int) = {
22    for {
23      i <- 0 until 5
24      j <- 0 until 5
25    } yield coord.isUpperLeftOf(fn1(y,i),fn2(x,j))
26  }.toList
27  ...
60  upperLeftFor5StepsInBothDimensions(testCoord1)(10, --)(11, ++)
61  .exists(_ == true) must be_!(true)
```



# Tests

🍄 200 fully automated Tests

🍄 Code Coverage scct

🍄 Model 100%

🍄 GUI / TUI: Utils 100%

🍄 Controller 76%

🍄 Coverage Report as html

# Generate Standalone Game

## • Server/WUI

- sbt “project wui” dist
- Generates zip file
- Extract and execute Skript wui in bin/ to run server

## • GUI/TUI

- sbt assembly
- Generates TacZombieClient.jar
- Execute java -jar TacZombieClient.jar for GUI
- Add parameter “tui” for TUI

# Demo

🍄 Lean back and enjoy :-)

# Summary

- 🍄 GUI & TUI & WUI usable
  - 🍄 at the *same* time
  - 🍄 on the *same* model
- 🍄 Model fully automated tested
- 🍄 Controller automated tested
- 🍄 SBT Multi-project
- 🍄 Scala is awesome!
- 🍄 Swing is ok
- 🍄 ScalaFx lacks of support and examples