

WEEK 1

1)

```
mahij@Mahija: ~  
mahij@Mahija:~$ nano hello.c  
mahij@Mahija:~$ gcc hello.c -o hello  
  
./hello  
  
Hello Linux  
mahij@Mahija:~$ |
```

2)

```
mahij@Mahija:~$ nano username.c  
mahij@Mahija:~$ gcc username.c -o username  
mahij@Mahija:~$ ./username  
Enter your name: Mahija  
Welcome Mahija
```

3)

```
mahij@Mahija:~$ nano displayprocessID.c  
mahij@Mahija:~$ gcc displayprocessID.c -o displayprocessID  
mahij@Mahija:~$ ./displayprocessID  
Process ID = 668  
mahij@Mahija:~$ |
```

4)

```
mahij@Mahija:~$ nano parentandchild.c  
mahij@Mahija:~$ gcc parentandchild.c -o parentandchild  
mahij@Mahija:~$ ./parentandchild  
I am Parent Process  
I am Child Process  
mahij@Mahija:~$ |
```

5)

```

mahij@Mahija:~$ nano parentandchild.c
mahij@Mahija:~$ gcc parentandchild.c -o parentandchild
mahij@Mahija:~$ ./parentandchild
I am Parent Process
I am Child Process
mahij@Mahija:~$ |

```

6)

```

mahij@Mahija:~$ nano displayPandDpid.c
mahij@Mahija:~$ gcc displayPandDpid.c -o displayPandDpid
mahij@Mahija:~$ ./displayPandDpid
Parent PID = 907
Child PID = 908
Parent PID = 907
mahij@Mahija:~$ |

```

7)

```

mahij@Mahija:~$ nano wait.c
mahij@Mahija:~$ gcc wait.c -o wait
mahij@Mahija:~$ ./wait
Child Running
Parent Running After Child
mahij@Mahija:~$ |

```

8)

```

mahij@Mahija:~$ nano null.c
mahij@Mahija:~$ gcc null.c -o null
mahij@Mahija:~$ ./null
Before exec()
Commands  Mahija      displayPandDpid.c  displayprocessID.c  fork  hello  null  parentandchild  shell  username.c  wait.c
Demo.c    displayPandDpid  displayprocessID  example.txt         fork.c  hello.c  null.c  parentandchild.c  username  wait
mahij@Mahija:~$ |

```

9)

```

mahij@Mahija:~$ nano forkandexec.c
mahij@Mahija:~$ gcc forkandexec.c -o forkandexec
mahij@Mahija:~$ ./forkandexec
Fri Aug  7 09:33:41 UTC 2026
Child Completed
mahij@Mahija:~$ |

```