

Practical 3

```
GNU nano 8.7.1
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    pid_t pid = fork();

    if (pid == 0)
    {
        printf("Child Process\n");
        printf("PID   : %d\n", getpid());
        printf("PPID  : %d\n", getppid());

        sleep(10);
    }
    else
    {
        printf("Parent Process\n");
        printf("PID   : %d\n", getpid());

        wait(NULL);
    }

    return 0;
}
```

```
mahij@Mahija: ~
mahij@Mahija:~$ nano ppid.c
mahij@Mahija:~$ gcc ppid.c -o ppid
mahij@Mahija:~$ ./ppid
Parent Process
PID   : 2732
Child Process
PID   : 2733
PPID  : 2732
mahij@Mahija:~$ |
```

Practical 4

GNU nano 8.7.1

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    int i;

    for(i = 0; i < 3; i++)
    {
        if(fork() == 0)
        {
            printf("Child %d PID=%d\n", i + 1, getpid());
            return 0;
        }
    }

    for(i = 0; i < 3; i++)
    {
        wait(NULL);
    }

    printf("All children completed.\n");

    return 0;
}
```

mahij@Mahija: ~

```
mahij@Mahija:~$ nano waitpid.c
mahij@Mahija:~$ gcc waitpid.c -o waitpid
mahij@Mahija:~$ ./waitpid
Child 1 PID=3253
Child 2 PID=3254
Child 3 PID=3255
All children completed.
mahij@Mahija:~$ |
```