

Securing Our API



Kevin Dockx

ARCHITECT

@KevinDockx <https://www.kevindockx.com>



Coming Up



The Hybrid Flow

Passing an Access Token and Validating It

Specifics to Keep in Mind When Reading,
Creating, Updating and Deleting
Resources

Including Identity Claims in an Access
Token

Role-based Authorization



The Hybrid Flow



Client application
(relying party)

IDP



authentication request



code id_token



code id_token

authorization endpoint

user authenticates
(user gives consent)

token is validated



token request (code, clientid, clientsecret)



id_token, access_token



id_token, access_token



token endpoint


tokens are validated



access_token (as Bearer token in Authorization header)



The Hybrid Flow



Demo



Securing Access to Our API



Demo



Passing an Access Token to Our API



Demo



Showing an Access Denied Page



Demo



Protecting the API When Getting a Resource Collection



Demo



Protecting the API When Getting a Single Resource



Demo



Protecting the API When Updating a Resource




Demo



Protecting the API When Deleting a Resource



Including Identity Claims in an Access Token



Sometimes an API needs access to identity claims

When defining a resource scope (API resource), include the required claims in the claims list

Demo



Including Identity Claims in an Access Token



Demo



Protecting the API When Creating a Resource (With Roles)



Summary



Access tokens are passed to the API as Bearer tokens

AccessTokenValidationmiddleware can be used to validate an access token at level of the API

Summary



Take care of

- Checking that a resource belongs to the current user
- Getting the user identifier from the token
- Avoiding invalid input by using separate classes

Role-based authorization

