

THE MOST RELIABLE SOLAR HOT WATER SYSTEM FOR ALL.

from an idea to implement green energy to better use. We aim at providing universally designed products to living. Amidst our industrial product range, Photovoltaics and Solar Water Heating Systems

Are you tired of hard water corroding your water heater?

Almost 80% of Indian homes have complaints about hard water problems. In the period of long usage, hard water sedimentation affects the performance level of a regular heater and leads to its decay. To solve hard water problems once and for all, we introduced Solarizer Ultra.

most dependable choice of all. It also has a full-plate absorber with a highly selective German coating which provides more area to absorb sunlight. As a result, it emits almost no radiation, enabling faster water heating.



FEATURES



ECOLOGICALLY SOUND



CORROSION RESISTANT



UNIQUE HEAT EXCHANGER DESIGN



ONE TIME
INVESTMENT

BENEFITS



EXTREMELY HYGIENIC & SAFE



PEACE OF MIND



NO WORRIES OF CORROSION OR LEAKS



EFFICIENT HEATING PERFORMANCE



SUPERIOR DURABILITY



CONVENIENT INSTALLATION



HIGHLY SELECTIVE ABSORPTION SHEETS (GERMAN TECHNOLOGY)

TECHNOLOGY TRANSFERS HEAT QUICKER

LASER WELDING

TECHNICAL SPECIFICATION

Hot water storage tank specifications

MATERIAL OF STORAGE TANK	GLASS ENAMEL COATED
INSULATION	CFC FREE PUF (50mm THICKNESS)
OUTER CLADDING	PRE-COATED STEEL (RAL7035)
SAFETY VALVE	AIRVENT FOR THERMOSYPHON & 6 BAR
	SAFETY VALVE FOR PRESSURISED SYSTEM
ELECTRICAL BACKUP HEATER	2 Kw BACKUP HEATER/230 Vac
WORKING PRESSURE	6 BAR FOR PRESSURISED SYSTEM
TANK CONSTRUCTION	JACKET TYPE HEAT EXCHANGER
TANK PROTECTION	MAGNESIUM ANODE
TANK CAPACITY	100, 200, 300 AND 500 Lpd

Collector specifications

ABSORBER CONSTRUCTION	SINGLE SHEET ABSORBER
ABSORBER COATING	HIGH SELECTIVE COATING
	ABSORPTIVITY: 0.95+/-0.002; EMMISSIVITY: 0.047+/-0.02
GLAZING	SOLAR GLASS
RETAINER KEY FOR GLASS	EXTRUDED ALUMINIUM WITH
	GREY COLOUR POWDER COATING
RUBBER BEADING FOR GLASS	EPDM RUBBER
HEAT EXCHANGE MEDIUM	GLYCOL MIXTURE (PRIMARY CIRCUIT)
WEIGHT OF COLLECTOR (DRY)	32 Kg
MAXIMUM WORKING PRESSURE	10 BAR

EMMVEE SOLAR SYSTEMS PRIVATE LIMITED

Corporate Office: No. 13/1, International Airport Road.

Bettahalasuru Post, Bengaluru - 562 157, India Phone: +91 80 2217 4328, +91 80 2217 4333

info@emmvee.in | www.emmvee.com

(An ISO 9001:2015 & ISO 14001:2015 Certified Company)

