library load

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
```

Datasets load

```
df_1 = pd.read_csv("/KEN Admissions data.csv")
```

```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 4313 entries, 0 to 4312
Data columns (total 31 columns):
 #   Column                  Non-Null Count  Dtype
---  ------                  --------------  -----
 0   ADM                     4313 non-null   object
 1   A & E                   4313 non-null   object
 2   A & E.1                 4313 non-null   object
 3   DOB                     4313 non-null   object
 4   AGE                     4313 non-null   object
 5   TIME OF ADMISSION-HOUR  4313 non-null   object
 6   TIME OF ADMISSION-MIN   4313 non-null   object
 7   DISCHARGE DATE          4313 non-null   object
 8   TIME OF DISCHARGE-HOUR  4313 non-null   object
 9   TIME OF DISCHARGE-MIN   4313 non-null   object
 10  DEPARTMENT              4313 non-null   object
 11  WARD                    4313 non-null   object
 12  CLINIC                  4313 non-null   object
 13  SPECIALTY               4313 non-null   object
 14  AGE.1                   4313 non-null   object
 15  SEX                     4313 non-null   object
 16  TRIBE                   4313 non-null   object
 17  RELIGION                4313 non-null   object
 18  MARITAL STATUS          4313 non-null   object
 19  OCCUPATION              4313 non-null   object
 20  RESIDENCE               4313 non-null   object
 21  REFERRAL                4313 non-null   object
 22  NHIF                    4313 non-null   object
 23  NHIF NO.                4313 non-null   object
 24  PAY METHOD              4313 non-null   object
 25  PAY                     4313 non-null   object
 26  PAY.1                   4313 non-null   object
 27  DIAGNOSIS               4313 non-null   object
 28  OUTCOME                 4313 non-null   object
 29  DEATH CERTIFICATE       4313 non-null   object
 30  DEATH CAUSE             4313 non-null   object
dtypes: object(31)
memory usage: 1.0+ MB
```

```
df.head()
```

```
   ADM  A & E  DOB  AGE  TIME OF ADMISSION-HOUR  TIME OF ADMISSION-MIN  DISCHARGE DATE  TIME OF DISCHARGE-HOUR  TIME OF DISCHARGE-MIN  DEPARTMENT  WARD  CLINIC  SPECIALTY  AGE.1  SEX  TRIBE  RELIGION  MARITAL STATUS  OCCUPATION  RESIDENCE  REFERRAL  NHIF  NHIF NO.  PAY METHOD  PAY  PAY.1  DIAGNOSIS  OUTCOME  DEATH CERTIFICATE  DEATH CAUSE
0  1  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0
1  2  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0
2  3  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0
3  4  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0
4  5  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0
```

Clean Column Names

```
df.columns = df.columns.str.strip()
df.columns
```

```
Index(['ADM', 'A & E', 'DOB', 'AGE', 'TIME OF ADMISSION-HOUR',
       'TIME OF ADMISSION-MIN', 'DISCHARGE DATE', 'TIME OF DISCHARGE-HOUR',
       'TIME OF DISCHARGE-MIN', 'DEPARTMENT', 'WARD', 'CLINIC', 'SPECIALTY',
       'AGE.1', 'SEX', 'TRIBE', 'RELIGION', 'MARITAL STATUS', 'OCCUPATION',
       'RESIDENCE', 'REFERRAL', 'NHIF', 'NHIF NO.', 'PAY METHOD', 'PAY',
       'PAY.1', 'DIAGNOSIS', 'OUTCOME', 'DEATH CERTIFICATE', 'DEATH CAUSE'],
      dtype='object')
```

Date Parsing

```
df['A & E'] = pd.to_datetime(df['A & E'], dayfirst=True, errors='coerce')
df['DISCHARGE DATE'] = pd.to_datetime(df['DISCHARGE DATE'], dayfirst=True, errors='coerce')
```

3. Duration column convert into number

```
df['DURATION_OF_STAY'] = (df['DISCHARGE DATE'] - df['A & E']).dt.days
df[['A & E', 'DISCHARGE DATE', 'DURATION_OF_STAY']].head()
```

```
       A & E DISCHARGE DATE  DURATION_OF_STAY
0 2021-01-01     2021-01-01                 0
1 2021-01-01     2021-01-01                 0
2 2021-01-01     2021-01-01                 0
3 2021-01-01     2021-01-01                 0
4 2021-01-01     2021-01-01                 0
```

occupancy (Time Series)

```
daily_admit = df['A & E'].dt.date.value_counts()
daily_discharge = df['DISCHARGE DATE'].dt.date.value_counts()
occupancy = (daily_admit - daily_discharge).fillna(0).cumsum()
occupancy.head()
```

```
2021-01-01    0.0
2021-01-02    0.0
2021-01-03    0.0
2021-01-04    0.0
2021-01-05    0.0
Name: count, dtype: float64
```

```
occupancy = occupancy[occupancy >= 0]
occupancy.head()
```

```
2021-01-01    0.0
2021-01-02    0.0
2021-01-03    0.0
2021-01-04    0.0
2021-01-05    0.0
Name: count, dtype: float64
```

```
occupancy = occupancy.sort_index()
occupancy.head()
```

```
2021-01-01    0.0
2021-01-02    0.0
2021-01-03    0.0
2021-01-04    0.0
2021-01-05    0.0
Name: count, dtype: float64
```

```
occupancy_df = occupancy.reset_index()
occupancy_df.columns = ['Date', 'Occupancy']
occupancy_df.head()
```

```
         Date  Occupancy
0  2021-01-01        0.0
1  2021-01-02        0.0
2  2021-01-03        0.0
3  2021-01-04        0.0
4  2021-01-05        0.0
```

visulization

```
import matplotlib.pyplot as plt
import seaborn as sns
sns.set_theme(style="whitegrid")
plt.figure(figsize=(12,5))
sns.lineplot(data=occupancy_df, x="Date", y="Occupancy", color="green")
plt.title("Daily Occupancy (Recovered Data)")
plt.xlabel("Date")
plt.ylabel("Total Occupancy")
plt.tight_layout()
plt.show()
```

Feature Engineering

```
df['A & E'] = pd.to_datetime(df['A & E'], errors='coerce')
df = df.dropna(subset=['A & E'])
```

calender

```
df['Visit_Date'] = df['A & E'].dt.date
```

```
df = df.sort_values('Visit_Date')
```

before 1 and 7 days patient pattern

```
df['Visit_Date'] = pd.to_datetime(df['Visit_Date'])
```

```
df['Visit_Date'] = df['Visit_Date'].dt.date
```

last 7 days patient mean

```
df['Patients_Next_7'] = df['Visits_Occupancy'].rolling(window=7).mean()
```

```
df.head()
```

```
  ADM A & E  DOB  AGE  TIME OF ADMISSION-HOUR  TIME OF ADMISSION-MIN  DISCHARGE DATE  TIME OF DISCHARGE-HOUR  TIME OF DISCHARGE-MIN  DEPARTMENT  WARD  CLINIC  SPECIALTY  AGE.1  SEX  TRIBE  RELIGION  MARITAL STATUS  OCCUPATION  RESIDENCE  REFERRAL  NHIF  NHIF NO.  PAY METHOD  PAY  PAY.1  DIAGNOSIS  OUTCOME  DEATH CERTIFICATE  DEATH CAUSE  DURATION_OF_STAY  Visit_Date  Patients_Next_7
0  1  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0.0  2021-01-01  NaN
1  2  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0.0  2021-01-01  NaN
2  3  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0.0  2021-01-01  NaN
3  4  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0.0  2021-01-01  NaN
4  5  A  1/1/1900  1  0  0  1/1/1900  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0  0.0  2021-01-01  NaN
```

Correlation Heatmap

```
plt.figure(figsize=(12, 10))
sns.heatmap(df_corr, annot=True, fmt=".2f", cmap='coolwarm', linewidths=0.5)
plt.title("Correlation Matrix: Feature Importance")
plt.show()
```




```
df_ml = df[['Visits_Occupancy', 'Lag_1', 'Lag_7', 'Rolling_Mean_7',
            'Day_of_Month', 'Month', 'Day_of_Month']].dropna()
```

Machine learning part

Random forest

```
df_ml.head()
```

```
  Visits_Occupancy  Lag_1  Lag_7  Rolling_Mean_7  Day_of_Month  Month  Day_of_Month
0              NaN    NaN    NaN             NaN             1      1             1
1              NaN    0.0    NaN             NaN             1      1             1
2              NaN    0.0    NaN             NaN             1      1             1
3              NaN    0.0    NaN             NaN             1      1             1
4              NaN    0.0    NaN             NaN             1      1             1
```

```
df_ml.dropna(inplace=True)
df_ml.head()
```

```
  Visits_Occupancy  Lag_1  Lag_7  Rolling_Mean_7  Day_of_Month  Month  Day_of_Month
7              0.0    0.0    0.0             0.0             8      1             8
8              0.0    0.0    0.0             0.0             9      1             9
9              0.0    0.0    0.0             0.0            10      1            10
10             0.0    0.0    0.0             0.0            11      1            11
11             0.0    0.0    0.0             0.0            12      1            12
```

```
X = df_ml.drop('Visits_Occupancy', 'Date'], axis=1)
y = df_ml['Visits_Occupancy']
```

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_state=42)
```

```
from sklearn.ensemble import RandomForestRegressor
model = RandomForestRegressor(n_estimators=100, random_state=42)
model.fit(X_train, y_train)
```

```
RandomForestRegressor()
```

```
y_pred = model.predict(X_test)
```

```
from sklearn.metrics import mean_absolute_error, mean_squared_error, r2_score
mae = mean_absolute_error(y_test, y_pred)
rmse = mean_squared_error(y_test, y_pred, squared=False)
r2 = r2_score(y_test, y_pred)
print("Random Forest Regression Results:")
print(f"MAE: {mae:.2f}")
print(f"RMSE: {rmse:.2f}")
print(f"R² Score: {r2:.2f}")
```

```
Random Forest Regression Results:
MAE: 0.00
RMSE: 0.00
R² Score: 1.00
```

linear Regression

```
from sklearn.linear_model import LinearRegression
```

```
model = LinearRegression()
model.fit(X_train, y_train)
```

```
LinearRegression()
```

```
y_pred = model.predict(X_test)
mae = mean_absolute_error(y_test, y_pred)
rmse = mean_squared_error(y_test, y_pred, squared=False)
r2 = r2_score(y_test, y_pred)
```

```
print("Results of Linear Regression:")
print(f"Mean Absolute Error (MAE): {mae:.2f}")
print(f"Root Mean Squared Error (RMSE): {rmse:.2f}")
print(f"R² Score: {r2:.2f}")
```

```
Results of Linear Regression:
Mean Absolute Error (MAE): 0.00
Root Mean Squared Error (RMSE): 0.00
R² Score: 1.00
```

```
plt.figure(figsize=(12, 5))
sns.lineplot(x=df_ml['Date'], y=df_ml['Visits_Occupancy'], label="Actual")
sns.lineplot(x=df_ml['Date'].iloc[-len(y_pred):], y=y_pred, label="Predicted", linestyle="--")
plt.title("Actual vs Predicted Hospital Occupancy")
plt.xlabel("Date")
plt.ylabel("Occupancy")
plt.legend()
plt.tight_layout()
plt.show()
```



GradientBoostingRegressor

```
from sklearn.ensemble import GradientBoostingRegressor
```

```
model = GradientBoostingRegressor(n_estimators=100, learning_rate=0.1,
                                  max_depth=3, random_state=42)
model.fit(X_train, y_train)
```

```
GradientBoostingRegressor()
```

```
y_pred = model.predict(X_test)
mae = mean_absolute_error(y_test, y_pred)
rmse = mean_squared_error(y_test, y_pred, squared=False)
r2 = r2_score(y_test, y_pred)
```

```
print("Results of Gradient Boosting:")
print(f"Mean Absolute Error (MAE): {mae:.2f}")
print(f"Root Mean Squared Error (RMSE): {rmse:.2f}")
print(f"R² Score: {r2:.2f}")
```

```
Results of Gradient Boosting:
Mean Absolute Error (MAE): 0.00
Root Mean Squared Error (RMSE): 0.00
R² Score: 1.00
```

Model Comparison: Which model performed best

```
import matplotlib.pyplot as plt
import seaborn as sns
model_names = ['Random Forest', 'Linear Regression', 'Gradient Boosting']
mae_values = [rf_mae, lr_mae, gb_mae]
rmse_values = [rf_rmse, lr_rmse, gb_rmse]
r2_values = [rf_r2, lr_r2, gb_r2]
```

```
fig, ax = plt.subplots(1, 3, figsize=(18, 5))
sns.barplot(x=model_names, y=mae_values, ax=ax[0], palette="Blues_d")
ax[0].set_title("Mean Absolute Error (MAE)")
ax[0].set_ylabel("Error (Lower is Better)")
sns.barplot(x=model_names, y=rmse_values, ax=ax[1], palette="Greens_d")
ax[1].set_title("Root Mean Squared Error (RMSE)")
ax[1].set_ylabel("Error (Lower is Better)")
sns.barplot(x=model_names, y=r2_values, ax=ax[2], palette="Purples_d")
ax[2].set_title("R² Score (Higher is Better)")
ax[2].set_ylabel("Score (Higher is Better)")
plt.suptitle("Model Comparison: Which Model Performed Best?", fontsize=16)
plt.tight_layout()
plt.show()
```



Feature Importance: Which clues helped the AI most?

```
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.ensemble import RandomForestRegressor
```

```
model = RandomForestRegressor(n_estimators=100, random_state=42)
model.fit(X_train, y_train)
```

```
RandomForestRegressor()
```

```
importances = model.feature_importances_
feature_names = X_train.columns
feature_importance_df = pd.DataFrame({'Feature': feature_names, 'Importance': importances})
feature_importance_df = feature_importance_df.sort_values(by='Importance', ascending=False)
```

```
plt.figure(figsize=(10, 6))
sns.barplot(x='Importance', y='Feature', data=feature_importance_df, palette='viridis')
plt.title('Feature Importance (What drives Hospital Occupancy?)', fontsize=16)
plt.xlabel('Importance Score')
plt.ylabel('Feature (Clue)')
plt.tight_layout()
plt.show()
```



Real-time Trend: Actual vs Predicted over Time

```
plt.figure(figsize=(14, 6))
plt.plot(df_ml['Date'], df_ml['Visits_Occupancy'], label='Actual Occupancy', color='blue')
plt.plot(df_ml['Date'].iloc[-len(y_pred):], y_pred, label='Predicted Occupancy', color='orange', linestyle='--')
plt.title('Time-Series Forecasting: Hospital Occupancy Over Time', fontsize=16)
plt.xlabel('Date')
plt.ylabel('Number of Patients')
plt.legend()
plt.tight_layout()
plt.show()
```


🚨 AI-Based Early Warning System Dashboard

```
# Add this code after the previous visualizations
import matplotlib.pyplot as plt
import seaborn as sns
import pandas as pd # Ensure pandas is imported

# Assuming 'occupancy_df' and 'model' are already defined from previous steps
# occupancy_df = pd.read_csv('your_occupancy_data.csv') # Example if you need to load it
# model = ... # Your trained RandomForestRegressor model

# Calculate the average occupancy for the entire period
avg_occupancy = occupancy_df['Occupancy'].mean()

# Define the threshold for the warning system (e.g., 10% above average)
threshold = avg_occupancy * 1.10

print(f"Average Occupancy: {avg_occupancy:.2f}")
print(f"Warning Threshold: {threshold:.2f}")

# Predict future occupancy (using the last known data point)
# Create a dataframe for the next 7 days
last_date = occupancy_df['Date'].max()
future_dates = pd.date_range(start=last_date + pd.Timedelta(days=1), periods=7)
future_df = pd.DataFrame({'Date': future_dates})

# Feature engineering for future dates (must match training features)
future_df['Day_of_Month'] = future_df['Date'].dt.day
future_df['Month'] = future_df['Date'].dt.month
future_df['Day_of_Week'] = future_df['Date'].dt.dayofweek

# Predict using the model
# Note: This is a simplified prediction. For accurate forecasting, you'd need to predict iteratively
# or use a more sophisticated time series model.
future_df['Predicted_Occupancy'] = model.predict(future_df[['Day_of_Month', 'Month', 'Day_of_Week']])

# Plot the forecast with the threshold
plt.figure(figsize=(12, 6))
plt.plot(occupancy_df['Date'], occupancy_df['Occupancy'], label='Historical Occupancy')
plt.plot(future_df['Date'], future_df['Predicted_Occupancy'], label='Predicted Occupancy', linestyle='--')
plt.axhline(threshold, color='red', linestyle='-.', label='Warning Threshold')
plt.title('Hospital Occupancy Forecast with Warning System')
plt.xlabel('Date')
plt.ylabel('Number of Patients')
plt.legend()
plt.tight_layout()
plt.show()

# Check if any predicted occupancy exceeds the threshold
if future_df['Predicted_Occupancy'].max() > threshold:
    print("\n🚨 WARNING: Predicted occupancy is expected to exceed the threshold in the next 7 days!")
else:
    print("\n✅ Predicted occupancy is within normal limits for the next 7 days.")
```

```
Average Occupancy: 0.00
Warning Threshold: 0.00

✅ Predicted occupancy is within normal limits for the next 7 days.
```

```
# Add this code after the previous visualizations
import matplotlib.pyplot as plt
import seaborn as sns
import pandas as pd # Ensure pandas is imported

# Assuming 'occupancy_df' and 'model' are already defined from previous steps
# occupancy_df = pd.read_csv('your_occupancy_data.csv') # Example if you need to load it
# model = ... # Your trained RandomForestRegressor model

# Calculate the average occupancy for the entire period
avg_occupancy = occupancy_df['Occupancy'].mean()

# Define the threshold for the warning system (e.g., 10% above average)
threshold = avg_occupancy * 1.10

print(f"Average Occupancy: {avg_occupancy:.2f}")
print(f"Warning Threshold: {threshold:.2f}")

# Predict future occupancy (using the last known data point)
# Create a dataframe for the next 7 days
last_date = occupancy_df['Date'].max()
future_dates = pd.date_range(start=last_date + pd.Timedelta(days=1), periods=7)
future_df = pd.DataFrame({'Date': future_dates})

# Feature engineering for future dates (must match training features)
future_df['Day_of_Month'] = future_df['Date'].dt.day
future_df['Month'] = future_df['Date'].dt.month
future_df['Day_of_Week'] = future_df['Date'].dt.dayofweek

# Predict using the model
# Note: This is a simplified prediction. For accurate forecasting, you'd need to predict iteratively
# or use a more sophisticated time series model.
future_df['Predicted_Occupancy'] = model.predict(future_df[['Day_of_Month', 'Month', 'Day_of_Week']])

# Plot the forecast with the threshold
plt.figure(figsize=(12, 6))
plt.plot(occupancy_df['Date'], occupancy_df['Occupancy'], label='Historical Occupancy')
plt.plot(future_df['Date'], future_df['Predicted_Occupancy'], label='Predicted Occupancy', linestyle='--')
plt.axhline(threshold, color='red', linestyle='-.', label='Warning Threshold')
plt.title('Hospital Occupancy Forecast with Warning System')
plt.xlabel('Date')
plt.ylabel('Number of Patients')
plt.legend()
plt.tight_layout()
plt.show()

# Check if any predicted occupancy exceeds the threshold
if future_df['Predicted_Occupancy'].max() > threshold:
    print("\n🚨 WARNING: Predicted occupancy is expected to exceed the threshold in the next 7 days!")
else:
    print("\n✅ Predicted occupancy is within normal limits for the next 7 days.")
```

```
Average Occupancy: 0.00
Warning Threshold: 0.00

✅ Predicted occupancy is within normal limits for the next 7 days.
```

⚠ Warning: Use only detailed descriptions. Personal identifiers will be removed.
⚠ Reminder: Do not upload confidential documents.