for loop

80, 92, 75, 60, 90, 95

↳ iterate over a sequence & execute a block of code for each element.

- range
- list
- string → "Mahipal" 0123456
- tuple
- dictionary

d = 2

2, 4, 6, 8, 10, 12 - - - -

4-2 = 8-6 = 10-8

A.P. Series

for variables in sequence:
    code_to_execute

Data Structures

↳ collection of data

A way to organize & store multiple values efficiently.

- List
- Tuples
- Sets
- Dictionary

LIST

↳ ordered collection of values stored inside square brackets.

x = [10, 20, 30, 40, 60, 90]

- x → variable name
- 10, 20, 30, 40, 60, 90 → elements(s)
- [ ] → list container

[30, 20.2, "Mahipal", True]

- Order
- Mutable
- store multiple data types.

[None] → absence of value
↳ None Type

x = None
print(x)
None

x = [10, 20, 30, 40, 50, 60, 70]

position number (indexing)	0	1	2	3	4	5	6	→ Zero Indexing
	-7	-6	-5	-4	-3	-2	-1	→ negative Indexing

List Slicing

list[start : stop]

Step slicing

list[start : stop : step]

x = [10, 20, 30, 40, 50, 60]

print(x[0:6:2])

[10, 30, 50]