Task 1 - Deploy a Static Website on AWS S3

Live Website Link:
http://mahir101.s3-website.eu-north-1.amazonaws.com

Requirements Completed:
- Created S3 bucket with static hosting enabled
- Uploaded HTML files
- Set public permissions and bucket policy
- Website accessible through public URLLive Website Link:

http://mahir101.s3-website.eu-north-1.amazonaws.com

6:31

S3 bucke...
mazon.com

AWS Console Mobile
Business

View

Mor

Amazon S3 > Buckets

Empty Delete

Create bucket

Buckets are containers for data stored in S3.

Find buckets by name

1

	Name	AWS Region	Creation date
○	mahir 101	Europe (Stockholm) eu-	March 9, 2026, 14:18:51

6:31

S3 bucke...
mazon.com

AWS Console Mobile
Business

View

Mor

Amazon S3 > Buckets

Empty Delete

Create bucket

Buckets are containers for data stored in S3.

Find buckets by name

1

	Name	AWS Region	Creation date
○	mahir 101	Europe (Stockholm) eu-	March 9, 2026, 14:18:51

6:33

mahir101 ...
mazon.com

AWS Console Mobile
Business

View

Mor

mahir101

stored in Amazon S3. You can use Amazon S3 inventory to get a list of all objects in your bucket. For others to access your objects, you'll need to explicitly grant them permissions. Learn more

Find objects by prefix

1

Name	Type	Last modified
index.html	html	March 9, 2026, 18:18:00 (UTC+05:3

6:33

mahir101 ...
mazon.com

AWS Console Mobile
Business

View

Mor

mahir101

more about Amplify Hosting
or View your existing Amplify apps

Create Amplify app

S3 static website hosting
Enabled

Hosting type
Bucket hosting

Bucket website endpoint
When you configure your bucket as a static website, the website is available at the AWS Region-specific website endpoint of the bucket.
Learn more

http://mahir101.s3-website.eu-north-

6:34

AWS Console Mobile
Business

View

Mor

mahir101

Bucket policy

Edit Delete

The bucket policy, written in JSON, provides access to the objects stored in the bucket. Bucket policies don't apply to objects owned by other accounts. Learn more

Copy

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "PublicReadGetObject",
            "Effect":
```