Problem | Editorial | Submissions | Comments

Output Window

Compilation Results | Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 3 5 8 9 2 6 7 6 8 9

Your Output:

3

Expected Output:

3

Java (21) | Start Timer

```java
class Solution {
    static int minJumps(int[] arr) {
        if (arr[0] == 0) return -1;

        int jumps = 1, maxReach = arr[0], steps = arr[0];

        for (int i = 1; i < arr.length; i++) {
            if (i == arr.length - 1) return jumps;

            maxReach = Math.max(maxReach, i + arr[i]);
            steps--;

            if (steps == 0) {
                jumps++;
                if (i >= maxReach) return -1;
                steps = maxReach - i;
            }
        }
        return -1;
    }
}
```

Custom Input | Compile & Run | Submit

Description | Editorial | Solutions | Submissions

1. Two Sum

Easy | Topics | Companies | Hint

Given an array of integers `nums` and an integer `target`, return *indices of the two numbers such that they add up to* `target`.

You may assume that each input would have ***exactly* one solution**, and you may not use the *same* element twice.

You can return the answer in any order.

Example 1:

```
Input: nums = [2,7,11,15], target = 9
Output: [0,1]
Explanation: Because nums[0] + nums[1] == 9, we return [0, 1].
```

Example 2:

67.9K | 1.9K | 2389 Online

Code

Java | Auto

```java
import java.util.*;

class Solution {
    public int[] twoSum(int[] nums, int target) {
        HashMap<Integer, Integer> map = new HashMap<>();

        for (int i = 0; i < nums.length; i++) {
```

Saved | Ln 1, Col 1

Testcase | Test Result

Output

```
[0,1]
```

Expected

```
[0,1]
```

Contribute a testcase

Description | Editorial | Solutions | Submissions

35. Search Insert Position

Easy | Topics | Companies

Given a sorted array of distinct integers and a target value, return the index if the target is found. If not, return the index where it would be if it were inserted in order.

You must write an algorithm with `O(log n)` runtime complexity.

Example 1:

```
Input: nums = [1,3,5,6], target = 5
Output: 2
```

Example 2:

```
Input: nums = [1,3,5,6], target = 2
Output: 1
```

Example 3:

18.7K | 427 | 224 Online

Code

Java | Auto

```java
class Solution {
    public int searchInsert(int[] nums, int target) {
        int l = 0, r = nums.length - 1;

        while (l <= r) {
            int mid = l + (r - l) / 2;

```

Saved | Ln 1, Col 1

Testcase | Test Result

Case 1 | Case 2 | Case 3

Input

nums =

[1,3,5,6]

target =

5

Search... Courses Tutorials Practice Jobs M

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 2 3 -2 5

Your Output:

9

Expected Output:

9

Java (21) Start Timer

```java
class Solution {
    public static int maxSubarraySum(int[] arr) {
        int currentSum = arr[0];
        int maxSum = arr[0];

        for (int i = 1; i < arr.length; i++) {
            currentSum = Math.max(arr[i], currentSum + arr[i]);
            maxSum = Math.max(maxSum, currentSum);
        }

        return maxSum;
    }
}
```

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Java (21) Start Timer

```java
class Solution {
    static void rotate(int[] arr) {
        int n = arr.length;
        if (n <= 1) return;

        int last = arr[n - 1];

        for (int i = n - 1; i > 0; i--) {
            arr[i] = arr[i - 1];
        }

        arr[0] = last;
    }
}
```

Custom Input Compile & Run Submit

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

1 2 3 4 5

Your Output:

5 1 2 3 4

Expected Output:

5 1 2 3 4

Search... Courses Tutorials Practice Jobs M

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 8 7 56 90

Your Output:

90

Expected Output:

90

Java (21) Start Timer

```java
class Solution {
    public static int largest(int[] arr) {
        int max = arr[0];
        for(int i = 1; i < arr.length; i++){
            if(arr[i] > max){
                max = arr[i];
            }
        }
        return max;
    }
}
```

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Input:

a[] =

1 2 3 4 5

b[] =

1 2 3

Your Output:

[1, 2, 3, 4, 5]

Expected Output:

[1, 2, 3, 4, 5]

Java (21) Start Timer

```java
class Solution {
    public static ArrayList<Integer> findUnion(int a[], int b[]) {
        HashSet<Integer> set = new HashSet<>();

        for(int x : a) set.add(x);
        for(int x : b) set.add(x);

        return new ArrayList<>(set);
    }
}
```

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Java (21) Start Timer

```java
import java.util.Arrays;

class Solution {
    public static int kthSmallest(int[] arr, int k) {
        Arrays.sort(arr);
        return arr[k - 1];
    }
}
```

Custom Input Compile & Run Submit

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

7 10 4 3 20 15

k =

3

Your Output:

Search... Courses Tutorials Practice Jobs M

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 4 3 5 4 8 6

Your Output:

[1, 8]

Expected Output:

[1, 8]

Java (21) Start Timer

```java
class Solution {
    public ArrayList<Integer> getMinMax(int[] arr) {
        ArrayList<Integer> result = new ArrayList<>();

        int min = arr[0];
        int max = arr[0];

        for (int i = 1; i < arr.length; i++) {
            if (arr[i] < min) {
                min = arr[i];
            }
            if (arr[i] > max) {
                max = arr[i];
            }
        }

        result.add(min);
        result.add(max);
        return result;
    }
}
```

Custom Input Compile & Run Submit

Search...

Courses Tutorials Practice Jobs

Problem Editorial Submissions Comments

Output Window

Compilation Results Custom Input

Compilation Completed

Case 1

Input:

arr[] =

1 2 3 4

Your Output:

[1, 2, 3, 4]

Expected Output:

[4, 3, 2, 1]

Java (21) Start Timer

```
class Solution {
    public void reverseArray(int arr[]) {
        // code here

    }
}
```

Custom Input Compile & Run Submit