

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

INPUT:

```
%{
#include<stdio.h>
#include<stdlib.h>
void dec_to_hex(int n){
    if(n==0){
        printf("0");
        return;
    }
    char hex_char[] = "0123456789abcdef";
    char hex_num[50];
    int i = 0;
    while(n>0){
        int remainder = n%16;
        hex_num[i] = hex_char[remainder];
        n = n/16;
        i++;
    }
    for(int j = i-1; j >= 0; j--){
        printf("%c", hex_num[j]);
    }
}
int yywrap(void) {
    return 1;
}
}%}
%%
[0-9]+ {
    int dec_val = atoi(yytext);
```

AGNEL INSTITUTE OF TECHNOLOGY AND DESIGN

```
    dec_to_hex(dec_val);
}
.\n {
    printf("%s", yytext);
}
%%

int main(void){
    yylex();
    return 0;
}
```

OUTPUT:

```
vboxuser@Ubuntu-05:~$ flex exp3.l
flex: can't open exp3.l
vboxuser@Ubuntu-05:~$ flex exp3.l
vboxuser@Ubuntu-05:~$ gcc lex.yy.c -o exp3 -lfl
vboxuser@Ubuntu-05:~$ ./exp3
42
2a
78
4e
674
2a2
13
d
```