

The Fibonacci Numbers

$$F_0 = 0$$

$$F_1 = 1$$

$$F_n = F_{n-1} + F_{n-2} \quad (n \geq 2)$$

The Fibonacci Numbers

$$F_0 = 0$$

$$F_1 = 1$$

$$F_n = F_{n-1} + F_{n-2} \quad (n \geq 2)$$

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, ...

The Fibonacci Numbers

$$F_0 = 0$$

$$F_1 = 1$$

$$F_n = F_{n-1} + F_{n-2} \quad (n \geq 2)$$

0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, ...

Algorithm *fib*(*n*)

Input: An integer $n \geq 0$.

Output: F_n .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n-1) + \text{fib}(n-2)$   
5: end if
```

The Running Time of $\text{fib}(n)$

Algorithm $\text{fib}(n)$

Input: An integer $n \geq 0$.

Output: F_n .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n - 1) + \text{fib}(n - 2)$   
5: end if
```

The Running Time of $\text{fib}(n)$

Algorithm $\text{fib}(n)$

Input: An integer $n \geq 0$.

Output: F_n .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n - 1) + \text{fib}(n - 2)$   
5: end if
```

Let $T(n)$ be the number of steps when running $\text{fib}(n)$.

The Running Time of $\text{fib}(n)$

Algorithm $\text{fib}(n)$

Input: An integer $n \geq 0$.

Output: F_n .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n - 1) + \text{fib}(n - 2)$   
5: end if
```

Let $T(n)$ be the number of steps when running $\text{fib}(n)$.

If $n = 0$ or $n = 1$,

The Running Time of $\text{fib}(n)$

Algorithm $\text{fib}(n)$

Input: An integer $n \geq 0$.

Output: F_n .

```
1: if  $n \leq 1$  then  
2:   return  $n$   
3: else  
4:   return  $\text{fib}(n-1) + \text{fib}(n-2)$   
5: end if
```

Let $T(n)$ be the number of steps when running $\text{fib}(n)$.

If $n = 0$ or $n = 1$, we do

comparison " $n \leq 1$ "	}	2 steps
return value		

The Running Time of $\text{fib}(n)$

If $n \geq 2$, we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$:	1 step
call $\text{fib}(n - 1)$:	?
compute $n - 2$:	1 step
call $\text{fib}(n - 2)$:	?
compute sum of two results	:	1 step
return output	:	1 step

The Running Time of $\text{fib}(n)$

If $n \geq 2$, we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$:	1 step
call $\text{fib}(n - 1)$:	$T(n - 1)$ steps
compute $n - 2$:	1 step
call $\text{fib}(n - 2)$:	?
compute sum of two results	:	1 step
return output	:	1 step

The Running Time of $\text{fib}(n)$

If $n \geq 2$, we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$:	1 step
call $\text{fib}(n - 1)$:	$T(n - 1)$ steps
compute $n - 2$:	1 step
call $\text{fib}(n - 2)$:	$T(n - 2)$ steps
compute sum of two results	:	1 step
return output	:	1 step

The Running Time of $\text{fib}(n)$

If $n \geq 2$, we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$:	1 step
call $\text{fib}(n - 1)$:	$T(n - 1)$ steps
compute $n - 2$:	1 step
call $\text{fib}(n - 2)$:	$T(n - 2)$ steps
compute sum of two results	:	1 step
return output	:	1 step

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n - 1) + T(n - 2) + 5 & \text{if } n \geq 2. \end{cases}$$

The Running Time of $\text{fib}(n)$

If $n \geq 2$, we do

comparison " $n \leq 1$ "	:	1 step
compute $n - 1$:	1 step
call $\text{fib}(n - 1)$:	$T(n - 1)$ steps
compute $n - 2$:	1 step
call $\text{fib}(n - 2)$:	$T(n - 2)$ steps
compute sum of two results	:	1 step
return output	:	1 step

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n - 1) + T(n - 2) + 5 & \text{if } n \geq 2. \end{cases}$$

What do we do with this?

The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

In Exercise #20, you will prove that $T(n) \geq F_n$. So the running time of $\text{fib}(n)$ is at least F_n .

The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

In Exercise #20, you will prove that $T(n) \geq F_n$. So the running time of $\text{fib}(n)$ is at least F_n .

The problem is that F_n is very large. Indeed, in Exercise #19, you will prove that $F_n \geq 2^{n/2}$ for all $n \geq 6$.

The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$

In Exercise #20, you will prove that $T(n) \geq F_n$. So the running time of $\text{fib}(n)$ is at least F_n .

The problem is that F_n is very large. Indeed, in Exercise #19, you will prove that $F_n \geq 2^{n/2}$ for all $n \geq 6$.

So $\text{fib}(n)$ takes at least exponential time: $\text{fib}(200)$ will not terminate during our lifetime!

The Running Time of $\text{fib}(n)$

$$T(n) = \begin{cases} 2 & \text{if } n = 0, \\ 2 & \text{if } n = 1, \\ T(n-1) + T(n-2) + 5 & \text{if } n \geq 2. \end{cases}$$


In Exercise #20, you will prove that $T(n) \geq F_n$. So the running time of $\text{fib}(n)$ is at least F_n .

The problem is that F_n is very large. Indeed, in Exercise #19, you will prove that $F_n \geq 2^{n/2}$ for all $n \geq 6$.


So $\text{fib}(n)$ takes at least exponential time: $\text{fib}(200)$ will not terminate during our lifetime!

Why is $\text{fib}(n)$ so slow?

The Running Time of $\text{fib}(n)$



The Running Time of $\text{fib}(n)$



Too many things are called multiple times.

A Better Algorithm

Algorithm *fib2*(n)

Input: An integer $n \geq 0$.

Output: F_n .

```
1: if  $n \leq 1$  then
2:   return  $n$ 
3: else
4:   initialize array  $f[0..n]$ 
5:    $f[0] = 0$ 
6:    $f[1] = 1$ 
7:   for  $i = 2$  to  $n$  do
8:      $f[i] = f[i - 1] + f[i - 2]$ 
9:   end for
10:  return  $f[n]$ 
11: end if
```

The running time of $\text{fib2}(n)$ is *linear in n* , i.e. it is $O(n)$. In this case, we can even say that it is $\Theta(n)$.

The running time of $\text{fib2}(n)$ is *linear in n* , i.e. it is $O(n)$. In this case, we can even say that it is $\Theta(n)$.

Running time of $\text{fib}(n)$: exponential

Running time of $\text{fib2}(n)$: linear

The running time of $\text{fib2}(n)$ is *linear in n* , i.e. it is $O(n)$. In this case, we can even say that it is $\Theta(n)$.

Running time of $\text{fib}(n)$: exponential

Running time of $\text{fib2}(n)$: linear

But!

The running time of $\text{fib2}(n)$ is *linear in n* , i.e. it is $O(n)$. In this case, we can even say that it is $\Theta(n)$.

Running time of $\text{fib}(n)$: exponential

Running time of $\text{fib2}(n)$: linear

But! Is it realistic to say that $\text{fib2}(n)$ takes a linear number of steps?

The running time of $\text{fib2}(n)$ is *linear in n* , i.e. it is $O(n)$. In this case, we can even say that it is $\Theta(n)$.

Running time of $\text{fib}(n)$: exponential

Running time of $\text{fib2}(n)$: linear

But! Is it realistic to say that $\text{fib2}(n)$ takes a linear number of steps?

In our analysis, one step corresponds to

comparison	}	involving very large numbers
addition		
subtraction		

In kindergarden, we learned that

Two n -bit numbers can be added in a linear number of bit-operations.

In kindergarden, we learned that

Two n -bit numbers can be added in a linear number of bit-operations.

When running $\text{fib2}(n)$, we do roughly n additions of numbers, each of these numbers is at most F_n , each of these numbers has roughly n bits.

In kindergarden, we learned that

Two n -bit numbers can be added in a linear number of bit-operations.

When running $\text{fib2}(n)$, we do roughly n additions of numbers, each of these numbers is at most F_n , each of these numbers has roughly n bits.

Therefore, $\text{fib2}(n)$ makes a *quadratic number* of bit-operations, i.e. $O(n^2)$ bit-operations.

In kindergarden, we learned that

Two n -bit numbers can be added in a linear number of bit-operations.

When running $\text{fib2}(n)$, we do roughly n additions of numbers, each of these numbers is at most F_n , each of these numbers has roughly n bits.

Therefore, $\text{fib2}(n)$ makes a *quadratic number* of bit-operations, i.e. $O(n^2)$ bit-operations.

In Exercise #23, you will prove that the number of bit-operations done by $\text{fib}(n)$ is $O(n \cdot F_n)$.

In kindergarden, we learned that

Two n -bit numbers can be added in a linear number of bit-operations.

When running $\text{fib2}(n)$, we do roughly n additions of numbers, each of these numbers is at most F_n , each of these numbers has roughly n bits.

Therefore, $\text{fib2}(n)$ makes a *quadratic number* of bit-operations, i.e. $O(n^2)$ bit-operations.

In Exercise #23, you will prove that the number of bit-operations done by $\text{fib}(n)$ is $O(n \cdot F_n)$.

Therefore, the running time, in terms of bit-operations:

Running time of $\text{fib}(n)$: exponential

Running time of $\text{fib2}(n)$: quadratic