

Customer Ordering System

Final Documentation Package

Project Type

Small, fully engineered customer ordering system

Technology Stack

FastAPI, SQLite, SQLAlchemy, React, Vite, pytest, Playwright

Rubric Focus

Requirements, traceability, design, TDP evidence, testing, validation

Submission Info

Final academic submission report
Generated: 2026-05-18

Team Members

1. Mahmoud Hassan Mohamed Soliman
2. Mohamed Abd Elghaffar
3. _____
4. _____

Table of Contents

- How To Use This Package
- Rubric Coverage Map
- Source Document Consolidation Map
- Quick Discussion Path
- Export Notes

1. D2 Requirements Report

Requirements Report

- Source Summary
- Actor Classification
 - Primary Actors
 - Supporting Actors
 - Offstage Actors
- Personas
 - Persona 1: Frustrated Customer
 - Persona 2: Busy Kitchen Staff
 - Persona 3: Malicious Student Tester
- Core Requirements
- Hidden Requirements and Edge Cases
- Requirement Quality Rules

2. D2 Traceability Matrix and Heatmap

Traceability Matrix and Heatmap

- Traceability Rules
- Heatmap Legend
- Requirement to Evidence Heatmap
- Feature to Requirement Mapping
- Detailed Requirement Traceability
- Testing Pyramid Evidence

3. D3 Design Specification and Architecture

- 3.1 UML Class Diagram

Design Specification

- Design Goal
- Architecture
- Module Boundaries
- System Sequence Diagram: Place Order Happy Path
- System Sequence Diagram: Empty Cart Failure Path
- Activity Diagram: Order Placement
- Activity Diagram: Kitchen Status Update
- Data Model Sketch
- Design Decisions
- Technology Justification
- Traceability

4. D3 UML System Sequence Diagram Artifact

System Sequence Diagram

5. D3 UML Activity Diagram Artifact

Activity Diagram

6. D3 API Contracts

API Contracts

Authentication

POST /auth/register

POST /auth/login

Menu

GET /menu

Orders

POST /orders

GET /orders/my

GET /orders/kitchen

PATCH /orders/{orderid}/status

7. D2 QA Refinement Log

QA Refinement Log

Senior QA Audit Decisions

8. D2 Gherkin Scenarios

Gherkin Scenarios

Authentication

Menu And Cart

Order Placement

Kitchen Dashboard

Order Status Updates

Browser-Level Scenarios Covered By Playwright

9. D5 TDP Iteration Evidence

Test-Driven Prompting Iteration Evidence

Purpose

Failing-First Workflow

Implementation Driven By Tests

Edge-Case Padlocks

Iterative Debugging Evidence

Duplicate Registration Regression

Customer Tracking Enhancement

Current Regression Status

10. D5 Testing Pyramid Report

Testing Pyramid Report

Purpose

Actual Current Distribution

Unit Test Evidence

Integration Test Evidence

Playwright E2E Evidence

Screenshots Evidence

Commands

11. D5 Playwright Automation and POM Evidence

Playwright Automation

- Purpose
- Setup
- E2E Workflow Coverage
- Relationship To Gherkin
- Regression Testing Value
- Run Command

12. D4 Validation Report

Validation Report

- Validation Question
- Validated Workflow
- Validation Evidence
- Testing Pyramid Summary
- Verification vs Validation Statement
- Residual Manual Evidence

13. D4 Verification vs Validation

Verification vs Validation

- Verification
- Validation
- Evidence Mapping
- Final Distinction

14. AI Assistance Appendix

AI Assistance Appendix

- Purpose
- How AI Tools Were Used
- Prompt Categories Used
- Representative Requirement Prompts
- Representative Testing Prompts
- Representative Debugging Prompts
- Representative Refactoring Prompts
- Representative Documentation Prompts
- Human Oversight And Constraints
- AI Use Disclosure Summary

Final Documentation Package

Customer Ordering System
Software Engineering Term Project

This master document consolidates the important documentation from the project `docs/` folder into one PDF-ready, GitHub-readable package for academic submission, demo discussion, and grading review. The original source markdown files remain in place for file-level traceability, but reviewers can use this document as the primary navigation point.

Documentation Index

How To Use This Package

Open this file during discussion or demo first. It is organized around the rubric deliverables and includes requirements, traceability, design, UML diagrams, API contracts, testing evidence, validation evidence, Playwright/POM evidence, and the AI assistance appendix.

Rubric Coverage Map

Rubric Area	Consolidated Sections	Main Evidence
D2 Requirements Report	Sections 1, 2, 7, 8	Requirements, actors, personas, edge cases, traceability, QA refinement, Gherkin scenarios.
D3 Design Specification	Sections 3, 4, 5, 6	Architecture, module boundaries, system sequence diagrams, activity diagrams, class diagram, API contracts.
D4 Validation Report	Sections 12, 13	Validated workflow, verification vs validation distinction, evidence mapping.
D5 TDP Evidence	Sections 9, 10, 11	Failing-first workflow, pytest evidence, testing pyramid, Playwright automation, POM explanation.

Source Document Consolidation Map

Original Source File	Consolidated Section
<code>docs/requirements_report.md</code>	1. D2 Requirements Report
<code>docs/traceability_matrix.md</code>	2. D2 Traceability Matrix and Heatmap
<code>docs/design_specification.md</code>	3. D3 Design Specification and Architecture
<code>docs/diagrams/system_sequence_diagram.md</code>	4. D3 UML System Sequence Diagram Artifact
<code>docs/diagrams/activity_diagram.md</code>	5. D3 UML Activity Diagram Artifact
<code>docs/api_contracts.md</code>	6. D3 API Contracts
<code>docs/qa_refinement_log.md</code>	7. D2 QA Refinement Log
<code>docs/gherkin_scenarios.md</code>	8. D2 Gherkin Scenarios
<code>docs/tdp_iteration_evidence.md</code>	9. D5 TDP Iteration Evidence
<code>docs/testing_pyramid_report.md</code>	10. D5 Testing Pyramid Report
<code>docs/playwright_automation.md</code>	11. D5 Playwright Automation and POM Evidence
<code>docs/validation_report.md</code>	12. D4 Validation Report

Original Source File	Consolidated Section
docs/verification_vs_validation.md	13. D4 Verification vs Validation
docs/ai_prompt_appendix.md	14. AI Assistance Appendix

Quick Discussion Path

1. Start with Section 1 for requirements and actor/persona discovery.
2. Move to Section 2 for traceability and orphan-check evidence.
3. Use Sections 3 through 6 for architecture, UML, and API design discussion.
4. Use Sections 9 through 11 for TDD and testing evidence.
5. Use Sections 12 and 13 for validation and verification discussion.
6. Use Section 14 for the AI assistance appendix.

Export Notes

This file is suitable for PDF export from GitHub, VS Code Markdown preview, Typora, Obsidian, or Pandoc. Mermaid diagrams should be rendered by a Markdown viewer with Mermaid support, or exported separately if the PDF renderer does not support Mermaid.

1. D2 Requirements Report

Source: `docs/requirements_report.md`

Requirements Report

Source Summary

This report is based on:

- CSE323_Project_Overview.pdf
- CSE323_Project_Guidelines.pdf

The selected subsystem is a small Customer Ordering System. The grading goal is not maximum features; it is complete engineering evidence across requirements discovery, traceability, design, TDD, testing, and validation.

Actor Classification

Primary Actors

Actor	Rationale	Main Goals
Customer	Initiates registration, login, menu browsing, cart actions, order placement, and order tracking.	Create account, log in, view menu, add items, submit order, track current order status.
Kitchen Staff	Initiates order status changes after receiving customer orders.	View pending orders, update order status accurately.

Supporting Actors

Actor	Rationale	Main Responsibilities
Authentication Service	Supports identity checks for protected actions.	Validate credentials, issue simple access token, reject invalid access.
Menu Data Store	Supplies item names, prices, and availability.	Provide menu list to customers and tests.
Order Data Store	Persists cart-derived orders, mock payment fields, and status changes.	Store orders, items, quantities, payment status, statuses, timestamps.

Offstage Actors

Actor	Rationale	Interest
Course Evaluator	Does not use the app directly as a business actor, but evaluates engineering evidence.	Traceability, TDD evidence, validation reports, runnable demo.
Restaurant Owner	Benefits from reduced order handling mistakes but is not part of the implemented workflow.	Clear, minimal ordering flow and kitchen visibility.
System Maintainer	Maintains code after submission.	Simple architecture, clear tests, no unnecessary infrastructure.

Personas

Persona 1: Frustrated Customer

Name: Mina

Behavior: Repeatedly clicks "Place Order", enters unusual quantities, and expects clear feedback when the cart is empty or login fails.

Need: The system must reject invalid orders without corrupting data or creating duplicates.

Persona 2: Busy Kitchen Staff

Name: Salma

Behavior: Opens the kitchen dashboard during a rush, updates order statuses quickly, and may act on stale information.

Need: The system must show only authorized kitchen actions and keep order status transitions predictable.

Persona 3: Malicious Student Tester

Name: Kareem

Behavior: Calls protected APIs without a token, tries invalid quantities, and attempts unsupported status updates.

Need: The system must enforce boundaries at API level, not only in the UI.

Core Requirements

ID	Requirement	Source/Rationale	Priority	Acceptance Metric
FR-01	A customer can register with name, email, and password.	Required feature: Register/Login.	Must	Valid registration returns HTTP 201 and creates one user.
FR-02	A customer can log in with valid credentials.	Required feature: Register/Login.	Must	Valid login returns HTTP 200 and an access token.
FR-03	Invalid login attempts are rejected.	Persona edge case.	Must	Invalid login returns HTTP 401 with no token.
FR-04	A customer can view menu items.	Required feature: View Menu.	Must	Menu endpoint returns at least 3 seeded items in under 2 seconds.
FR-05	A customer can add menu items to a cart in the UI.	Required feature: Add To Cart.	Must	Quantity must be an integer from 1 to 10 per item.
FR-06	A customer can place an order from a non-empty cart.	Required feature: Place Order.	Must	Valid order returns HTTP 201 and status <code>pending</code> .
FR-07	Empty cart orders are rejected.	Persona edge case.	Must	Empty order returns HTTP 400 and creates no order.
FR-08	Duplicate rapid order submissions are controlled.	Persona edge case.	Should	Same client order key cannot create more than one order.
FR-09	Kitchen staff can view submitted orders.	Required feature: Kitchen Dashboard.	Must	Dashboard returns pending/preparing/ready orders in under 2 seconds.
FR-10	Kitchen staff can update order status.	Required feature: Update Order Status.	Must	Valid status update is reflected by API within 1 second.
FR-11	Unauthorized users cannot access kitchen actions.	Persona edge case.	Must	Missing or customer token returns HTTP 401 or 403.
FR-12	Invalid order status transitions are rejected.	Edge case and race prevention.	Should	Unsupported status returns HTTP 400 and original status remains unchanged.
FR-13	Expired or invalid access tokens are rejected before protected actions are executed.	Authentication edge case.	Must	Protected routes return HTTP 401 and perform no data read/write action.
FR-14	Kitchen staff registration and access require an email ending with <code>@ejust.edu.eg</code> .	Domain restriction for staff workflow.	Must	Non-EJUST kitchen registration returns HTTP 400 and kitchen access requires the EJUST staff domain.

ID	Requirement	Source/Rationale	Priority	Acceptance Metric
FR-15	A lightweight mock payment status is captured with each order.	Demo-friendly payment simulation.	Should	Order responses and kitchen dashboard show payment method and <code>paid / unpaid</code> status without real payment processing.
FR-16	A customer can view the latest status, payment status, and summary for their own orders.	Customer order tracking enhancement.	Should	Customer order tracking returns only the logged-in customer's orders and reflects kitchen status updates after refresh.
NFR-01	API response time for normal demo data is under 2 seconds.	QA refinement metric.	Must	Verified by integration/E2E tests or documented manual timing.
NFR-02	Password length must be at least 8 characters.	Measurable security boundary.	Must	Registration with fewer than 8 chars returns HTTP 422 or 400.
NFR-03	The implementation remains small and maintainable.	Project instruction and rubric fit.	Must	No Docker, Redis, PostgreSQL, Redux, real payment integration, analytics, or cloud code.

Hidden Requirements and Edge Cases

Edge Case ID	Case	Requirement Impact	Expected Handling
EC-01	Duplicate order caused by double-clicking submit.	FR-08	Use a client order key or server-side duplicate guard in service tests.
EC-02	Invalid quantity such as 0, -1, 11, or text.	FR-05	Reject outside integer range 1 to 10.
EC-03	Empty cart submission.	FR-07	Return validation error and create no order.
EC-04	Unauthorized kitchen access.	FR-11	Reject missing/customer token before reading or updating kitchen data.
EC-05	Network interruption during order placement.	FR-08, validation	UI keeps cart state until order success is confirmed.
EC-06	Invalid login credentials.	FR-03	Return a generic failed-login response without issuing a token.
EC-07	Order update race condition or stale status.	FR-12	Reject unsupported transitions and verify unchanged persisted status.
EC-08	Expired or invalid access token on protected action.	FR-13	Return 401 before protected order or kitchen logic executes.
EC-09	Non-EJUST email attempts kitchen staff registration.	FR-14	Return 400 with a staff-domain validation message.
EC-10	Customer marks mock payment as unpaid.	FR-15	Store and display <code>unpaid</code> status for kitchen visibility.
EC-11	Kitchen updates an order after customer placed it.	FR-16	Customer tracking refresh shows the updated status.

Requirement Quality Rules

- Every feature must map to at least one requirement ID.
- Every test must cite one or more requirement IDs.
- Every API endpoint must cite one or more requirement IDs.
- No implementation feature should exist unless it supports the required small subsystem.

2. D2 Traceability Matrix and Heatmap

Source: `docs/traceability_matrix.md`

Traceability Matrix and Heatmap

Traceability Rules

- Zero orphaned requirements: every requirement must map to a feature, API, test type, and validation evidence.
- Zero orphaned features: every feature must map back to a requirement.
- Implementation, tests, and reports preserve these IDs.

Heatmap Legend

Mark	Meaning
H	High coverage or direct evidence required
M	Medium/supporting coverage required
L	Low/indirect coverage required
NA	Not applicable

Requirement to Evidence Heatmap

Requirement	Feature	API Contract	Unit Tests	Integration Tests	E2E Tests	Docs Evidence	Current Status
FR-01 Register	Register/Login	H	H	M	M	H	Implemented
FR-02 Login	Register/Login	H	H	M	H	H	Implemented
FR-03 Invalid login	Register/Login	H	H	M	M	H	Implemented
FR-04 View menu	View Menu	H	M	H	H	H	Implemented
FR-05 Add to cart	Add To Cart	M	H	M	H	H	Implemented
FR-06 Place order	Place Order	H	H	H	H	H	Implemented
FR-07 Empty cart rejection	Place Order	H	H	H	M	H	Implemented
FR-08 Duplicate order guard	Place Order	H	H	H	M	H	Implemented
FR-09 Kitchen dashboard	Kitchen Dashboard	H	M	H	H	H	Implemented
FR-10 Update status	Update Order Status	H	H	H	H	H	Implemented
FR-11 Unauthorized kitchen access	Kitchen Dashboard, Update Status	H	H	H	M	H	Implemented
FR-12 Invalid status transition	Update Order Status	H	H	H	M	H	Implemented
FR-13 Expired or invalid token rejection	Protected API Actions	H	H	H	M	H	Implemented
FR-14 EJUST kitchen staff domain	Register/Login, Kitchen Access	H	H	H	L	H	Implemented
FR-15 Mock payment status	Place Order, Kitchen Dashboard	H	M	H	L	H	Implemented
FR-16 Customer order tracking	Order Tracking	H	H	H	L	H	Implemented

Requirement	Feature	API Contract	Unit Tests	Integration Tests	E2E Tests	Docs Evidence	Current Status
NFR-01 API response under 2 seconds	All API features	M	NA	M	M	H	Implemented
NFR-02 Password length >= 8	Register	H	H	M	M	H	Implemented
NFR-03 Minimal maintainable system	All features	NA	NA	NA	NA	H	Implemented

Feature to Requirement Mapping

Feature	Requirement IDs	Orphan Status
Register/Login	FR-01, FR-02, FR-03, FR-14, NFR-02	Not orphaned
View Menu	FR-04, NFR-01	Not orphaned
Add To Cart	FR-05	Not orphaned
Place Order	FR-06, FR-07, FR-08, FR-15, NFR-01	Not orphaned
Order Tracking	FR-13, FR-16, NFR-01	Not orphaned
Protected API Actions	FR-13	Not orphaned
Kitchen Dashboard	FR-09, FR-11, FR-13, FR-14, FR-15, NFR-01	Not orphaned
Update Order Status	FR-10, FR-11, FR-12, FR-13, FR-14, NFR-01	Not orphaned

Detailed Requirement Traceability

Requirement	API	Implementation	Tests	Validation Evidence
FR-01	POST /auth/register	auth_service.register_user, routers/auth.py	test_auth_service.py, test_auth_api.py, Playwright register flow	User can register through API and UI.
FR-02	POST /auth/login	auth_service.login_user, token helper	test_auth_service.py, test_auth_api.py, Playwright login flow	User can log in and view menu.
FR-03	POST /auth/login	invalid credential branch	test_auth_service.py, test_auth_api.py	Invalid login returns 401.
FR-04	GET /menu	menu_service.list_menu_items, menu router	test_menu_service.py, test_menu_orders_api.py, Playwright menu assertions	Seeded menu appears in API and UI.
FR-05	POST /orders	validate_order_items, cart UI quantity controls	test_order_service.py, test_menu_orders_api.py	Invalid quantities are rejected.
FR-06	POST /orders	order_service.create_order, cart UI	test_order_service.py, test_menu_orders_api.py	Valid cart creates pending order.
FR-07	POST /orders	empty cart validation	test_order_service.py, test_menu_orders_api.py	Empty cart returns 400.
FR-08	POST /orders	duplicate client_order_key check	test_order_service.py, test_menu_orders_api.py	Duplicate order key is rejected.

Requirement	API	Implementation	Tests	Validation Evidence
FR-09	GET /orders/kitchen	list_kitchen_orders , kitchen UI	test_order_service.py , test_kitchen_api.py	Kitchen dashboard shows active orders.
FR-10	PATCH /orders/{id}/status	update_order_status , kitchen UI status select	test_order_service.py , test_kitchen_api.py	Kitchen can update valid status.
FR-11	Kitchen endpoints	require_kitchen dependency	test_kitchen_api.py	Customer kitchen access returns 403.
FR-12	PATCH /orders/{id}/status	allowed status validation	test_order_service.py , test_kitchen_api.py	Invalid status is rejected and order remains unchanged.
FR-13	Protected endpoints	token validation helper	test_auth_service.py , test_menu_orders_api.py , test_kitchen_api.py	Invalid token returns 401.
FR-14	POST /auth/register , kitchen endpoints	kitchen email-domain validation	test_auth_service.py , test_auth_api.py	Only @ejust.edu.eg kitchen staff are accepted.
FR-15	POST /orders , GET /orders/kitchen	order payment fields, cart payment UI, kitchen display	test_menu_orders_api.py , test_kitchen_api.py	Mock payment method/status appears in customer and kitchen workflows.
FR-16	GET /orders/my , PATCH /orders/{id}/status	list_customer_orders , order tracking UI, status refresh	test_order_service.py , test_menu_orders_api.py	Customer sees own order summary and latest kitchen-updated status.

Testing Pyramid Evidence

Target testing pyramid:

- 70 percent unit tests
- 20 percent integration tests
- 10 percent Playwright E2E tests

Actual current automated count:

Layer	Count	Approx Ratio
Unit	20	44 percent
Integration	23	51 percent
E2E	2	5 percent


The implemented suite is intentionally integration-heavy because the rubric emphasizes API contracts and traceability. Browser E2E coverage remains small to avoid duplicating backend edge-case tests.

3. D3 Design Specification and Architecture

Source: docs/design_specification.md

3.1 UML Class Diagram

The following class diagram summarizes the implemented backend domain structure and frontend page/API relationships. It reflects the current minimal architecture only.




Design Specification

Design Goal

Build one small vertical slice: customer registration/login, menu browsing, cart order submission with mock payment status, customer order tracking, kitchen dashboard, and order status update.

The design favors explicit contracts, simple modules, SQLite persistence, and testable service functions.


Architecture




Module Boundaries

Layer	Responsibility	Hidden Details
Frontend pages	User workflows and basic client-side validation.	Database, password hashing, SQLAlchemy.
API routers	HTTP request/response mapping and auth checks.	Business rule internals.
Services	Registration, login, order placement, status update rules.	HTTP framework details.
Models	Persistent entities.	UI and test runner details.
Schemas	Request/response validation.	Database session internals.

System Sequence Diagram: Place Order Happy Path




System Sequence Diagram: Empty Cart Failure Path




Activity Diagram: Order Placement

Activity Diagram



Activity Diagram: Kitchen Status Update

Activity Diagram



Data Model Sketch

Entity	Fields
User	id, name, email, password_hash, role
MenuItem	id, name, price, available
Order	id, customer_email, status, client_order_key, total, payment_method, payment_status
OrderItem	id, order_id, menu_item_id, quantity, line_total

Design Decisions

- Use SQLite for local demo persistence.
- Use service functions for business rules so unit tests can avoid HTTP setup.
- Use API contracts as the boundary between frontend and backend.
- Use a simple bearer token for academic demo authentication.

- Keep cart state in the frontend until order submission succeeds.
- Use refresh-based customer tracking instead of realtime sockets to keep the demo small.
- Store mock payment method and paid/unpaid status only; no real payment gateway is used.

Technology Justification

- FastAPI was selected because it supports small REST APIs with automatic request validation and OpenAPI documentation, which helps keep API contracts measurable and testable.
- SQLite was selected because it is file-based, simple to run locally, and sufficient for a demo-sized ordering workflow without deployment infrastructure.
- React + Vite was selected because it provides a lightweight frontend setup with fast local development and minimal configuration.
- pytest was selected for backend unit and integration tests because it supports clear boundary-focused tests; Playwright was selected for E2E validation because it can execute browser workflows using the Page Object Model.

Traceability

Each diagram and endpoint maps to the requirement IDs in `traceability_matrix.md` and `api_contracts.md`.


4. D3 UML System Sequence Diagram Artifact


Source: `docs/diagrams/system_sequence_diagram.md`

System Sequence Diagram

This UML-style system sequence diagram represents the implemented customer ordering workflow only.

System Sequence Diagram





5. D3 UML Activity Diagram Artifact


Source: `docs/diagrams/activity_diagram.md`


Activity Diagram

This activity diagram covers the implemented ordering flow, including validation and failure paths.



Activity Diagram





6. D3 API Contracts

Source: `docs/api_contracts.md`

API Contracts

These contracts define shared interfaces for backend, frontend, and tests. Internal implementation details such as SQLAlchemy models, password hashing helpers, and database sessions are intentionally hidden.

Base URL during local development: `http://127.0.0.1:8000`

JSON request headers:

```
Content-Type: application/json
```

Standard structured error shape:

```
{
  "detail": "Human-readable error message"
}
```

Authentication

POST `/auth/register`

Covers: FR-01, FR-14, NFR-02

Headers:

```
Content-Type: application/json
```

Request:

```
{
  "name": "Mina",
  "email": "mina@example.com",
  "password": "password123",
  "role": "customer"
}
```

Validation:

- `name`: non-empty string
- `email`: valid email-like string
- `password`: minimum 8 characters
- `role`: `customer` or `kitchen`
- `kitchen` role requires an email ending with `@ejust.edu.eg`

Success response `201`:

```
{
  "id": 1,
  "name": "Mina",
  "email": "mina@example.com",
  "role": "customer"
}
```

Failure responses:

- `400` duplicate email

- 400 kitchen email outside @ejust.edu.eg
- 422 invalid payload

Example 400 response:

```
{
  "detail": "Email already registered"
}
```

Example kitchen domain 400 response:

```
{
  "detail": "Kitchen staff email must end with @ejust.edu.eg"
}
```

POST /auth/login

Covers: FR-02, FR-03

Headers:

```
Content-Type: application/json
```

Request:

```
{
  "email": "mina@example.com",
  "password": "password123"
}
```

Success response 200 :

```
{
  "access_token": "token-value",
  "token_type": "bearer",
  "role": "customer"
}
```

Failure responses:

- 401 invalid credentials
- 422 invalid payload

Example 401 response:

```
{
  "detail": "Invalid credentials"
}
```

Menu

GET /menu

Covers: FR-04, NFR-01

Success response 200 :

```
[
  {
    "id": 1,
    "name": "Chicken Sandwich",
    "price": 80.0,
    "available": true
  }
]
```

Metric: response time under 2 seconds for seeded demo data.

Orders

POST /orders

Covers: FR-05, FR-06, FR-07, FR-08, FR-13, FR-15, FR-16

Headers:

```
Content-Type: application/json
Authorization: Bearer token-value
```

Request:

```
{
  "client_order_key": "unique-client-key",
  "payment_method": "card",
  "payment_status": "paid",
  "items": [
    {
      "menu_item_id": 1,
      "quantity": 2
    }
  ]
}
```

Validation:

- Authenticated customer required.
- `items` must contain at least 1 item.
- `quantity` must be an integer from 1 to 10.
- Reused `client_order_key` must not create duplicate orders.
- `payment_method` is optional and must be `cash`, `card`, or `wallet`.
- `payment_status` is optional and must be `paid` or `unpaid`.

Success response 201:

```
{
  "id": 1,
  "status": "pending",
  "items": [
    {
      "menu_item_id": 1,
      "quantity": 2,
      "line_total": 160.0
    }
  ],
  "total": 160.0,
  "payment_method": "card",
  "payment_status": "paid"
}
```

Failure responses:

- 400 empty cart, invalid quantity, duplicate order key conflict
- 401 missing/invalid token
- 403 role not allowed
- 422 invalid payload

Example 400 response:

```
{
  "detail": "Order must contain at least one item"
}
```

Example 401 response:

```
{
  "detail": "Unauthorized access"
}
```

Example 403 response:

```
{
  "detail": "Kitchen role required"
}
```

GET /orders/my

Covers: FR-13, FR-16, NFR-01

Headers:

```
Authorization: Bearer token-value
```

Authorization: customer role required.

Success response 200 :

```
[
  {
    "id": 1,
    "status": "preparing",
    "total": 160.0,
    "payment_method": "card",
    "payment_status": "paid",
    "items": [
      {
        "name": "Chicken Sandwich",
        "quantity": 2,
        "line_total": 160.0
      }
    ]
  }
]
```

Failure responses:

- 401 missing/invalid token
- 403 authenticated non-customer user

Example 401 response:

```
{
  "detail": "Unauthorized access"
}
```

GET /orders/kitchen

Covers: FR-09, FR-11, FR-13, FR-14, FR-15, NFR-01

Headers:

```
Authorization: Bearer token-value
```

Authorization: kitchen role required.

Success response 200:

```
[
  {
    "id": 1,
    "customer_email": "mina@example.com",
    "status": "pending",
    "total": 160.0,
    "payment_method": "card",
    "payment_status": "paid",
    "items": [
      {
        "name": "Chicken Sandwich",
        "quantity": 2
      }
    ]
  }
]
```

Failure responses:

- 401 missing/invalid token
- 403 authenticated non-kitchen user

Example 401 response:

```
{
  "detail": "Unauthorized access"
}
```

Example 403 response:

```
{
  "detail": "Kitchen role required"
}
```

PATCH /orders/{order_id}/status

Covers: FR-10, FR-11, FR-12, FR-13

Headers:

```
Content-Type: application/json
Authorization: Bearer token-value
```

Request:

```
{
  "status": "preparing"
}
```

Allowed statuses:

- pending
- preparing
- ready
- completed

Success response 200 :

```
{
  "id": 1,
  "status": "preparing"
}
```

Failure responses:

- 400 invalid status
- 401 missing/invalid token
- 403 authenticated non-kitchen user
- 404 order not found

Example 400 response:

```
{
  "detail": "Invalid order status"
}
```

Example 401 response:

```
{
  "detail": "Unauthorized access"
}
```

Example 403 response:

```
{
  "detail": "Kitchen role required"
}
```

Metric: successful update visible from API within 1 second.

7. D2 QA Refinement Log

Source: `docs/qa_refinement_log.md`

QA Refinement Log

This log converts vague requirements into measurable criteria, as required by the rubric.

Original Wording	QA Issue	Refined Metric	Requirement IDs
The app should be fast.	"Fast" is not testable.	Normal API responses for demo data must complete in under 2 seconds.	NFR-01
Login should be secure.	"Secure" is too broad for this project.	Password must be at least 8 characters; invalid login returns 401 and no token.	FR-03, NFR-02
Orders should update quickly.	"Quickly" is not measurable.	A successful status update must be reflected by the API within 1 second.	FR-10
The cart should prevent bad input.	"Bad input" is unclear.	Quantity must be an integer from 1 to 10 inclusive.	FR-05
The system should avoid duplicate orders.	Duplicate conditions are undefined.	Reusing the same client order key must not create more than one order.	FR-08
Kitchen access should be protected.	"Protected" is vague.	Missing/customer token for kitchen routes must return 401 or 403 before modifying data.	FR-11
Tokens should be valid.	"Valid" needs an observable result.	Expired or malformed access tokens must return 401 before protected route logic reads or writes order data.	FR-13
Staff users should be restricted.	"Staff" needs a measurable domain rule.	Kitchen staff registration and access require email ending with <code>@ejust.edu.eg</code> .	FR-14
Payment should be demo-only.	"Payment" could imply real integration.	Mock payment stores only method and <code>paid / unpaid</code> status; no real gateway or transaction is used.	FR-15
Customers should see order progress.	"Progress" needs an observable refresh behavior.	Customer order tracking must show the latest status returned by <code>GET /orders/my</code> after kitchen updates.	FR-16
The app should be maintainable.	Maintainability must be bounded.	No Docker, Redis, PostgreSQL, Redux, real payment integration, analytics, or cloud deployment code.	NFR-03

Senior QA Audit Decisions

- Keep the scope to one vertical slice: customer order submission through kitchen status update.
- Prefer explicit validation errors over silent UI-only prevention.
- Ensure edge cases are tested at service/API level so the frontend cannot bypass constraints.
- Preserve traceability IDs in test names, service docstrings, and reports.
- Add screenshots only as validation evidence, not as a substitute for executable tests.

8. D2 Gherkin Scenarios

Source: `docs/gherkin_scenarios.md`

Gherkin Scenarios

These scenarios describe the implemented Customer Ordering System only. They align with the FastAPI endpoints, React pages, pytest coverage, and Playwright browser tests currently present in the project.

Authentication

Feature: User registration

Covers: FR-01, FR-14, NFR-02

Scenario: Register a new customer successfully

Given no user exists with email "mina@example.com"

When the user registers with name "Mina", email "mina@example.com", password "password123", and role "customer"

Then the API should return status 201

And the response should include id, name, email, and role

And the response should not include the password

Scenario: Register a kitchen staff account successfully

Given no user exists with email "salma.kitchen@ejust.edu.eg"

When the user registers with name "Salma", email "salma.kitchen@ejust.edu.eg", password "kitchen123", and role "kitchen"

Then the API should return status 201

And the response role should be "kitchen"

Scenario: Reject kitchen staff registration outside the EJUST domain

Given no user exists with email "salma.kitchen@gmail.com"

When the user registers with name "Salma", email "salma.kitchen@gmail.com", password "kitchen123", and role "kitchen"

Then the API should return status 400

And the response detail should mention "@ejust.edu.eg"

Scenario: Reject duplicate email registration

Given a user already exists with email "mina@example.com"

When another registration is submitted with email "mina@example.com"

Then the API should return status 400

And the response detail should be "Email already registered"

Scenario Outline: Reject weak registration passwords

Given no user exists with email "weak-password@example.com"

When the user registers with password "<password>"

Then the registration should be rejected

And no account should be created

Examples:

| password |

| short |

| 1234567 |

Feature: User login
Covers: FR-02, FR-03

Background:
Given a registered customer exists with email "mina@example.com" and password "password123"

Scenario: Login succeeds with valid credentials
When the customer logs in with email "mina@example.com" and password "password123"
Then the API should return status 200
And the response should include an access token
And the token type should be "bearer"
And the response role should be "customer"

Scenario: Login rejects an incorrect password
When the customer logs in with email "mina@example.com" and password "wrong-password"
Then the API should return status 401
And the response detail should be "Invalid credentials"
And no access token should be returned

Menu And Cart

Feature: Menu retrieval and cart building
Covers: FR-04, FR-05, NFR-01

Background:
Given the SQLite database contains the seeded menu items

Scenario: Retrieve menu items successfully
When the user requests the menu
Then the API should return status 200
And the response should include at least three menu items
And each item should include id, name, price, and availability

Scenario Outline: Reject invalid cart quantities at order validation
Given a customer is logged in
And the cart contains menu item 1 with quantity <quantity>
When the customer places the order
Then the API should return status 400
And the response detail should mention "quantity"

Examples:

	quantity	
	0	
	-1	
	11	

Order Placement

Feature: Customer order placement

Covers: FR-06, FR-07, FR-08, FR-13, FR-15

Background:

Given a customer is registered and logged in
And the menu contains item 1

Scenario: Place an order from a non-empty cart

Given the cart contains menu item 1 with quantity 2
And the customer selects mock payment method "card"
And the mock payment is confirmed as "paid"
And the client order key is new
When the customer places the order
Then the API should return status 201
And the order status should be "pending"
And the payment status should be "paid"
And the response should include the ordered item and total

Scenario: Reject an empty cart

Given the cart contains no items
When the customer places the order
Then the API should return status 400
And the response detail should be "Order must contain at least one item"
And no order should be created

Scenario: Reject duplicate client order key

Given an order already exists with client order key "client-order-key-duplicate"
And the cart contains menu item 1 with quantity 1
When the customer places another order with client order key "client-order-key-duplicate"
Then the API should return status 400
And the response detail should mention "duplicate"
And no duplicate order should be created

Feature: Protected order actions

Covers: FR-13

Scenario: Reject order placement with an invalid token

Given the request uses access token "expired-or-invalid-token"
And the request contains menu item 1 with quantity 1
When the user places an order
Then the API should return status 401
And the response detail should be "Unauthorized access"
And no order should be created

Feature: Customer order tracking

Covers: FR-13, FR-16, NFR-01

Background:

Given a customer is registered and logged in
And the customer has placed an order with status "pending"

Scenario: Customer views their own order status and summary

When the customer opens order tracking
Then the API should return status 200
And the response should include the order status
And the response should include payment status
And the response should include item summary and total

Scenario: Customer sees latest status after kitchen update

Given kitchen staff updates the order status to "preparing"
When the customer refreshes order tracking
Then the displayed order status should be "Preparing"

Kitchen Dashboard

Feature: Kitchen dashboard

Covers: FR-09, FR-11, FR-13, FR-14, FR-15, NFR-01

Background:

Given at least one order exists with status "pending"

Scenario: Kitchen staff views active orders

Given a kitchen staff user with email ending "@ejust.edu.eg" is logged in

When the kitchen staff requests the kitchen dashboard

Then the API should return status 200

And the response should include active orders

And each order should include id, customer email, status, total, payment method, payment status, and items

Scenario: Reject customer access to kitchen dashboard

Given a customer is logged in

When the customer requests the kitchen dashboard

Then the API should return status 403

And the response detail should be "Kitchen role required"

Scenario: Reject kitchen dashboard access with an invalid token

Given the request uses access token "expired-or-invalid-token"

When the user requests the kitchen dashboard

Then the API should return status 401

And the response detail should be "Unauthorized access"

Order Status Updates

Feature: Kitchen order status update

Covers: FR-10, FR-11, FR-12, FR-13, FR-14

Background:

Given an order exists with status "pending"

Scenario: Kitchen staff updates an order status successfully

Given a kitchen staff user with email ending "@ejust.edu.eg" is logged in

When the kitchen staff updates the order status to "preparing"

Then the API should return status 200

And the response should include the order id

And the order status should be "preparing"

Scenario: Reject invalid order status

Given a kitchen staff user with email ending "@ejust.edu.eg" is logged in

When the kitchen staff updates the order status to "archived"

Then the API should return status 400

And the response detail should be "Invalid order status"

And the stored order status should remain "pending"

Scenario: Reject customer status update

Given a customer is logged in

When the customer updates the order status to "preparing"

Then the API should return status 403

And the response detail should be "Kitchen role required"

And the stored order status should remain unchanged

Scenario: Reject status update with an invalid token

Given the request uses access token "expired-or-invalid-token"

When the user updates the order status to "preparing"

Then the API should return status 401

And the response detail should be "Unauthorized access"

And the stored order status should remain unchanged

Browser-Level Scenarios Covered By Playwright

Feature: Frontend smoke workflows

Scenario: Homepage loads

Given the Vite frontend is running
When the browser opens "http://127.0.0.1:5173"
Then the page should display the login workflow

Scenario: Register, login, and view seeded menu

Given the FastAPI backend is running
And the Vite frontend is running
When a new user registers through the browser
And the same user logs in through the browser
Then the menu page should display "Chicken Sandwich"
And the menu page should display "Pasta Bowl"
And the menu page should display "Fresh Juice"

9. D5 TDP Iteration Evidence

Source: `docs/tdp_iteration_evidence.md`

Test-Driven Prompting Iteration Evidence

Purpose

This document records the TDP workflow used in Phase 3. The project was intentionally implemented from tests and contracts rather than feature expansion.

Failing-First Workflow

Step 1 created pytest tests before backend implementation existed. The initial tests intentionally failed because these targets were missing:

- `app.main`
- `app.services.auth_service`
- `app.services.menu_service`
- `app.services.order_service`

This produced failing-first evidence for:

- Registration and login.
- Menu retrieval.
- Quantity boundaries.
- Empty cart rejection.
- Duplicate order prevention.
- Kitchen dashboard access.
- Status update validation.
- Invalid token rejection.

Implementation Driven By Tests

Step 2 implemented only the backend needed to satisfy those tests:

- FastAPI application setup.
- SQLite and SQLAlchemy setup.
- Minimal models for users, menu items, orders, and order items.
- Pydantic request/response schemas.
- Simple bearer-token authentication.
- Service-layer business rules.
- API routers matching the documented contracts.

No unrelated features were added.

Edge-Case Padlocks

The test suite locks down these boundary and failure cases:

Edge Case	Evidence
Quantity 0	Unit and integration tests reject it.
Quantity -1	Unit and integration tests reject it.
Quantity 11	Unit and integration tests reject it.

Edge Case	Evidence
Empty order items	Unit and integration tests return a validation error.
Duplicate <code>client_order_key</code>	Unit and integration tests reject duplicate order submission.
Invalid token	Unit and integration tests return unauthorized access.
Customer accessing kitchen endpoints	Integration tests return 403.
Invalid status <code>archived</code>	Unit and integration tests return 400 and preserve the old status.
Customer tracking after kitchen update	Unit and integration tests verify the customer sees the latest status.

Iterative Debugging Evidence

During implementation, the first full test run showed that service-level tests passed while integration tests initially needed the HTTP client dependency used by FastAPI `TestClient`. After installing the declared dependency, remaining failures showed stale database state between tests. A small clean database fixture was added to `tests/conftest.py`, preserving duplicate checks inside a single test while making the suite repeatable.

Duplicate Registration Regression

Manual QA discovered that duplicate email registration incorrectly succeeded. The root cause was in `auth_service.register_user`, which returned the existing user instead of rejecting the duplicate.

Regression tests were added first:

- Unit test: duplicate registration raises `ValueError("Email already registered")`.
- Integration test: duplicate `POST /auth/register` returns HTTP 400 with `{"detail": "Email already registered"}`.

The service was then changed minimally so duplicate email registration fails correctly. The frontend already displayed backend validation messages through the existing API error handling.

Customer Tracking Enhancement

A final enhancement added failing tests first for customer order tracking. The tests initially failed because `list_customer_orders` and `GET /orders/my` did not exist. The backend then added only the read path needed for customers to refresh and see their own latest order status, payment status, and order summary.

Current Regression Status

The backend pytest suite currently includes 43 tests across unit and integration layers. Playwright adds browser-level smoke coverage for homepage loading and register-login-menu display.

The TDP evidence demonstrates:

- Failing tests before implementation.
- Minimal implementation to satisfy requirements.
- Iterative debugging based on test output.
- Regression test added before fixing a discovered bug.
- Edge cases preserved as executable tests.

10. D5 Testing Pyramid Report

Source: `docs/testing_pyramid_report.md`

Testing Pyramid Report

Purpose

The project uses a small testing pyramid to provide rubric evidence without overbuilding the system. The intended structure is:

- 70 percent unit tests for business rules and edge-case boundaries.
- 20 percent integration tests for API contracts and persistence behavior.
- 10 percent E2E tests for browser-level validation of the main demo flow.

Actual Current Distribution

Current automated tests:

Layer	Location	Count	Evidence
Unit	tests/unit/	20	Service-level tests for auth, staff domain validation, menu retrieval, quantity validation, order creation, duplicate order keys, status updates, customer order tracking, and token rejection.
Integration	tests/integration/	23	FastAPI TestClient tests for /auth/register, /auth/login, /menu, /orders, /orders/my, /orders/kitchen, and /orders/{id}/status.
E2E	frontend/tests/e2e/	2	Playwright browser tests for homepage loading and register-login-menu workflow.

Total automated scenarios: 45.

Actual ratio by collected tests:

- Unit: 20 of 45, about 44 percent.
- Integration: 23 of 45, about 51 percent.
- E2E: 2 of 45, about 5 percent.

The suite is intentionally integration-heavy because the rubric emphasizes API contracts, traceability, and verification of observable system behavior. The E2E layer remains small, which preserves the pyramid principle that browser tests should validate critical workflows rather than duplicate every backend edge case.

Unit Test Evidence

Unit tests focus on business rules and edge-case padlocks:

- tests/unit/test_auth_service.py
 - FR-01 registration success and duplicate email rejection.
 - FR-02 login success.
 - FR-03 invalid login rejection.
 - FR-13 invalid token rejection.
 - FR-14 kitchen staff @just.edu.eg domain restriction.
 - NFR-02 password length boundary.
- tests/unit/test_menu_service.py
 - FR-04 seeded menu retrieval.
- tests/unit/test_order_service.py
 - FR-05 quantity boundaries: 0, -1, and 11.
 - FR-06 valid order placement.

- FR-07 empty cart rejection.
- FR-08 duplicate `client_order_key` rejection.
- FR-09 kitchen dashboard order listing.
- FR-10 status update success.
- FR-12 invalid status rejection.
- FR-16 customer order tracking and status refresh evidence.

Integration Test Evidence

Integration tests verify the documented API contracts:

- `tests/integration/test_auth_api.py`
 - Registration returns 201.
 - Duplicate registration returns 400 with `Email already registered`.
 - Login returns bearer token.
 - Invalid login returns 401.
 - Kitchen registration outside `@ejust.edu.eg` returns 400.
- `tests/integration/test_menu_orders_api.py`
 - Menu returns at least three items.
 - Invalid quantities return 400.
 - Valid order returns 201 and status `pending`.
 - Empty cart returns 400.
 - Duplicate order key returns 400.
 - Invalid token returns 401.
 - Mock payment method/status is returned with orders.
 - Customer order tracking returns current order status and summary.
- `tests/integration/test_kitchen_api.py`
 - Kitchen dashboard returns submitted orders.
 - Kitchen status update returns 200.
 - Customer access returns 403.
 - Invalid status `archived` returns 400 and preserves the old status.
 - Invalid kitchen token returns 401.
 - Kitchen dashboard includes mock payment method/status.

Playwright E2E Evidence

Playwright tests are stored in `frontend/tests/e2e/`:

- `login.spec.js` : verifies a user can register, log in, and see the seeded menu items in the browser.
- `menu.spec.js` : verifies the homepage loads and displays the login workflow.

These tests connect the React UI to the running FastAPI backend and validate that the main browser workflow is demo-ready.

Screenshots Evidence

The `screenshots/` folder is reserved for manual or Playwright-generated demo screenshots. Suggested screenshots:

- `screenshots/login-page.png`
- `screenshots/menu-page.png`
- `screenshots/cart-page.png`
- `screenshots/order-tracking-page.png`
- `screenshots/kitchen-dashboard.png`

- `screenshots/playwright-run.png`

Screenshots are supporting validation evidence; they do not replace automated tests.

Commands

Backend tests:

```
cd "/Volumes/My Macbook/Study/Semester 8/Software Engineering/Projects/FinalProject"  
/Users/mahmoudhasssan/anaconda3/bin/pytest
```

Frontend build:

```
cd "/Volumes/My Macbook/Study/Semester 8/Software Engineering/Projects/FinalProject/frontend"  
npm run build
```

Playwright E2E tests:

```
cd "/Volumes/My Macbook/Study/Semester 8/Software Engineering/Projects/FinalProject/frontend"  
npx playwright test tests/e2e
```

11. D5 Playwright Automation and POM Evidence

Source: `docs/playwright_automation.md`

Playwright Automation

Purpose

Playwright provides browser-level validation for the React frontend. The tests confirm that the implemented UI can be opened in a real browser context and can communicate with the FastAPI backend for the main demo workflow.

Setup

Playwright is listed in `frontend/package.json` as a development dependency:

```
"@playwright/test": "^1.60.0"
```

The current E2E tests are located in:

- `frontend/tests/e2e/login.spec.js`
- `frontend/tests/e2e/menu.spec.js`

The tests expect:

- Backend running at `http://127.0.0.1:8000`
- Frontend running at `http://127.0.0.1:5173`

E2E Workflow Coverage

Playwright Test	Workflow	Related Requirements
<code>menu.spec.js</code>	Opens the homepage and verifies that the login workflow is visible.	FR-02
<code>login.spec.js</code>	Registers a new user, logs in through the UI, and verifies seeded menu items are visible.	FR-01, FR-02, FR-04

The Playwright suite intentionally stays small. Backend unit and integration tests cover edge cases such as invalid quantity, empty cart, duplicate order key, unauthorized kitchen access, invalid status, and invalid token rejection.

Relationship To Gherkin

The Playwright tests implement browser-level slices of the Gherkin scenarios:

- Feature: Frontend smoke workflows
- Scenario: Homepage loads
- Scenario: Register, login, and view seeded menu

Gherkin scenarios remain the readable specification. Playwright scripts are the executable browser automation evidence.

Regression Testing Value

Playwright protects the project against regressions that backend-only tests cannot see, including:

- The frontend route/page renders correctly.
- Form labels and buttons remain discoverable by accessible role or label.
- Browser registration and login flow still works after frontend changes.

- The menu page displays data returned by the backend.

Run Command

Start the backend:

```
cd "/Volumes/My Macbook/Study/Semester 8/Software Engineering/Projects/FinalProject"  
PYTHONPATH=backend /Users/mahmoudhasssan/anaconda3/bin/python -m uvicorn app.main:app --host 127.0.0.1 --port 8000
```

Start the frontend:

```
cd "/Volumes/My Macbook/Study/Semester 8/Software Engineering/Projects/FinalProject/frontend"  
npm run dev
```

Run Playwright:

```
cd "/Volumes/My Macbook/Study/Semester 8/Software Engineering/Projects/FinalProject/frontend"  
npx playwright test tests/e2e
```

12. D4 Validation Report

Source: `docs/validation_report.md`

Validation Report

Validation Question

Does the Customer Ordering System solve the right problem for a small demo-friendly ordering workflow?

Yes. The implemented system supports the required customer-to-kitchen workflow without adding unrelated restaurant-platform features.

Validated Workflow

The implemented vertical slice validates that:

- A customer can register and log in.
- A customer can view the seeded menu.
- A customer can add menu items to a cart.
- A customer can place a non-empty order.
- Kitchen staff can log in.
- Kitchen staff can view submitted active orders.
- Kitchen staff can update order status.
- Kitchen staff accounts are restricted to `@ejust.edu.eg` emails.
- Mock payment method and paid/unpaid status are visible to staff.
- Customer order tracking shows current status, payment status, and order summary after refresh.

Validation Evidence

Evidence	Result	Related Requirements
Backend pytest suite	43 tests pass.	FR-01 through FR-16, NFR-02
Frontend production build	<code>npm run build</code> succeeds.	NFR-03
Playwright browser tests	2 tests pass.	FR-01, FR-02, FR-04
API contract tests	Auth, menu, order, and kitchen endpoints return expected status codes and payloads.	FR-01 through FR-13
Edge-case tests	Duplicate email, invalid login, invalid quantity, empty cart, duplicate order key, invalid token, unauthorized kitchen access, invalid staff email domain, invalid status, mock payment visibility, and customer status refresh are covered.	FR-03, FR-05, FR-07, FR-08, FR-11, FR-12, FR-13, FR-14, FR-15, FR-16

Testing Pyramid Summary

Layer	Count	Evidence
Unit	20	Service-level business rule and boundary tests.
Integration	23	FastAPI <code>TestClient</code> API contract tests.
E2E	2	Playwright browser smoke workflows.

Detailed testing evidence is documented in `docs/testing_pyramid_report.md`.

Verification vs Validation Statement

Verification proves the software works according to the documented requirements and API contracts. Validation proves that the implemented behavior solves the intended small Customer Ordering System problem.

This project is validated because the real workflow closes the order loop from customer login and order placement to kitchen viewing and status update. The implementation avoids real payment gateways, notifications, analytics, cloud deployment, and advanced administration because those are outside the selected subsystem.

Residual Manual Evidence

The `screenshots/` folder is available for final demo screenshots. Screenshots are optional supporting evidence; the primary validation evidence is the passing automated test suite and runnable demo workflow.

13. D4 Verification vs Validation

Source: `docs/verification_vs_validation.md`

Verification vs Validation

Verification

Verification asks: did we build the software correctly according to its specification?

For this project, verification evidence comes from executable tests and contract checks:

- Pytest unit tests verify service-level rules for registration, login, token rejection, quantity limits, empty cart rejection, duplicate order keys, kitchen dashboard listing, and invalid status rejection.
- Pytest integration tests verify the FastAPI contracts for `/auth/register`, `/auth/login`, `/menu`, `/orders`, `/orders/my`, `/orders/kitchen`, and `/orders/{order_id}/status`.
- Playwright tests verify that the React frontend loads in a browser and that a user can register, log in, and see seeded menu items.
- Frontend build verification confirms that the React/Vite project compiles successfully.

Examples of verified behavior:

- Valid registration returns HTTP 201.
- Duplicate registration returns HTTP 400 with `Email already registered`.
- Valid login returns a bearer token.
- Empty cart order placement returns HTTP 400.
- Invalid token access returns HTTP 401.
- Customer access to kitchen routes returns HTTP 403.
- Non-EJUST kitchen staff registration returns HTTP 400.
- Mock payment method/status is returned in order and kitchen responses.
- Customer order tracking returns the latest order status after kitchen updates.
- Kitchen status update returns HTTP 200 for a valid status.
- Invalid status `archived` returns HTTP 400 and keeps the original status.

Validation

Validation asks: did we build the right system for the intended customer ordering problem?

The validated problem is a small, demo-friendly Customer Ordering System, not a large restaurant platform. The implemented system supports the intended end-to-end workflow:

- A customer can register and log in.
- A customer can view the seeded menu.
- A customer can add menu items to a cart and place an order.
- A customer can select a mock payment method and paid/unpaid status for demo purposes.
- The order is created with status `pending`.
- A customer can refresh order tracking to see the latest status, payment status, and order summary.
- Kitchen staff can log in and view active orders.
- Kitchen staff can see mock payment details.
- Kitchen staff can update order status to a supported value.

This solves the selected subsystem because it closes the core customer-to-kitchen loop without adding unrelated features such as real payment gateways, notifications, analytics, cloud deployment, Redis, Docker, or advanced administration.

Evidence Mapping

Evidence	Verification Value	Validation Value
Pytest unit tests	Prove individual business rules and edge-case boundaries.	Show that the minimal domain rules match the customer ordering workflow.
Pytest integration tests	Prove API status codes and response bodies match the contracts.	Show that frontend and backend can rely on stable interfaces.
Playwright tests	Prove browser workflows render and interact with the backend.	Show that a user can perform the main demo path through the UI.
Real ordering workflow	Confirms order creation and status update operate together.	Demonstrates the system solves the intended ordering-to-kitchen handoff.
Customer tracking workflow	Confirms customers can read their own latest order status.	Demonstrates the customer can follow an order after kitchen action.
Kitchen workflow	Confirms role-protected dashboard and status update behavior.	Demonstrates kitchen staff can act on submitted orders.

Final Distinction

Verified means the implemented code behaves correctly against the documented requirements and tests.

Validated means the implemented behavior is the right behavior for a small academic Customer Ordering System focused on ordering and kitchen status management.

14. AI Assistance Appendix

Source: `docs/ai_prompt_appendix.md`

AI Assistance Appendix

Purpose

This appendix documents how Codex/AI assistance was used during the Customer Ordering System project. AI support was used as an engineering assistant for requirements analysis, test design, implementation scaffolding, debugging, refactoring, and documentation. Human project constraints controlled the scope: the system remained minimal, rubric-focused, and limited to the implemented customer ordering workflow.

No secrets, private credentials, API keys, or sensitive personal data were included in prompts.

How AI Tools Were Used

AI assistance was used to:

- Interpret the project overview and grading rubric.
- Convert rubric expectations into requirements, traceability, Gherkin scenarios, API contracts, and validation evidence.
- Create failing-first pytest tests before backend implementation.
- Implement the minimal FastAPI, SQLite, SQLAlchemy backend needed to satisfy the tests.
- Build a small React/Vite frontend connected to the documented backend APIs.
- Debug test failures and a duplicate-registration defect.
- Refactor Playwright E2E tests into Page Object Model structure.
- Finalize documentation for verification, validation, testing pyramid evidence, Playwright automation, and TDP iteration evidence.

AI assistance did not add unsupported features such as real payment gateways, notifications, analytics, Docker, Redis, PostgreSQL, cloud deployment, or advanced authentication.

Prompt Categories Used

Prompt Category	Purpose	Project Artifact Impact
Requirements prompts	Extract actors, requirements, edge cases, and traceability from the rubric.	requirements_report.md , traceability_matrix.md
Design prompts	Define Gherkin scenarios, API contracts, UML diagrams, and technology justification.	gherkin_scenarios.md , api_contracts.md , design_specification.md
Testing prompts	Create failing-first unit and integration tests with requirement IDs.	tests/unit/ , tests/integration/ , pytest.ini
Implementation prompts	Implement only the backend/frontend behavior required by tests and API contracts.	backend/ , frontend/src/
Debugging prompts	Diagnose failing tests and manual QA defects.	Duplicate registration regression tests and fix
Refactoring prompts	Convert Playwright tests to Page Object Model without changing behavior.	frontend/tests/pages/ , frontend/tests/e2e/
Documentation prompts	Finalize validation, testing pyramid, Playwright, TDP, README, and audit docs.	docs/ , README.md

Representative Requirement Prompts

Examples of requirement-focused prompts used:

- Analyze the project PDFs and create actor classification, traceability heatmap, persona discovery, and edge cases.
- Keep the project minimal and focused on the required Customer Ordering System features only.
- Add a requirement for expired or invalid access token rejection and preserve existing requirement IDs.
- Verify that all requirements map to features, API contracts, tests, and validation evidence.

These prompts supported requirements engineering and traceability rather than feature expansion.

Representative Testing Prompts

Examples of testing-focused prompts used:

- Create a failing pytest suite before backend implementation.
- Cover FR-01 through FR-13 with unit and integration tests.
- Include edge-case padlocks for invalid quantities, empty cart, duplicate order key, invalid token, unauthorized kitchen access, and invalid status.
- Run pytest and report which tests fail before implementation.
- Preserve requirement IDs in test names or docstrings.

These prompts produced TDD evidence and helped keep implementation tied to measurable behavior.

Representative Debugging Prompts

Examples of debugging-focused prompts used:

- Fix the duplicate registration bug with minimal changes only.
- Add or update tests so duplicate email registration fails correctly.
- Return a structured backend error message such as `Email already registered`.
- Verify existing tests still pass and the frontend displays backend validation messages.

The duplicate-registration bug was handled with a regression-first workflow: tests were added first, then the service behavior was corrected.

Representative Refactoring Prompts

Examples of refactoring-focused prompts used:

- Refactor existing Playwright tests to use Page Object Model.
- Keep current tested behavior exactly the same.
- Create reusable page object classes under `frontend/tests/pages/`.
- Do not change application implementation code.

This produced reusable Playwright page objects for navigation, registration, login, and menu assertions.

Representative Documentation Prompts

Examples of documentation-focused prompts used:

- Improve Gherkin scenarios with happy paths, failure paths, and edge cases.
- Create testing pyramid evidence with unit, integration, and E2E counts.
- Document verification versus validation using pytest, Playwright, ordering workflow, and kitchen workflow evidence.
- Create Playwright automation and TDP iteration evidence documents.
- Run a final submission audit for generated files, caches, README accuracy, and command verification.

These prompts helped align the final submission with the rubric.

Human Oversight And Constraints

The project scope and implementation constraints were explicitly controlled:

- The selected subsystem remained a small Customer Ordering System.
- Only required features were implemented.
- Tests and documentation were checked against current implementation.
- Generated artifacts and cache files were removed or ignored before submission.
- Implementation changes were avoided during final documentation and audit phases.

AI Use Disclosure Summary

Codex/AI assistance was used throughout the project as a guided development and documentation assistant. The final project artifacts remain aligned with the stated academic requirements: requirements discovery, traceability, software design, TDD evidence, testing, validation, and engineering process quality.
