# Positional Encodings Anchor Spatial Structure in Vision Transformers: A Geometric Perspective on Robustness

**Anonymous Author(s)**
Affiliation
Address
email

## Abstract

Positional embeddings (PEs) in Vision Transformers (ViTs) are known to impact performance and robustness, but their role in shaping internal spatial representations is not well understood. In this work, we study how different forms of PEs influence the representational geometry of ViTs and how these changes relate to robustness under content-disrupting distribution shifts. We introduce a metric, the Spatial Similarity Distance Correlation (SSDC), to quantify spatial structure in token representations. Using this metric, we show that ViTs trained without PEs still develop non-trivial spatial structure, but this structure is driven by visual content and collapses under token permutation. In contrast, we find that all PEs considered (learned absolute, sinusoidal, and rotary) are associated with a consistent shift toward an index-anchored spatial organization. Representations in these models remain stable under perturbations that disrupt content, and exhibit substantially improved robustness to such distributional shifts. We further show that while different PEs produce distinct depth-wise trajectories of spatial structure, their robustness properties are largely similar (with secondary variation across encoding schemes), suggesting that robustness appears to depend on the presence of a stable positional reference frame more than it depends on the specific encoding mechanism. These results offer a geometric account of how positional encodings shape internal representations, with implications for the principled design of future encoding schemes.

## 1 Introduction

Vision Transformers (ViTs) model images as sequences of patch tokens processed by self-attention [Dosovitskiy et al., 2021]. Unlike convolutional architectures, they lack built-in inductive biases toward locality and translation equivariance, and instead rely on positional embeddings (PEs) to inject spatial information, enabling the model to distinguish tokens originating from different locations.

While PEs are designed to provide positional information, this design does not determine how that signal is integrated into internal representations. In particular, it remains unclear whether positional information organizes token representations into similarity structures anchored to absolute indices, or whether spatial structure continues to arise primarily from visual content.

Prior work shows that ViTs retain substantial performance even when positional information is removed or degraded [Dosovitskiy et al., 2021, Chu et al., 2023], suggesting that spatial relationships can partially emerge from patch content alone. This raises a central question: if spatial structure can arise without explicit positional guidance, what functional role do positional embeddings play?

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

Existing studies have largely addressed this question through downstream performance comparisons or architectural variations. While informative, these approaches provide limited insight into how positional information shapes internal representations. In particular, it remains unclear whether different positional encoding schemes (learned absolute, sinusoidal, or rotary) induce distinct spatial reasoning strategies, or whether their effects on robustness arise from a shared mechanism.

In this work, we adopt a geometric perspective. We analyze the evolution of token representations across the transformer stack using tools from representational geometry [Raghu et al., 2021], introducing the Spatial Similarity Distance Correlation (SSDC) as a probe of spatial structure. Critically, we use SSDC in conjunction with a random permutation intervention at inference to distinguish whether spatial organization is anchored to token indices or driven by patch content. We compare models trained with learned absolute positional embeddings (APE), sinusoidal encodings, rotary embeddings (RoPE), and no positional embeddings, and evaluate their robustness to distributional shifts.

Our central finding is that the specific encoding mechanism matters less than the presence of a consistent positional signal. We show that:

- **Positional encodings are associated with index-based spatial organization:** All PE types shift ViTs away from purely content-driven spatial structure toward representations that remain partially anchored to token indices under permutation.
- **This shift, not the encoding form, is associated with robustness:** Despite differing in how spatial structure develops across depth, APE, sinusoidal, and RoPE models exhibit broadly comparable robustness to content-disrupting distributional shifts (despite consistent but smaller differences between encoding schemes), while models lacking index-based organization are substantially more fragile.
- **A stable positional reference frame is strongly implicated in robustness:** Using Random Permutation Training (RPT), which preserves PEs but destroys index-to-location consistency, we find that robustness is greatly reduced when a consistent positional frame cannot be learned.

Together, these results provide a unified, geometric account of how positional encodings shape internal representations and why they remain critical for robust visual recognition, though we emphasize that the evidence is intervention-based rather than strictly causal.

## 2 Related Work

### Positional Information in Vision Transformers

The standard Vision Transformer (ViT) breaks the permutation invariance of self-attention by adding learnable absolute positional embeddings (PEs) to patch tokens [Dosovitskiy et al., 2021], establishing the dominant paradigm for spatial encoding. However, ViTs retain substantial performance when positional information is degraded or removed [Dosovitskiy et al., 2021, Chu et al., 2023], suggesting that spatial structure can partially emerge from patch content alone.

Similar observations have been reported beyond vision. Recent work on decoder-only transformers shows that models trained without PEs can recover positional information implicitly and tend to rely on relative positions in practice [Kazemnejad et al., 2023]. Earlier findings in convolutional networks further demonstrate that substantial positional information can be learned implicitly from architectural biases such as zero-padding [Islam* et al., 2020]. Together, these results suggest that explicit positional signals are not strictly required for structured spatial information to emerge.

This creates a central puzzle: if spatial structure can arise without explicit positional guidance, what functional role do PEs play? Prior work has primarily addressed this question through architectural variants [d'Ascoli et al., 2022, Liu et al., 2021, Heo et al., 2024] or performance comparisons [Dosovitskiy et al., 2021, Chu et al., 2023], leaving their mechanistic impact on internal representations largely unexplored.

### Representational Analysis of Transformers

A separate line of work studies the geometry and dynamics of transformer representations. Early analyses compare ViT and CNN representations [Raghu et al., 2021], revealing differences in spatial organization. Subsequent work examines how attention transforms representations [Kobayashi

et al., 2021], how representational rank evolves with depth [Dong et al., 2021], and how token representations tend to homogenize in deeper layers [Bhojanapalli et al., 2021]. The residual stream framework provides a useful lens for analyzing these dynamics [Elhage et al., 2021]. However, these approaches do not isolate the causal role of positional embeddings, nor do they connect representational structure to robustness.

**Robustness of Visual Models**

Vision Transformers exhibit distinct robustness profiles compared to convolutional networks. Prior work shows that transformers are generally more robust to certain spatial perturbations but can be more sensitive to texture-based changes [Bhojanapalli et al., 2021]. Additional studies report favorable out-of-distribution generalization properties for ViTs [Paul and Chen, 2022], connecting to broader findings on shape versus texture bias in visual recognition [Geirhos et al., 2019]. While the impact of positional embeddings on robustness has been observed (particularly that models trained with PEs exhibit better robustness profiles than models trained without them) [Mao et al., 2021], the relationship between a model's spatial organization strategy (whether anchored to absolute position or inferred from content) and its robustness to distributional shifts remains poorly understood.

**Our Contribution**

We connect these lines of work by showing that positional embeddings are associated with a shift toward index-based spatial organization, and that this shift (rather than the specific encoding mechanism) appears to be a dominant correlate of robustness. Using SSDC and controlled permutation interventions (RPT and RPI), we provide a geometric account of how positional information shapes internal representations and why it improves robustness.

# 3 Preliminaries

## 3.1 Vision Transformer Architecture and Positional Encodings

All models are Vision Transformers trained from scratch on ImageNet-100 (a subset of Imagenet-1K) [Deng et al., 2009], with approximately 22M parameters (details in Appendix A). Images are partitioned into fixed-size patches, projected into token embeddings, and processed by a stack of self-attention and feedforward layers.

Since self-attention is permutation invariant, positional encodings are required to inject spatial information. We consider three commonly used PE schemes, all adapted to 2D grids:

**Learned Absolute Positional Embeddings (APE):** learnable vectors added to token embeddings before the first transformer block, establishing a fixed index-to-location mapping.

**Sinusoidal Positional Embeddings (SPE):** fixed, deterministic encodings constructed from sinusoidal functions applied independently along spatial axes and added to token embeddings.

**Rotary Positional Embeddings (RoPE):** position-dependent rotations applied to query and key vectors within each attention layer, introducing positional information multiplicatively.

These approaches differ in parameterization (learned vs. fixed) and integration (additive vs. multiplicative), enabling comparison of how different positional signals shape internal representations.

## 3.2 Index-Based and Content-Based Spatial Organization

We distinguish between two qualitatively distinct modes of spatial organization.

**Index-based spatial organization** refers to representations whose similarity structure depends systematically on token position. Tokens that are spatially proximate tend to have more similar representations by virtue of their indices, and this structure persists under disruptions to patch content. This definition is behavioral and does not assume explicit coordinate representations.

**Content-based spatial organization** refers to representations in which similarity is driven primarily by patch content. Spatial structure arises indirectly from natural image statistics and degrades under transformations that disrupt content or token ordering.

In practice, models may exhibit both behaviors; the key distinction is which signal dominates.

# 4 Methods

## 4.1 Residual Stream Geometry

At selected layers, we extract the residual stream as a matrix $R \in \mathbb{R}^{T \times C}$, where $T$ is the number of tokens and $C$ the embedding dimension. We compute pairwise cosine similarities between unit-normalized token representations to form a symmetric similarity matrix, averaged across the batch dimension.

## 4.2 Spatial Similarity Distance Correlation

Let $S \in \mathbb{R}^{T \times T}$ denote the token similarity matrix, and let $p_i \in \mathbb{Z}^2$ denote the spatial coordinates of token $i$. Define the spatial distance matrix $D$ by $D_{ij} = \|p_i - p_j\|_1$. We define SSDC as the Spearman rank correlation between similarity and negative spatial distance over all token pairs:

$$\mathrm{SSDC} = \rho_{\mathrm{Spearman}} \left( \{S_{ij}\}_{i<j},\ \{-D_{ij}\}_{i<j} \right).$$

Higher SSDC values indicate that spatially proximate tokens tend to have more similar representations. We use Spearman rank correlation to remain agnostic to the precise functional form relating spatial distance and representational similarity.

Importantly, SSDC should be interpreted as a coarse proxy for spatial organization rather than a direct measurement of a specific mechanism. Absolute values may reflect multiple factors (e.g., data statistics, architectural biases), and therefore SSDC is primarily used comparatively (to track changes across depth and to measure sensitivity to controlled interventions).

## 4.3 Random Permutation at Inference (RPI)

To distinguish index-based from content-based organization, we randomly permute token order at inference while keeping positional indices fixed. This breaks the correspondence between token order and spatial location. Under this setup, spatial structure driven purely by patch content is expected to be disrupted, as spatially adjacent tokens no longer correspond to neighboring image patches. In contrast, if a model has learned representations that depend systematically on token indices via positional signals, some spatial structure may persist or be partially recoverable.

As a result, SSDC under RPI should be interpreted as an indicator of the extent to which spatial organization depends on token indices, rather than as a definitive separation between index-based and content-based mechanisms.

## 4.4 Random Permutation during Training (RPT)

Random Permutation Training (RPT) applies a fresh random permutation to the token sequence at every forward pass during training. At each batch, patch tokens are shuffled while positional embeddings remain fixed to their original indices, breaking the consistent mapping between token index and spatial location. This prevents the model from learning a stable index-based spatial organization despite the presence of positional signals.

## 4.5 Positional Embedding Magnitude Scaling

We scale positional embeddings at inference by a factor $\alpha$, replacing $\mathbf{e}_i$ with $\alpha \mathbf{e}_i$. This provides a continuous intervention on positional signal strength without retraining. We apply this to APE and sinusoidal models; an equivalent scaling for RoPE is not directly defined due to its multiplicative formulation.

## 4.6 Fragility Score

We quantify robustness using the Fragility Score (FS):

$$\mathrm{FS} = 1 - \frac{A_{\mathrm{shift}}}{A_{\mathrm{normal}}},$$

where $A_{\mathrm{normal}}$ and $A_{\mathrm{shift}}$ denote accuracy on clean and shifted data. Higher values indicate greater sensitivity to distributional shift.




(a) **Evolution of SSDC across depth on untrained ablated models**

(b) **Evolution of SSDC across depth on untrained ablated models, trained ablated models, and intact (trained with APE) models**

Figure 1: (a) SSDC grows weakly and remains at a relatively high value across layers, indicating static spatial correlations induced by architectural and data priors rather than learning.
(b) While untrained ablated models exhibit relatively high but slowly varying SSDC consistent with static data and architectural priors, trained ablated models display a sharp increase in early layers, indicating the emergence of learned spatial structure despite the absence of explicit positional encoding.

# 5 Results

## 5.1 Architectural Priors Induce Static Spatial Correlations at Initialization

**Experimental Setup:** We evaluate SSDC across all layers of untrained ablated models on the Imagenet-100 dataset. Unless stated otherwise, all reported results are averaged over 4 random seeds. Shaded regions in figures indicate variability across runs (±1 standard deviation).

**Results:** The untrained ablated model exhibits a substantial non-zero SSDC (approximately 0.57–0.64) with only a weak, gradual increase across depth (Figure 1a). This behavior is highly consistent across runs and reflects static spatial correlations induced by architectural priors and the inherent structure of natural images, rather than learned spatial reasoning.

Crucially, this baseline highlights that SSDC should not be interpreted as a standalone metric whose absolute magnitude reflects the presence or strength of learned spatial organization. Even in the absence of training, relatively high SSDC values emerge. Instead, the layer-wise dynamics of SSDC (in particular, the rate and pattern of change across depth) are the informative signal. In contrast to the shallow, nearly static progression observed here, trained models exhibit rapid and structured changes in SSDC (e.g., sharp increases in early layers), indicating the emergence of learned spatial structure.

This establishes a static baseline, allowing us to distinguish genuinely learned spatial organization from correlations that arise purely from architectural and data-driven effects.

## 5.2 Emergence of Spatial Structure Without Positional Encoding

**Experimental Setup:** To investigate whether spatial structure can emerge in the absence of explicit positional information, we evaluate SSDC across all layers of untrained ablated models, trained ablated models, and trained intact (APE) models on the Imagenet-100 dataset.

**Results:** Figure 1b compares the layer-wise evolution of SSDC for an untrained ablated model, a trained ablated model, and a trained model with positional embeddings. The untrained ablated model exhibits relatively high SSDC (approximately 0.57–0.64) with only weak growth across depth, reflecting static spatial correlations induced by architectural and data priors rather than learning.

In contrast, the trained ablated model shows a qualitatively different trajectory: starting from lower SSDC, it exhibits a sharp increase in early layers followed by continued growth. This dynamic pattern closely resembles that of the trained model with positional embeddings. The key distinction is not




(a) **Models with positional encodings.** APE, Sinusoidal PEs, and RoPE models exhibit substantial SSDC recovery under RPI, indicating spatial organization anchored to token indices. RoPE shows a gradual accumulation of structure across depth, while APE and Sinusoidal PEs exhibit earlier, injection-like peaks.

(b) **Models without a stable positional reference frame.** Ablated and RPT models collapse to near-zero SSDC across all layers under RPI, indicating that their spatial structure is entirely content-driven and does not survive token permutation.

Figure 2: **SSDC under random permutation at inference (RPI).** RPI disrupts the correspondence between token content and spatial position. Only models that anchor spatial structure to token indices exhibit SSDC recovery after permutation. In contrast, models lacking a consistent positional mapping collapse to near-zero SSDC, revealing a purely content-based spatial organization.

absolute SSDC magnitude, but its evolution—static in the untrained model, structured and rapidly changing after training.

These results indicate that non-trivial spatial structure emerges during training even without positional embeddings. This is consistent with the non-trivial performance of ablated models and prior evidence that transformers can implicitly recover positional information.

We emphasize that this emergent structure is not equivalent to that induced by positional embeddings. Rather, this establishes that spatial organization can arise without explicit positional signals, motivating a more precise characterization of its underlying mechanism in the next section.

### 5.3 Disentangling Index-Based and Content-Based Spatial Organization

**Experimental Setup:** To distinguish between index-based and content-based spatial organization, we evaluate SSDC across all layers under a *Random Permutation at Inference* (RPI) intervention. Concretely, patch tokens are randomly permuted before being processed by the transformer, while positional embedding indices (when present) remain fixed to their original spatial locations. This operation disrupts the correspondence between token content and spatial position, while preserving any mapping between token indices and positional embeddings.

Under this setup, any spatial structure that arises purely from patch content is destroyed, as spatially adjacent tokens no longer correspond to neighboring image patches. In contrast, if a model has learned to anchor its representations to absolute token indices via positional embeddings, spatial structure can be re-established through the fixed positional signal. As a result, *SSDC recovery under RPI* serves as a probe for index-based spatial organization: models that rely on absolute positional information exhibit non-trivial SSDC despite permutation, whereas models that rely on content-based cues collapse to near-zero SSDC.

We evaluate this behavior across models trained with learned absolute positional embeddings (APE), sinusoidal encodings, rotary embeddings (RoPE), no positional embeddings (ablated), and under Random Permutation Training (RPT).

**Results:** Models trained without positional embeddings exhibit a complete collapse of SSDC under RPI across all layers, suggesting that their spatial structure is predominantly content-driven under this probe. Despite exhibiting non-trivial SSDC in the unpermuted setting (Section 5.2), this structure does not survive disruption of patch content, indicating that it is not anchored to token indices.




(a) **Gaussian Blur ($\sigma = 2.5$).** Fragility scores under a mild perturbation that removes high-frequency detail while largely preserving global spatial structure. Differences between models are present but compressed, reflecting the weaker disruption of content-based cues.

(b) **JPEG Compression (quality = 5).** Fragility scores under a strong content-disrupting transformation. Models with positional encodings exhibit substantially lower fragility than ablated and RPT models, with RoPE achieving the lowest fragility overall.

Figure 3: **Robustness to distributional shifts.** Fragility scores across model variants under two perturbation regimes. The gap between models with and without a stable positional reference frame is most pronounced under strong content disruption (JPEG), while remaining consistent but attenuated under milder perturbations (Gaussian blur).

In contrast, all models trained with positional embeddings show substantial SSDC recovery under RPI, indicating representations that are more consistent with index-anchored spatial organization. However, the nature of this recovery differs across encoding schemes. For APE and sinusoidal embeddings, SSDC exhibits a rapid increase in early layers following permutation, reaching a peak within the first few layers before stabilizing or slightly decreasing. This behavior suggests that spatial structure is injected early in the network via additive positional signals.

RoPE models display a qualitatively different trajectory: SSDC increases more gradually and continues to grow with depth, without a pronounced early-layer peak. This indicates that positional information is integrated progressively throughout the network, consistent with its multiplicative incorporation into attention mechanisms.

RPT models, despite having positional embeddings present, fail to exhibit meaningful SSDC recovery under RPI, behaving similarly to fully ablated models. This suggests that the mere presence of positional embeddings is insufficient; a consistent mapping between token indices and spatial locations during training appears necessary for index-based spatial organization to emerge.

Taken together, these results establish that positional embeddings are associated with a shift from content-based to index-based spatial organization, and that this shift depends critically on the stability of the positional reference frame rather than on the architectural presence of positional signals alone.

### 5.4 Robustness to Content-Preserving and Content-Disrupting Perturbations

**Experimental Setup:** To evaluate how spatial organization strategy influences robustness, we measure performance under distribution shifts that perturb image content while preserving global structure. We consider two transformations:

**JPEG Compression:** We apply aggressive compression (quality = 5), introducing blocking artifacts that strongly disrupt local texture statistics while preserving coarse spatial layout. This provides a targeted probe of reliance on content-based cues.

**Gaussian Blur:** We apply Gaussian blur with standard deviation $\sigma = 2.5$, attenuating high-frequency detail while preserving low-frequency structure. This constitutes a milder perturbation than JPEG.

For each model, we compute the *Fragility Score* (FS), defined as the relative drop in accuracy under each transformation.

We include **Random Permutation Training (RPT)** as a critical control. RPT preserves the presence of positional embeddings but prevents the formation of a stable index-based spatial organization, allowing us to distinguish between the mere presence of positional signals and the emergence of a consistent positional reference frame.

We emphasize that these robustness results are limited to content-disrupting perturbations (e.g., compression artifacts and blur) and do not necessarily generalize to other forms of distribution shift such as geometric transformations or semantic shifts.

**Results:** Under JPEG compression, models with positional encodings exhibit substantially lower fragility (APE and sinusoidal: $\sim$0.43, RoPE: $\sim$0.30) than ablated and RPT models ($\sim$0.66). This large gap indicates that robustness to severe content degradation is strongly influenced by the presence of a stable positional reference frame. Within PE-based models, RoPE consistently achieves lower fragility, suggesting a secondary effect of the encoding mechanism.

Under Gaussian blur, the same ordering is preserved but differences are attenuated (RoPE: $\sim$0.15, APE: $\sim$0.17–0.20, sinusoidal: $\sim$0.22, RPT: $\sim$0.25, ablated: $\sim$0.30). Because blur preserves global structure, it provides a weaker test of reliance on content-based cues, reducing the separation between models.

Taken together, these results support a two-level interpretation: (1) the emergence of a stable positional reference frame appears to be a dominant factor associated with robustness, and (2) the specific encoding mechanism introduces secondary variation, with RoPE exhibiting consistently lower fragility.

Crucially, the poor robustness of RPT models shows that the mere presence of positional embeddings is insufficient: robustness appears to rely on learning a consistent mapping between token indices and spatial locations. This provides evidence for a relationship between the spatial organization patterns identified earlier and downstream robustness.

### 5.5 Linking Index-Based Spatial Organization to Robustness via Positional Scaling

**Experimental Setup:** To probe the relationship between spatial organization and robustness, we require a controlled intervention that selectively disrupts index-based spatial structure while preserving the rest of the model. We achieve this by scaling the magnitude of learned absolute positional embeddings (APE) at inference time by a factor $\alpha \in [0, 1]$, without retraining.

While this intervention operates on positional embeddings, our goal is not to study positional signal strength per se, but to use it as a mechanism to continuously degrade the model's *index-based spatial organization*. To measure the integrity of this organization, we evaluate Spatial Similarity Distance Correlation (SSDC) under Random Permutation at Inference (RPI), as introduced in Section 5.3. Under RPI, any recovered spatial structure must be anchored to token indices rather than content. We therefore interpret SSDC recovery as a proxy for the presence of index-based spatial organization.

Importantly, SSDC recovery approaching zero does not imply that the model is actively constructing a content-based spatial structure; rather, it indicates that index-based spatial organization is no longer preserved under permutation.

To summarize this behavior compactly, we define:

$$\Delta\mathrm{SSDC} = \mathrm{SSDC}_{\text{layer 1}} - \mathrm{SSDC}_{\text{layer 0}},$$

which captures the immediate recovery of spatial structure after the first encoder block under RPI. Thus, $\Delta\mathrm{SSDC}$ serves as a measure of index-based spatial organization.

We jointly analyze $\Delta\mathrm{SSDC}$ and the Fragility Score (FS) across varying $\alpha$. For clarity, we report representative magnitudes illustrating distinct regimes, with the full results provided in Appendix B.1 (and Appendix B.2 for Sinusoidal PEs).

| $\alpha$ | $\Delta$SSDC (RPI) | | Fragility Score | |
|---|---|---|---|---|
| | Mean | Std | Mean | Std |
| 1.0 | 0.4725 | 0.0228 | 0.4338 | 0.0127 |
| 0.8 | 0.3125 | 0.0259 | 0.4780 | 0.0146 |
| 0.7 | 0.1845 | 0.0342 | 0.5145 | 0.0145 |
| 0.5 | 0.0475 | 0.0083 | 0.5975 | 0.0202 |
| 0.4 | 0.0000 | 0.0000 | 0.6272 | 0.0189 |

Table 1: Effect of positional embedding magnitude $\alpha$ on index-based spatial organization and robustness. $\Delta$SSDC (measured under RPI) captures the recovery of index-based spatial structure after the first encoder block. As $\alpha$ decreases, $\Delta$SSDC collapses, indicating the breakdown of index-based spatial organization, while fragility increases sharply in the same regime before plateauing once spatial structure is lost.

**Results:** We observe a clear correspondence between the degradation of index-based spatial organization and the loss of robustness.

At high magnitudes ($\alpha \geq 0.9$), models exhibit strong SSDC recovery ($\Delta\text{SSDC} \approx 0.37$–$0.47$), indicating intact index-based spatial organization. In this regime, fragility remains relatively low and stable (FS $\approx 0.44$–$0.46$), suggesting that robustness is preserved when spatial structure is intact.

As $\alpha$ decreases into an intermediate regime ($0.8 \geq \alpha \geq 0.5$), SSDC recovery drops sharply ($\Delta\text{SSDC} \approx 0.30 \rightarrow 0.02$), reflecting the progressive breakdown of index-based spatial organization. This degradation is accompanied by a pronounced increase in fragility (FS $\approx 0.48 \rightarrow 0.63$). Notably, the most significant increases in fragility occur precisely where SSDC recovery is actively decreasing, indicating that robustness degradation is strongly correlated with the loss of spatial structure.

Below a critical threshold ($\alpha \leq 0.4$), SSDC recovery collapses to zero ($\Delta\text{SSDC} \approx 0$), indicating that index-based spatial organization is no longer recoverable under permutation. In this regime, fragility continues to increase, but only marginally (FS $\approx 0.65 \rightarrow 0.685$). This suggests that once spatial organization is fully disrupted, further degradation in robustness is no longer correlated with changes in spatial structure, but instead reflects secondary effects such as reduced representational quality or distribution mismatch induced by scaling.

A complementary effect is observed at high magnitudes: when index-based spatial organization is already fully intact, small reductions in $\alpha$ have limited impact on fragility. Together, these observations reveal three regimes: (1) a stable regime with intact spatial organization and low fragility, (2) a transition regime where spatial structure degrades and fragility increases sharply, and (3) a collapsed regime where spatial organization is absent and fragility plateaus.

Overall, these results provide evidence that robustness may be driven in part by the presence of index-based spatial organization. Positional scaling serves only as a means of intervention; the observed changes in robustness track the degradation of spatial structure rather than the magnitude of the positional signal itself.

## 6 Conclusion

We studied how positional encodings shape spatial organization in Vision Transformers and its relationship to robustness under content-disrupting perturbations. Using SSDC and permutation-based interventions, we found that spatial structure emerges even without positional encodings, but remains content-driven and collapses under token permutation. Models with positional encodings exhibit representations more consistent with index-anchored spatial organization. Across experiments, robustness under content-disrupting shifts is closely associated with a stable positional reference frame rather than the mere presence of positional embeddings — evidenced by RPT models and positional scaling, where robustness degrades alongside the breakdown of index-anchored spatial structure. Differences between encoding schemes persist but appear secondary. Overall, our results suggest positional encodings contribute to robustness by supporting a stable positional reference frame, though we emphasize this conclusion is based on intervention-based evidence and identifies a strong relationship rather than a fully isolated causal mechanism.

# References


Srinadh Bhojanapalli, Ayan Chakrabarti, Daniel Glasner, Daliang Li, Thomas Unterthiner, and Andreas Veit. Understanding robustness of transformers for image classification. pages 10211–10221, 10 2021. doi: 10.1109/ICCV48922.2021.01007.

Xiangxiang Chu, Zhi Tian, Bo Zhang, Xinlong Wang, and Chunhua Shen. Conditional positional encodings for vision transformers. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=3KWnuT-R1bh`.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE Conference on Computer Vision and Pattern Recognition*, pages 248–255, 2009. doi: 10.1109/CVPR.2009.5206848.

Yihe Dong, Jean-Baptiste Cordonnier, and Andreas Loukas. Attention is not all you need: pure attention loses rank doubly exponentially with depth. In Marina Meila and Tong Zhang, editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 2793–2803. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/dong21a.html`.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=YicbFdNTTy`.

Stéphane d'Ascoli, Hugo Touvron, Matthew L Leavitt, Ari S Morcos, Giulio Biroli, and Levent Sagun. Convit: improving vision transformers with soft convolutional inductive biases*. *Journal of Statistical Mechanics: Theory and Experiment*, 2022(11):114005, nov 2022. doi: 10.1088/1742-5468/ac9830. URL `https://doi.org/10.1088/1742-5468/ac9830`.

Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 2021. https://transformer-circuits.pub/2021/framework/index.html.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A. Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=Bygh9j09KX`.

Byeongho Heo, Song Park, Dongyoon Han, and Sangdoo Yun. Rotary position embedding for vision transformer. In *Computer Vision – ECCV 2024: 18th European Conference, Milan, Italy, September 29–October 4, 2024, Proceedings, Part X*, page 289–305, Berlin, Heidelberg, 2024. Springer-Verlag. ISBN 978-3-031-72683-5. doi: 10.1007/978-3-031-72684-2_17. URL `https://doi.org/10.1007/978-3-031-72684-2_17`.

Md Amirul Islam*, Sen Jia*, and Neil D. B. Bruce. How much position information do convolutional neural networks encode? In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rJeB36NKvB`.

Amirhossein Kazemnejad, Inkit Padhi, Karthikeyan Natesan, Payel Das, and Siva Reddy. The impact of positional encoding on length generalization in transformers. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=Drrl2gcjzl`.

Goro Kobayashi, Tatsuki Kuribayashi, Sho Yokoi, and Kentaro Inui. Incorporating Residual and Normalization Layers into Analysis of Masked Language Models. In Marie-Francine Moens, Xuanjing Huang, Lucia Specia, and Scott Wen-tau Yih, editors, *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 4547–4568. Association for Computational Linguistics, November 2021. doi: 10.18653/v1/2021.emnlp-main.373. URL `https://aclanthology.org/2021.emnlp-main.373/`.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin Transformer: Hierarchical Vision Transformer using Shifted Windows . In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 9992–10002. IEEE Computer Society, October 2021. doi: 10.1109/ICCV48922.2021.00986. URL https://doi.ieeecomputersociety.org/10.1109/ICCV48922.2021.00986.

Xiaofeng Mao, Gege Qi, Yuefeng Chen, Xiaodan Li, Ranjie Duan, Shaokai Ye, Yuan He, and Hui Xue. Towards robust vision transformer. *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 12032–12041, 2021. URL https://api.semanticscholar.org/CorpusID:235211752.

Sayak Paul and Pin-Yu Chen. Vision transformers are robust learners. *Proceedings of the AAAI Conference on Artificial Intelligence*, 36(2):2071–2081, Jun. 2022. doi: 10.1609/aaai.v36i2.20103. URL https://ojs.aaai.org/index.php/AAAI/article/view/20103.

Maithra Raghu, Thomas Unterthiner, Simon Kornblith, Chiyuan Zhang, and Alexey Dosovitskiy. Do vision transformers see like convolutional neural networks? In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL https://openreview.net/forum?id=R-616EWWKF5.

# A Experimental Setup and Hyperparameters

Table 2: Model architecture and training hyperparameters used in all experiments.

| **Parameter** | **Value** |
|---|---|
| *Input & Tokenization* | |
| Input resolution | $224 \times 224$ |
| Patch size | $16 \times 16$ |
| Number of patches | 196 |
| Input channels ($C$) | 3 |
| *ViT Architecture* | |
| Embedding dimension ($D$) | 384 |
| Number of encoder layers | 12 |
| Number of attention heads | 8 |
| Key/query dimension ($d_k$) | 48 |
| Dropout (embedding) | 0.15 |
| Dropout (attention) | 0.15 |
| Dropout (MLP) | 0.15 |
| Stochastic depth rate | 0.2 |
| *Training Hyperparameters* | |
| Batch size | 128 |
| Optimizer | Adam |
| Learning rate | $1 \times 10^{-3}$ |
| Weight decay | $5 \times 10^{-2}$ |
| Adam $\beta_1$ | 0.9 |
| Adam $\beta_2$ | 0.999 |
| Training epochs | 60 |

# B Additional Positional Encoding Scaling Results

## B.1 Full Learnable APE Scaling Results

These results exhibit a clear three-regime structure. For large values of $\alpha$, $\Delta$SSDC remains high and fragility is relatively low, indicating stable index-aligned spatial organization. As $\alpha$ decreases

| $\alpha$ | $\Delta$SSDC (RPI) | | Fragility Score | |
|---|---|---|---|---|
| | Mean | Std | Mean | Std |
| 1.0 | 0.4725 | 0.0228 | 0.4338 | 0.0127 |
| 0.9 | 0.3850 | 0.0301 | 0.4520 | 0.0135 |
| 0.8 | 0.3125 | 0.0259 | 0.4780 | 0.0146 |
| 0.7 | 0.1845 | 0.0342 | 0.5145 | 0.0145 |
| 0.6 | 0.0975 | 0.0109 | 0.5597 | 0.0169 |
| 0.5 | 0.0475 | 0.0083 | 0.5975 | 0.0202 |
| 0.4 | 0.0000 | 0.0000 | 0.6272 | 0.0189 |
| 0.3 | 0.0000 | 0.0000 | 0.6425 | 0.0171 |
| 0.2 | 0.0000 | 0.0000 | 0.6483 | 0.0210 |
| 0.1 | 0.0000 | 0.0000 | 0.6522 | 0.0245 |

Table 3: Effect of positional embedding magnitude $\alpha$ on index-based spatial organization and robustness. $\Delta$SSDC (measured under RPI) captures the recovery of index-based spatial structure after the first encoder block. As $\alpha$ decreases, $\Delta$SSDC collapses, indicating the breakdown of index-based spatial organization, while fragility increases sharply in the same regime before plateauing once spatial structure is lost.

past a critical range (around $\alpha \approx 0.5$–$0.6$), $\Delta$SSDC collapses sharply to zero, coinciding with a rapid increase in fragility. Below this threshold, fragility plateaus despite further reductions in $\alpha$, suggesting that once index-aligned spatial structure is lost, additional degradation of positional signal has limited further impact on robustness.

### B.2 Sinusoidal Positional Encoding Scaling Results

| $\alpha$ | $\Delta$SSDC (RPI) | Fragility Score |
|---|---|---|
| 1.0 | 0.29 | 0.4415 |
| 0.9 | 0.28 | 0.4526 |
| 0.8 | 0.25 | 0.4674 |
| 0.7 | 0.24 | 0.4868 |
| 0.6 | 0.25 | 0.5065 |
| 0.5 | 0.21 | 0.5204 |
| 0.4 | 0.17 | 0.5492 |
| 0.3 | 0.13 | 0.5756 |
| 0.2 | 0.07 | 0.6091 |
| 0.1 | 0.022 | 0.6357 |

Table 4: Effect of sinusoidal positional embedding magnitude $\alpha$ on index-based spatial organization and robustness (single-seed experiment). $\Delta$SSDC (measured under RPI) captures the recovery of index-based spatial structure after the first encoder block. We report no standard deviations because results are obtained from a single seed; this experiment is intended as a qualitative confirmation rather than a statistically rigorous estimate. Specifically, it verifies that the same qualitative relationship observed with absolute positional embeddings—namely, the collapse of $\Delta$SSDC and the increase in fragility as $\alpha$ decreases—also holds for sinusoidal positional encodings.

A similar overall relationship is observed for sinusoidal positional encodings, with decreasing $\alpha$ leading to reduced $\Delta$SSDC and increased fragility. However, in contrast to learnable APE, the transition is more gradual: $\Delta$SSDC degrades smoothly across the full range of $\alpha$ without a sharp collapse threshold, and fragility increases correspondingly in a continuous manner. This suggests that while the coupling between spatial structure and robustness persists across encoding types, the dynamics of how spatial organization degrades are encoding-dependent.