

1. Create a user account with the following attribute
 - ✓ username: islam `useradd -c "Islam Asker" -md /home/islam islam` *comment*
 - ✓ Fullname/comment: Islam Asker
 - ✓ Password: islam `passwd islam`
2. Create a user account with the following attribute
 - ✓ Username: baduser `useradd -c "Bad User" -md /home/baduser baduser ; passwd`
 - ✓ Full name/comment: Bad User `-c`
 - ✓ Password: baduser `groupadd -g 30000 pgroup` *Da...*
3. Create a supplementary (Secondary) group called pgroup with group ID of 30000
4. Create a supplementary group called badgroup `groupadd badgroup`
5. Add islam user to the pgroup group as a supplementary group `usermod -aG pgroup islam`
6. Modify the password of islam's account to password `passwd`
7. Modify islam's account so the password expires after 30 days `passwd -ex 30 islam`
8. Lock bad user account so he can't log in `sudo passwd -l islam` *Block*
9. Delete bad user account `rm -rf baduser` *rm -rf*
`userdel baduser` *com*
10. Delete the supplementary group called badgroup. `groupdel badgroup` *Inf. group*
11. Create a folder called myteam in your home directory and change its permissions to read only for the owner. `chmod go-r myteam` *myteam*
12. Log out and log in by another user `su - / exit`
13. Try to access (by cd command) the folder (myteam) *not have permission*
14. Using the command Line
 - ✓ Change the permissions of oldpasswd file to give owner read and write permissions and for group write and execute and execute only for the others (using chmod in 2 different ways) `"rw-r-x--x" → chmod`
 - ✓ Change your default permissions to be as above.
 - ✓ What is the maximum permission a file can have, by default when it is just created? And what is that for directory. *(3)*
 - ✓ Change your default permissions to be no permission to everyone then create a directory and a file to verify.



17. What are the minimum permission needed for:

- ✓ • Copy a directory (permission for source directory and permissions for target parent directory) high low
- Copy a file (permission for source file and permission for target parent directory)
- Delete a file ✓ # According to use case I put a permission to file or directory
- Change to a directory ✓
- List a directory content (ls command) → ls
- View a file content (more/cat command) less
- Modify a file content → Write through text editor.

18. Create a file with permission 444. Try to edit in it and to remove it? Note what happened.

chmod.

19. What is the difference between the "x" permission for a file and for a directory?

