

Elmich Pedestal Calculator



VersiJack® Pedestals

Total: 129 no.

Area: 105 m

Shortest height: 118 mm

Slope percentage: 3%


VersiJack® Breakdown

Model	Height Range	Quantity
VersiJack® F1	37 - 50 mm	5
VersiJack® F2	50 - 74 mm	8
VersiJack® F3	74 - 117 mm	7
VersiJack® F4	117 - 201 mm	9
VersiJack® F5	196 - 281 mm	112
VersiJack® F6	277 - 446 mm	16
VersiJack® F7	356 - 524 mm	230
VersiJack® F8	437 - 690 mm	500
VersiJack® F9	516 - 768 mm	1100
VersiJack® F10	596 - 934 mm	12
VersiJack® F11	675 - 1014 mm	14

VersiJack® Accessories



Wall Spacer with compressible buffer allows for expansion, contraction and paver movement.




Vertical Edge Clips secure pavers upright for free fall edge installations.



Variable Angle Spacer Tab with rotatable posts supports up to 6 pavers.



Bearer Holder keeps battens of 35 mm to 80 mm width secured centrally on the pedestals.




Concealed Paver Retainer increases wind uplift resistance for elevated roof pavers.



Exposed Paver Retainer increases wind uplift resistance for elevated roof pavers.



Bottom Slope Corrector allows pedestals to remain upright on inclines of up to 5%.



Pedestal Shim allows for minor height increments, as well as providing sound and vibration dampening.



ELMICH PTE LTD www.elmich.com

Singapore: (+65) 6356 2800

info@elmich.com

Singapore | Australia | Germany | Malaysia | Switzerland | USA

