

Lab Report: Week 3 Session A

Agile Scaffolding Practice

Mahmudul Hasan (Student ID: 4125999049)

May 20, 2026

Abstract

This report documents Week 3 Session A on **agile scaffolding**: a hydrology user story was turned into a technical specification, then OpenCode Desktop generated a complete Python package in `week3_session_a/` from one scaffold prompt. The project includes SCS-CN core logic, CSV loaders, visualization, a four-subcommand CLI, 18 unit tests, `requirements.txt`, and `README.md`. OpenCode fixed Python 3.8 type-hint compatibility and incorrect test expectations during generation. Local verification: 18 tests passed; `single 80 85` gave $Q = 43.55$ mm; batch and plot commands succeeded. Four OpenCode screenshots (`opencode1–opencode4`) document *one* long chat session (scroll steps). Full source, data, config, scaffold prompt, and `prompt_log.md` appear in Appendix ??–??.

1 Introduction

An empty repository plus a short user story invites the **cold-start** problem: missing tests, ad-hoc layout, or wrong hydrology. **Scaffolding** uses AI to supply directories, modules, and stubs that engineers refine with domain data and verification. Work was done in `ai_water_lab/week3_session_a/`, separate from the Week 2 flood-monitoring stack in `week2_session_a/`.

2 Objectives

- Convert a user story to a brief technical specification.
- Generate project scaffolding with AI from that spec.
- Customize and validate the AI-generated structure.
- Reflect on what scaffolding does and does not solve.

3 Methods

3.1 Story → specification

The user story was expanded into actor, inputs (P , CN or land-use table, optional watershed id), outputs (Q , tables/plots, assumptions), quality bar (edge-case tests, validation), and explicit SCS-CN formulas for cross-check with Week 1 Session B and Week 2 Session A ($P = 80$ mm, CN = 85).

3.2 Scaffold prompt (Exercise 1)

One prompt (`scaffold_prompt.txt`, Appendix ??) requested: directory structure, `scs_cn` module, data loaders, visualization, tests, `requirements.txt`, `README.md`, production error handling, and use of existing `data/cn_lookup.csv` and `data/sample_rainfall.csv`.

3.3 Customization (Exercise 2)

README was updated with author name and student ID; commands use `python3`; a virtual environment was created after installing `python3.8-venv`; `runoff_curves.png` was produced via the plot CLI.

3.4 Documentation (Exercise 3)

`prompt_log.md` records spec, prompt, matches, fixes, and cold-start reflection (Appendix ??).

4 Results

4.1 Project file inventory

Table ?? lists all submitted project files (full listings in the appendix).

Table 1: Generated and customized files in <code>week3_session_a/</code> .	
Path	Role
<code>src/scs_cn.py</code>	Scalar/vector SCS-CN, <code>summarize_runoff</code>
<code>src/data_loader.py</code>	CN lookup and rainfall CSV loaders
<code>src/visualization.py</code>	Runoff curves and bar charts
<code>src/cli.py</code>	CLI: <code>single</code> , <code>batch</code> , <code>table</code> , <code>plot</code>
<code>src/__init__.py</code>	Package marker (empty)
<code>tests/test_scs_cn.py</code>	18 pytest cases
<code>tests/__init__.py</code>	Test package marker (empty)
<code>data/cn_lookup.csv</code>	Land-use $\rightarrow$ CN table
<code>data/sample_rainfall.csv</code>	Five sample watershed events
<code>requirements.txt</code>	numpy, pandas, matplotlib, pytest
<code>README.md</code>	Setup, usage, assumptions
<code>scaffold_prompt.txt</code>	Prompt sent to OpenCode
<code>prompt_log.md</code>	AI interaction log
<code>runoff_curves.png</code>	Plot output (Exercise 2)

4.2 OpenCode session (one prompt, four screenshots)

Figures ??–?? are consecutive scroll captures of the **same** scaffold prompt session (not four separate prompts).

4.3 Terminal verification

Key numeric results:

- `python3 -m pytest tests/ -v` — 18 passed (≈ 0.33 s).
- `python3 -m src.cli single 80 85` — $Q = 43.55$ mm.
- `python3 -m src.cli batch` — runoff for five land-use events on watershed WS01.

5 Analysis and validation

Hydrology: $Q = 43.55$ mm for $P = 80$ mm, $CN = 85$ matches prior course checks (≈ 43.6 mm).

AI during scaffold: Incompatible `X | Y` type hints were fixed for Python 3.8; some test expected values were wrong until recalculated.

Cold-start: Scaffolding delivered layout, CLI, tests, and README quickly; the author still supplied CSV domain data, ran `pytest`, and verified a reference case in the terminal.




Figure 1: OpenCode step 1/4: scaffold prompt and start of generation.




Figure 2: OpenCode step 2/4: creating `src/`, `tests/`, and modules.

New session

Python 3.8 doesn't support the `X | Y` type annotation syntax. I'll fix the type hints for compatibility.

Edit `scs_cn.py /src/` +4 -0

Edit `scs_cn.py /src/` +2 -2

Edit `scs_cn.py /src/` +3 -3

Shell Re-run unit tests after fix

The expected values in my tests were wrong. Let me fix them with correct calculations.

Edit `test_scs_cn.py /tests/` +2 -1

Edit `test_scs_cn.py /tests/` +8 -5

❌ Shell The bash tool was called with invalid arguments

Shell Re-run tests after fixing expected values

All 18 tests pass. Let me verify the CLI commands too.

Shell Test CLI single command

Shell Test CLI batch command

Shell Test CLI table command

Shell Test CLI plot command (save to file)

Shell Show final directory tree

Figure 3: OpenCode step 3/4: Python 3.8 fixes and test corrections.




Figure 4: OpenCode step 4/4: project summary; 18 tests pass.




Figure 5: Terminal: pytest (18 passed), single 80 85, and batch.

6 Discussion

1. Four screenshots appropriately document one long OpenCode reply.
2. Customization was modest (README, python3, plot PNG, venv) because the scaffold matched the written spec.
3. Scaffolding is faster than manual cold start; hydrologic trust still requires local tests.
4. Stating Python version and spec bullets in the first prompt reduced rework.

7 Problems encountered

python was not on PATH (use python3). python3-venv was required before .venv could be created. No fake API keys appeared in this project.

8 Lessons learned

Story→spec before scaffolding; review every generated path; terminal verification is mandatory; keep prompt_log.md and screenshots as an audit trail.

9 Conclusion

Week 3 Session A objectives were met. Submitted artifacts: full week3_session_a/ tree (Appendix ??), prompt_log.md, four OpenCode screenshots (one session), and terminal screenshot.

A Submitted project files

A.1 Core module: src/scs_cn.py

src/scs_cn.py (full file)

```
SCS-CN_runoff_calculation_module.

Formulas
-----
S_ = 25400 / CN_ - 254 (potential_maximum_retention, mm)
Ia_ = 0.2 * S_ (initial_abstraction, mm)
Q_ = (P_ - Ia_)^2 / (P_ - Ia_ + S_) when P_ > Ia_, else 0

Assumptions
-----
- Ia_ = 0.2 * S_ (standard_SCS_assumption)
- CN_ is in [1, 100], rainfall_P_ >= 0
- Q_ is clipped to P_ (physical_upper_bound)

from __future__ import annotations

from typing import Sequence

import numpy as np
import pandas as pd

_VALID_CN_RANGE = (1, 100)
_MIN_RETENTION = 0.0
```

```

def _validate_scalar(value, name, lower=0.0, upper=None):
    if not isinstance(value, (int, float, np.floating, np.integer)):
        raise TypeError(f{name}_must_be_numeric, got {type(value).__name__})
    if np.isnan(value):
        raise ValueError(f{name}_must_not_be_NaN)
    if value < lower:
        raise ValueError(f{name}_{value}_must_be_>={lower})
    if upper is not None and value > upper:
        raise ValueError(f{name}_{value}_must_be_<={upper})
    return float(value)

def calculate_runoff(P: float, CN: float) -> float:
    Compute_SCS-CN_runoff_depth_Q(mm) from rainfall_P(mm) and curve_number_CN.

    Parameters
    -----
    P: float
    Rainfall depth (mm). Must be >= 0.
    CN: float
    Curve number in [1, 100].

    Returns
    -----
    float
    Runoff depth Q (mm). Guaranteed 0 <= Q <= P.

    Raises
    -----
    TypeError
    If either argument is non-numeric.
    ValueError
    If P < 0, CN < 1, CN > 100, or either value is NaN.

    Examples
    -----
    >>> calculate_runoff(50, 80)
    24.36
    >>> calculate_runoff(10, 80) # P < Ia
    0.0
    >>> calculate_runoff(0, 80)
    0.0

    P = _validate_scalar(P, P, lower=0.0)
    CN = _validate_scalar(CN, CN, lower=_VALID_CN_RANGE[0], upper=_VALID_CN_RANGE[1])

    S = 25400.0 / CN - 254.0
    Ia = 0.2 * S

    if P <= Ia:
        return 0.0

    numerator = (P - Ia) ** 2
    denominator = P - Ia + S
    Q = numerator / denominator
    return min(Q, P)

def calculate_runoff_series(
    P: Sequence[float],
    CN: Sequence[float],

```



```

) -> np.ndarray:
    Vectorised SCS-CN calculation over arrays of rainfall and CN values.

    Parameters
    -----
    P: array-like of float
    Rainfall depth(s) (mm).
    CN: array-like of float
    Curve number(s) in [1, 100].

    Returns
    -----
    np.ndarray
    Runoff depths Q (mm), same shape as inputs.

    Raises
    -----
    ValueError
    If P and CN have different lengths or any value is invalid.
    """
    P_arr = np.asarray(P, dtype=float)
    CN_arr = np.asarray(CN, dtype=float)

    if P_arr.shape != CN_arr.shape:
        raise ValueError(
            f"P shape {P_arr.shape} does not match CN shape {CN_arr.shape}"
        )

    if np.any(P_arr < 0):
        raise ValueError("All P values must be >= 0")
    if np.any((CN_arr < _VALID_CN_RANGE[0]) | (CN_arr > _VALID_CN_RANGE[1])):
        raise ValueError("All CN values must be in [{_VALID_CN_RANGE[0]}, {_VALID_CN_RANGE[1]}]")
    if np.any(np.isnan(P_arr)) or np.any(np.isnan(CN_arr)):
        raise ValueError("P and CN must not contain NaN values")

    S = 25400.0 / CN_arr - 254.0
    Ia = 0.2 * S

    # Avoid division-by-zero: denominator is always > 0 when P > Ia
    Q = np.where(
        P_arr > Ia,
        (P_arr - Ia) ** 2 / (P_arr - Ia + S),
        0.0,
    )
    return np.clip(Q, 0.0, P_arr)

def summarize_runoff(
    P: Sequence[float],
    CN: Sequence[float],
    labels: Sequence[str] | None = None,
) -> pd.DataFrame:
    Return a DataFrame with P, CN, S, Ia, Q for each input pair.

    Parameters
    -----
    P: array-like
    Rainfall depths (mm).
    CN: array-like
    Curve numbers.
    labels: list of str, optional

```

```

Optional_labels(e.g. land-use_names_or_eventIDs).

Returns
-----
pd.DataFrame
Columns: label(optional), P(mm), CN, S(mm), Ia(mm), Q(mm).
P_arr = np.asarray(P, dtype=float).ravel()
CN_arr = np.asarray(CN, dtype=float).ravel()

S = 25400.0 / CN_arr - 254.0
Ia = 0.2 * S

Q = calculate_runoff_series(P_arr, CN_arr)

df = pd.DataFrame({P(mm): P_arr, CN: CN_arr, S(mm): S, Ia(mm): Ia, Q(mm): Q})
if labels is not None:
    df.insert(0, label, labels)
return df

```

A.2 Data loaders: src/data_loader.py

src/data_loader.py (full file)

```

Data-loading utilities for CN lookup tables and rainfall event files.

from __future__ import annotations

import os
from typing import NamedTuple

import pandas as pd

class CNLookup(NamedTuple):
    land_use: str
    cn: int
    description: str

def load_cn_lookup(path: str) -> pd.DataFrame:
    Load the CN lookup CSV and validate its columns.

    Expected columns: `land_use`, `cn`, `description`.

Parameters
-----
path: str
    Path to the CSV file.

Returns
-----
pd.DataFrame
    Cleaned lookup table with CN cast to int and validated in [1,100].

Raises
-----
FileNotFoundError
    If *path* does not exist.
ValueError

```

```

#####If required columns are missing or any CN is out of range.
#####
    if not os.path.isfile(path):
        raise FileNotFoundError(fCN_lookup_file_not_found:{path})

    df = pd.read_csv(path)
    required = {land_use, cn, description}
    missing = required - set(df.columns)
    if missing:
        raise ValueError(fMissing_columns_in_{path}:{missing})

    df[cn] = df[cn].astype(int)
    invalid = df[(df[cn] < 1) | (df[cn] > 100)]
    if not invalid.empty:
        bad = invalid[[land_use, cn]].to_string(index=False)
        raise ValueError(fCN_values_out_of_range_{1,100}:{bad})

    return df

def load_rainfall_events(path: str) -> pd.DataFrame:
    Load_sample_rainfall_events_CSV_and_validate_columns.

#####Expected columns:``event_id``,``watershed_id``,``rainfall_mm``,``land_use``.

#####Parameters
#####-----
#####path:str
#####Path to the CSV file.

#####Returns
#####-----
#####pd.DataFrame
#####Event table with rainfall_mm validated >= 0.

#####Raises
#####-----
#####FileNotFoundError
#####If *path* does not exist.
#####ValueError
#####If required columns are missing or any rainfall value is negative.
#####
    if not os.path.isfile(path):
        raise FileNotFoundError(fRainfall_events_file_not_found:{path})

    df = pd.read_csv(path)
    required = {event_id, watershed_id, rainfall_mm, land_use}
    missing = required - set(df.columns)
    if missing:
        raise ValueError(fMissing_columns_in_{path}:{missing})

    if (df[rainfall_mm] < 0).any():
        raise ValueError(rainfall_mm must not contain negative values)

    return df

```

A.3 Visualization: src/visualization.py

src/visualization.py (full file)

```
Visualization_components_for_SCS-CN_runoff_analysis.

from __future__ import annotations

import matplotlib.pyplot as plt
import numpy as np
import pandas as pd

def plot_runoff_vs_rainfall(
    P_values: np.ndarray,
    CN_values: list[int] | np.ndarray,
    ax: plt.Axes | None = None,
    title: str = SCS-CN_Runoff_vs_Rainfall,
) -> plt.Figure:
    Plot_runoff_depth_Q_against_rainfall_P_for_one_or_more_CN_curves.

    """Parameters
    """-----
    """P_values: np.ndarray
    """1-D array of rainfall depths (mm) to evaluate.
    """CN_values: list of int or np.ndarray
    """Curve numbers to plot.
    """ax: plt.Axes, optional
    """Matplotlib axes to draw on. A new figure+axes is created if not provided.
    """title: str
    """Plot title.

    """Returns
    """-----
    """plt.Figure
    """The figure handle.
    """
    if ax is None:
        fig, ax = plt.subplots(figsize=(8, 5))
    else:
        fig = ax.figure

    P = np.asarray(P_values, dtype=float)

    for CN in CN_values:
        S = 25400.0 / CN - 254.0
        Ia = 0.2 * S
        Q = np.where(
            P > Ia,
            (P - Ia) ** 2 / (P - Ia + S),
            0.0,
        )
        ax.plot(P, Q, label=f'CN={CN}')

    ax.plot(P, P, k--, alpha=0.4, label=f'P (upper bound)')
    ax.set_xlabel(Rainfall_P(mm))
    ax.set_ylabel(Runoff_Q(mm))
    ax.set_title(title)
    ax.legend()
    ax.grid(True, alpha=0.3)
    fig.tight_layout()
    return fig
```

```

def plot_runoff_by_land_use(
    df: pd.DataFrame,
    ax: plt.Axes | None = None,
    title: str = Runoff_by_Land_Use,
) -> plt.Figure:
    Bar chart of runoff depth per land-use category.

    Parameters
    -----
    df: pd.DataFrame
        Must contain columns ``land_use`` (or ``label``) and ``Q(mm)``.
        Typically the output of :func:`src.scs_cn.summarize_runoff`.
    ax: plt.Axes, optional
    title: str

    Returns
    -----
    plt.Figure
    """
    if ax is None:
        fig, ax = plt.subplots(figsize=(8, 5))
    else:
        fig = ax.figure

    label_col = land_use if land_use in df.columns else label
    x = df[label_col].astype(str)
    y = df[Q(mm)]

    bars = ax.bar(x, y, color=steelblue, edgecolor=black)
    ax.bar_label(bars, fmt=%.1f, padding=2)
    ax.set_xlabel(Land_Use)
    ax.set_ylabel(Runoff_Q(mm))
    ax.set_title(title)
    ax.grid(axis=y, alpha=0.3)
    fig.tight_layout()
    return fig

```

A.4 CLI: src/cli.py

src/cli.py (full file)

```

Command-line interface for SCS-CN runoff analysis.

from __future__ import annotations

import argparse
import sys
from pathlib import Path

from src.data_loader import load_cn_lookup, load_rainfall_events
from src.scs_cn import calculate_runoff, calculate_runoff_series, summarize_runoff
from src.visualization import plot_runoff_by_land_use, plot_runoff_vs_rainfall

def _resolve_data_path(filename: str) -> str:
    return str(Path(__file__).resolve().parent.parent / data / filename)

```

```

def build_parser() -> argparse.ArgumentParser:
    parser = argparse.ArgumentParser(
        description=SCS-CN_runoff_calculator_for_flood_risk_screening.,
    )
    sub = parser.add_subparsers(dest=command, required=True)

    # single
    single = sub.add_parser(single, help=Single_(P,CN)_pair)
    single.add_argument(P, type=float, help=Rainfall_depth_(mm))
    single.add_argument(CN, type=float, help=Curve_number_[1,100])

    # batch
    batch = sub.add_parser(batch, help=Run_all_events_from_sample_rainfall.csv)
    batch.add_argument(
        --cn-lookup,
        default=_resolve_data_path(cn_lookup.csv),
        help=Path_to_CN_lookup_CSV,
    )
    batch.add_argument(
        --rainfall,
        default=_resolve_data_path(sample_rainfall.csv),
        help=Path_to_rainfall_events_CSV,
    )

    # table
    table = sub.add_parser(table, help=Print_summary_table_for_a_range)
    table.add_argument(P, type=float, help=Rainfall_depth_(mm))
    table.add_argument(
        CN_values,
        type=int,
        nargs=+,
        help=One_or_more_CN_values,
    )
    table.add_argument(--labels, nargs=*, help=Optional_per-CN_labels)

    # plot
    plt_cmd = sub.add_parser(plot, help=Plot_runoff_curves)
    plt_cmd.add_argument(
        --max-P,
        type=float,
        default=150.0,
        help=Maximum_rainfall_for_plot_(mm),
    )
    plt_cmd.add_argument(
        --CN,
        type=int,
        nargs=+,
        default=[70, 80, 90, 98],
        help=CN_curves_to_plot,
    )
    plt_cmd.add_argument(
        --output,
        -o,
        default=None,
        help=Save_plot_to_file_instead_of_showing,
    )

    return parser

def main(argv: list[str] | None = None) -> int:
    parser = build_parser()

```

```

args = parser.parse_args(argv)

if args.command == single:
    Q = calculate_runoff(args.P, args.CN)
    print(fP={args.P:.1f}_mm, CN={args.CN:.0f} -> Q={Q:.2f}_mm)
    return 0

if args.command == batch:
    cn_df = load_cn_lookup(args.cn_lookup)
    rain_df = load_rainfall_events(args.rainfall)

    merged = rain_df.merge(cn_df, on=land_use, how=left)
    if merged[cn].isna().any():
        missing = merged.loc[merged[cn].isna(), land_use].unique()
        print(fWARNING: No CN for land use(s): {list(missing)}, file=sys.stderr)

    merged[Q(mm)] = calculate_runoff_series(
        merged[rainfall_mm].values,
        merged[cn].values,
    )
    print(merged.to_string(index=False))
    return 0

if args.command == table:
    labels = args.labels if args.labels else None
    P_arr = [args.P] * len(args.CN_values)
    df = summarize_runoff(P_arr, args.CN_values, labels=labels)
    print(df.to_string(index=False))
    return 0

if args.command == plot:
    import numpy as np

    P = np.linspace(0, args.max_P, 200)
    fig = plot_runoff_vs_rainfall(P, args.CN)
    if args.output:
        fig.savefig(args.output, dpi=150)
        print(fPlot saved to {args.output})
    else:
        plt.show()
    return 0

parser.print_help()
return 1

if __name__ == '__main__':
    sys.exit(main())

```

A.5 Tests: tests/test_scs_cn.py

tests/test_scs_cn.py (full file)

```

Unit tests for SCS-CN runoff calculation.

import math

import numpy as np
import pytest

```

```

from src.scs_cn import calculate_runoff, calculate_runoff_series, summarize_runoff

class TestCalculateRunoff:
    Tests_for_the_scalar_calculate_runoff_function.

    def test_zero_rainfall(self):
        assert calculate_runoff(0, 80) == 0.0

    def test_rainfall_less_than_ia(self):
        Q = calculate_runoff(10, 80)
        #  $I_a = 0.2 * (25400/80 - 254) = 0.2 * (317.5 - 254) = 0.2 * 63.5 = 12.7$ 
        #  $P = 10 < 12.7 \Rightarrow Q = 0$ 
        assert Q == 0.0

    def test_normal_case(self):
        Q = calculate_runoff(50, 80)
        #  $S = 25400/80 - 254 = 63.5$ 
        #  $I_a = 12.7$ 
        #  $Q = (50 - 12.7)^2 / (50 - 12.7 + 63.5) = 37.3^2 / (37.3 + 63.5) = 1391.29 / 100.8$ 
        expected = (50 - 12.7) ** 2 / (50 - 12.7 + 63.5)
        assert Q == pytest.approx(expected, rel=1e-9)

    def test_invalid_cn_too_low(self):
        with pytest.raises(ValueError, match=must_be_1):
            calculate_runoff(50, 0)

    def test_invalid_cn_too_high(self):
        with pytest.raises(ValueError, match=must_be_100):
            calculate_runoff(50, 101)

    def test_invalid_cn_nan(self):
        with pytest.raises(ValueError, match=must_not_be_NaN):
            calculate_runoff(50, math.nan)

    def test_invalid_p_negative(self):
        with pytest.raises(ValueError, match=must_be_0):
            calculate_runoff(-1, 80)

    def test_runoff_never_exceeds_rainfall(self):
        for P in [5, 10, 25, 50, 100, 200]:
            for CN in [30, 50, 70, 90, 99]:
                Q = calculate_runoff(P, CN)
                assert 0 <= Q <= P, f'P={P}, CN={CN}: Q={Q} not in [0, {P}]'

    def test_cn_close_to_100(self):
        Q = calculate_runoff(50, 100)
        #  $S = 25400/100 - 254 = 0$ 
        #  $I_a = 0$ 
        #  $Q = P = 50$ 
        assert Q == pytest.approx(50.0)

    def test_cn_1_edge(self):
        #  $CN = 1 \Rightarrow S = 25400/1 - 254 = 25146$ 
        #  $I_a = 5029.2 \rightarrow$  huge, so  $Q = 0$  for any reasonable  $P$ 
        Q = calculate_runoff(50, 1)
        assert Q == 0.0

class TestCalculateRunoffSeries:
    Tests_for_the_vectorised_calculate_runoff_series.

```



```

def test_all_zero(self):
    Q = calculate_runoff_series([0, 0], [80, 90])
    assert (Q == 0).all()

def test_mixed(self):
    P = np.array([10, 50, 100])
    CN = np.array([80, 80, 80])
    Q = calculate_runoff_series(P, CN)
    # confirm monotonic and Q <= P
    assert (Q >= 0).all()
    assert (Q <= P).all()
    assert Q[0] == 0.0 # P < Ia

def test_shape_mismatch(self):
    with pytest.raises(ValueError, match=shape):
        calculate_runoff_series([1, 2, 3], [1, 2])

def test_nan_handling(self):
    with pytest.raises(ValueError, match=NaN):
        calculate_runoff_series([1, 2], [1, math.nan])

def test_q_le_p_vectorised(self):
    rng = np.random.default_rng(42)
    P = rng.uniform(1, 200, 50)
    CN = rng.integers(30, 99, 50)
    Q = calculate_runoff_series(P, CN)
    assert np.all(Q >= 0)
    assert np.all(Q <= P)

class TestSummarizeRunoff:
    Tests for the summary DataFrame builder.

    def test_basic(self):
        df = summarize_runoff([50], [80])
        assert list(df.columns) == [P_(mm), CN, S_(mm), Ia_(mm), Q_(mm)]
        expected = (50 - 12.7) ** 2 / (50 - 12.7 + 63.5)
        assert df[Q_(mm)].iloc[0] == pytest.approx(expected)

    def test_with_labels(self):
        df = summarize_runoff([50, 50], [70, 98], labels=[forest, paved])
        assert list(df.columns) == [label, P_(mm), CN, S_(mm), Ia_(mm), Q_(mm)]
        assert df[label].tolist() == [forest, paved]

class TestIntegration:
    Integration-level checks.

    def test_manual_cn_lookup_values(self):
        # Known calculation check
        # P=50, CN=80: S=63.5, Ia=12.7, Q=(37.3^2)/(37.3+63.5) 13.80
        Q = calculate_runoff(50, 80)
        expected = (50 - 12.7) ** 2 / (50 - 12.7 + 63.5)
        assert Q == pytest.approx(expected, abs=0.01)
        # P=50, CN=70: S=25400/70-254=108.857, Ia=21.771, Q=(28.229^2)/(28.229+108.857)
        Q = calculate_runoff(50, 70)
        S70 = 25400 / 70 - 254
        expected70 = (50 - 0.2 * S70) ** 2 / (50 - 0.2 * S70 + S70)
        assert Q == pytest.approx(expected70, abs=0.01)

```

A.6 Configuration and documentation

requirements.txt (full file)

```
numpy>=1.23
pandas>=1.5
matplotlib>=3.6
pytest>=7.0
```

README.md (full file)

```
# SCS-CN Runoff Calculator

**Author:** Mahmudul Hasan
**Student ID:** 4125999049
**Course:** Software Development | Week 3 Session A (Agile Scaffolding)

Calculate runoff depth (Q) from rainfall (P) and curve number (CN) using the
USDA SCS Curve Number method, for flood-risk screening of a watershed.

## Setup

```bash
Optional: on Ubuntu, if venv creation fails:
sudo apt install python3.8-venv

python3 -m venv .venv
source .venv/bin/activate

pip install -r requirements.txt
```

## Usage

### Single calculation
```bash
python3 -m src.cli single 50 80
Output: P = 50.0 mm, CN = 80 -> Q = 24.36 mm
```

### Batch processing
```bash
python3 -m src.cli batch
```

### Table
```bash
python3 -m src.cli table 50 70 80 90 --labels forest pasture residential
```

### Plot
```bash
python3 -m src.cli plot --max-P 150 --CN 70 80 90 98
python3 -m src.cli plot --max-P 150 --CN 70 80 90 98 --output runoff_curves.png
```

## Tests

```bash
python3 -m pytest tests/ -v
```

## Data
```

```
- `data/cn_lookup.csv` | Land-use → CN mapping
- `data/sample_rainfall.csv` | Sample rainfall events by watershed

## Assumptions

- Initial abstraction  $I_a = 0.2 \times S$  (standard SCS assumption)
- Curve number CN [1, 100]
- Runoff Q is clipped to rainfall P (physical upper bound)
```

A.7 Scaffold prompt: scaffold_prompt.txt

scaffold_prompt.txt (full file)

As a hydrologist, I want to calculate SCS-CN runoff for different land use types so that I
 ↪ can estimate flood risk for my watershed.

Please generate a complete Python project structure in THIS folder (week3_session_a)

↪ including:

1. Directory structure
2. Main module with SCS-CN calculation function
3. Data loading utilities
4. Visualization components
5. Test file structure
6. requirements.txt
7. README.md with setup instructions

Make it production-ready with proper error handling and documentation.

Technical spec to follow:

- Inputs: rainfall depth P (mm), curve number CN per land use (optional watershed id)
- Outputs: runoff depth Q (mm), tables or plots, documented assumptions
- SCS-CN: $S = 25400 / CN - 254$, $I_a = 0.2 \times S$, $Q = 0$ if $P < I_a$, else $Q = (P - I_a)^2 / (P - I_a + S)$,
 ↪ enforce $Q \leq P$
- Tests: $P=0$, $P < I_a$, normal case (e.g. $P=50$ $CN=80$), invalid CN, $Q \leq P$
- Use numpy/pandas/matplotlib as needed; no fake API keys

A.8 Data files

data/cn_lookup.csv (full file)

```
land_use,cn,description
forest,70,Woods good condition
pasture,80,Pasture fair condition
cultivated,85,Cultivated straight row
residential,90,Urban residential
paved,98,Paved areas
```

data/sample_rainfall.csv (full file)

```
event_id,watershed_id,rainfall_mm,land_use
1,WS01,50,forest
2,WS01,50,pasture
3,WS01,50,cultivated
4,WS01,80,residential
5,WS01,30,paved
```

B Submitted prompt log: prompt_log.md

prompt_log.md (full file)

```
# Prompt Log - Week 3 Session A

## Story → spec (brief)

**User story:** As a hydrologist, I want to calculate SCS-CN runoff for different land
↪ use types so that I can estimate flood risk for my watershed.

**Technical spec (before prompting):**

- **Actor / goal:** Hydrologist; runoff by land use for flood-risk screening.
- **Inputs:** Rainfall depth P (mm); curve number CN per land use (or land-use CN lookup
↪ table); optional watershed id.
- **Outputs:** Runoff depth Q (mm); summary tables and/or plots; assumptions documented
↪ ( $I_a = 0.2S$ ,  $Q = 0$  if  $P < I_a$ ,  $Q \leq P$ ).
- **Quality bar:** Unit tests for edge cases ( $P=0$ ,  $P < I_a$ , CN bounds,  $Q \leq P$ ); clear errors
↪ for invalid CN or negative rainfall.
- **Formulas:**  $S = 25400/CN - 254$ ;  $I_a = 0.2 \cdot S$ ;  $Q = (P - I_a)^2 / (P - I_a + S)$  when  $P > I_a$ .

---

## Scaffolding generation

**Prompt used:** See `scaffold_prompt.txt` (user story + 7 deliverables + technical spec
↪ bullets; read existing `data/cn_lookup.csv` and `data/sample_rainfall.csv`).

**Where saved:** `ai_water_lab/week3_session_a/`

**What matched my spec:**

- Directory layout: `src/`, `tests/`, `data/`
- `calculate_runoff(P, CN)` with  $I_a$ ,  $Q=0$  when  $P < I_a$ ,  $Q$  clipped to  $P$ 
- `data_loader.py` for CSV with validation
- `visualization.py` and CLI (`single`, `batch`, `table`, `plot`)
- 18 pytest cases (edge cases, vectorised, integration)
- `requirements.txt`, `README.md`; no fake API keys

**What was wrong or generic at first:**

- Type hints used `X | Y` syntax (invalid on Python 3.8); OpenCode fixed to
↪ Union/Optional.
- Some test expected values were wrong until recalculated against the formula.
- OpenCode summary mentioned six land uses; `cn_lookup.csv` has five rows (minor wording
↪ slip).

**Changes made in Exercise 2 (customize):**

- README: author Mahmudul Hasan, student ID 4125999049, `python3` commands, venv note.
- Kept domain files `data/cn_lookup.csv`, `data/sample_rainfall.csv`.
- Generated `runoff_curves.png` via CLI plot command.
- Created `.venv`, installed requirements, re-ran batch and pytest locally.

---

## Cold-start reflection

**What would have been harder without scaffolding:** Empty-repo start would require
↪ choosing package layout, writing test stubs, CLI entry points, README, and
↪ requirements from scratch before focusing on hydrology.
```

```
**What I still had to decide myself:** CN values per land use in CSV, sample watershed  
↳ events, trusting terminal over AI test numbers until pytest passed, using `python3`  
↳ vs `python` on Linux, and verifying P=80 mm / CN=85 Q 43.55 mm (consistent with  
↳ Week 1 Session B and Week 2 debug lab).
```

Lessons learned

Story spec before the scaffold prompt improved alignment. Four OpenCode screenshots
↳ document one long session (not four separate prompts). Always run `pytest` and a
↳ known SCS-CN case locally after AI generation.