5 Decision Trees & Random Forest : Predict loan approval using a banking dataset

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier, plot_tree
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import classification_report, confusion_matrix
, accuracy_score
from sklearn.preprocessing import LabelEncoder
import matplotlib.pyplot as plt
import seaborn as sns

#1 Load the dataset
#Example : Assuming 'loan_data.csv' where 'Loan_Status' is
 the target (Y= Approved, N= Not Approved)
df = pd.read_csv ('loan_data.csv')

# Preview the dataset
print ("Dataset Preview :")
print (df.head())

#2. Handle missing values (simple fill or drop)
df = df.dropna() # or you can use df.fillna (method='ffill')
                  depending on your data

#3. Encode categorical variables
#identify categorical columns
cat_cols = df.select_dtypes (include ='object').columns
```

```
#label Encoding
le = LabelEncoder()
for col in cat_cols:
    df[col] = le.fit_transform(df[col])

#4. Prepare features and labels
X = df.drop('Loan_status', axis=1) #Features
y = df['Loan_Status'] # Target (1 = Approved, 0 = Not Approved
                                after encoding)

#5 Split the data
X_train, X_test, y_train, y_test = train_test_split(X, y,
test_size = 0.3, random_state = 42)

#6 Decision Tree Model
dtree = DecisionTreeClassifier(random_state = 42)
dtree.fit(X_train, y_train)

#7 Random Forest Model
rforest = RandomForestClassifier(n_estimators = 100, random_state =
42)
rforest.fit(X_train, y_train)

#8. Predictions
dtree_preds = dtree.predict(X_test)
rforest_preds = rforest.predict(X_test)
```

#9 Evaluation

```
print("\n-- Decision Tree Performance ---")
print("Confusion Matrix :\n", confusion_matrix(y_test, dtree_preds))
print("classification Report :\n", classification_report(y_test, dtree_preds))
print("Accuracy Score :", accuracy_score(y_test, dtree_preds))
print("\n -- Random Forest Performance ---")
print("Confusion Matrix :\n", confusion_matrix(y_test, rforest_preds))
print("classification Report :\n", classification_report(y_test, rforest_preds))
print("Accuracy Score", accuracy_score(y_test, rforest_preds))
```

#10 Visulization of Decision Tree

```
plt.figure(figsize=(20,10))
plot_tree(dtree, feature_names=X.columns, class_names=['Not Approved', 'Approved'], filled=True)
plt.title('Decision Tree visualization')
plt.show()
```

#11. Feature Importance (Random Forest)

```
importances = rforest.feature_importances_
features = X.columns
feature_importance_df = pd.DataFrame({'Feature': features, 'Importance': importances})
```

```
feature_importance_df
  feature_importance_df.sort_values(by='Importance', ascending=
False)

plt.figure(figsize=(12,6))
sns.barplot(x='Importance', data=feature_importance_df)
plt.title('Feature Importance from Random Forest')
plt.show()
```



Dataset Preview:

	Loan_ID	Gender	Married	Dependents	Education	Self_Employed
0	LP001002	Male	No	0	Graduate	No
1	LP001003	Male	Yes	1	Graduate	No
2	LP001005	Male	Yes	0	Graduate	Yes
3	LP001006	Male	Yes	0	Not Graduate	No
4	LP001008	Male	No	0	Graduate	No

	ApplicantIncome	CoapplicantIncome	LoanAmount	Loan_Amount_Term
0	5849	0.0	NaN	360.0
1	4583	1508.0	128.0	360.0
2	3000	0.0	66.0	360.0
3	2583	2358.0	120.0	360.0
4	6000	0.0	141.0	360.0

	Credit_History	Property_Area	Loan_Status
0	1.0	Urban	Y
1	1.0	Rural	N
2	1.0	Urban	Y
3	1.0	Urban	Y
4	1.0	Urban	Y

--- Decision Tree Performance --- Confusion Matrix:
[[21 23]
[15 85]]
Classification Report:

	precision	recall	f1-score	support
0	0.58	0.48	0.53	44
1	0.79	0.85	0.82	100
accuracy			0.74	144
macro avg	0.69	0.66	0.67	144
weighted avg	0.72	0.74	0.73	144

Accuracy Score: 0.7361111111111112

--- Random Forest Performance --- Confusion Matrix:
[[19 25]
[3 97]]
Classification Report:

	precision	recall	f1-score	support
0	0.86	0.43	0.58	44
1	0.80	0.97	0.87	100
accuracy			0.81	144
macro avg	0.83	0.70	0.72	144
weighted avg	0.82	0.81	0.78	144

Accuracy Score: 0.8055555555555556