

GGPv 6570

ProfiLine



Total gross capacity	601 litre
Ext. dimensions in mm (w/d/h)	700/830/2150
Int. dimensions in mm (w/d/h)	510/650/1550
Energy consumption in 24 h	4,513 kWh
Climate rating ¹	T 5
Cooling system	forced-air
Defrosting	automatic
Temperature range	-10°C to -35°C
Gastronorm	530 x 650 mm
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	304-grade stainless steel
Type of control	electronic controller
Temperature display	external digital
Interior light	–
Fault: warning signal	visual and audible
Interface	–
volt-free alarm contact	yes
Shelves	5
Adjustable Shelving	–
Number of drawers	–
Number of baskets	–
Maximum number of baskets	–
Shelf material	grid shelves plastic-coated
Shelf loading	60 kg
Height of adjustable legs	120-170
Castors/type of castors	–
Door handle	full-length integrated door handle
Foot pedal opener	–
Self-closing door	yes
Insulation	83 - 60 mm
Defrost water drain	–
Refrigerant	R 290
Noise level	60 dB(A)
Gross/net weight	146/130 kg
EAN-Nr.	9005382170113

¹ Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

Subject to modification. Timestamp: 23.03.2015

LIEBHERR