



API Specification for Basic Data

Document Version: 1.0

Release Date: August 29, 2025

Contents

1 Structure of Response.....	4
1.1 Status Codes.....	4
1.2 Statuses.....	4
1.3 Successful Messages.....	4
1.4 Format of Response.....	4
2 Education Level.....	5
2.1 Add.....	5
2.2 Update.....	5
2.3 Delete.....	6
2.4 Active.....	7
2.5 Inactive.....	7
2.6 Fetch Specific Record.....	8
2.7 Get All Records.....	8
2.8 Get Combo List.....	9
3 Priority.....	10
3.1 Add.....	10
3.2 Update.....	11
3.3 Delete.....	11
3.4 Active.....	12
3.5 Inactive.....	12
3.6 Fetch Specific Record.....	13
3.7 Get All Records.....	14
3.8 Get Combo List.....	14
4 Issue Type.....	15
4.1 Add.....	15
4.2 Update.....	16
4.3 Delete.....	17
4.4 Active.....	17
4.5 Inactive.....	18
4.6 Fetch Specific Record.....	18
4.7 Get All Records.....	19
4.8 Get Combo List.....	20
5 Status.....	21
5.1 Add.....	21
5.2 Update.....	21
5.3 Delete.....	22
5.4 Active.....	23
5.5 Inactive.....	23
5.6 Fetch Specific Record.....	24
5.7 Get All Records.....	25
5.8 Get Combo List.....	25

6 Resolvation.....26

6.1 Add..... 26

6.2 Update.....27

6.3 Delete.....28

6.4 Active.....28

6.5 Inactive..... 29

6.6 Fetch Specific Record..... 29

6.7 Get All Records..... 30

6.8 Get Combo List..... 31

1 Structure of Response

1.1 Status Codes

All APIs in Horizon System follow the [List of HTTP status Code](#).

1.2 Statuses

No	Status	Description
1	success	When the API returns successful result.
2	error	When the API returns fault result.

1.3 Successful Messages

No	Messages	Reason
1	The record is added successfully.	New Item Insertion.
2	The record is updated successfully.	Updating Specific Item
3	The record is deleted successfully.	Deleting Specific Item
4	The record is activated successfully.	Activating Specific Inactive Item
5	The record is inactivated successfully.	Inactivating Specific active Item

1.4 Format of Response

No	Property Name	Data Type	Description
1	statusCode	integer	
2	status	string	It presented in section 1.1.
3	message	string	Successful (section 1.2) and error message.
4	errorCode	integer	Error code based on “System Error List” document.
5	data	object	To return data objects and properties.

2 Education Level

2.1 Add

Description

This API adds a record of “education level” into the basic data.

Request CURL Sample

```
curl --request POST \  
  --url 'https://[maindomian]/api/basic/educationLevel' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json' \  
  --data '{  
    "Code" : "[code]",  
    "Title" : "[title]",  
    "Decription" : "[description (optional)]"  
  }'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is added successfully."  
  "errorCode": 0,  
  "data": {  
    "id": 123  
  }  
}
```

2.2 Update

Description

This API updates a specific record of “education level” in the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/educationLevel/[id]' \  

```

```
--header 'Authorization: Bearer [token]' \  
--header 'content-type: application/json' \  
--data '{  
  "Code" : "[code]",  
  "Title" : "[title]",  
  "Decription" : "[description (optional)]"  
}'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is updated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

2.3 Delete

Description

This API ***logically*** deletes a record of “education level” from the basic data.

Request CURL Sample

```
curl --request DELETE \  
  --url 'https://[maindomian]/api/basic/educationLevel/[id]' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is deleted successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

2.4 Active

Description

This API activates a specific record of “education level” in the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/educationLevel/active/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is activated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

2.5 Inactive

Description

This API in-activates a specific record of “education level” in the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/educationLevel/active/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is inactivated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

```
}
```

2.6 Fetch Specific Record

Description

This API returns a specific record of “education level” from the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/educationLevel/active/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : {  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123",  
    "description" : "test",  
    "createdAt" : "2025-8-25 12:00:00",  
    "createdBy" : "John Davis"  
  }  
}
```

2.7 Get All Records

Description

This API returns all active records of “education level” from the basic data.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomian]/api/basic/educationLevel/getAll?'
```



```
title=test&code=123&description=test&offset=0&limit=15&sort_by=desc(fieldname)' \
--header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
  "data" : [{
    "id" : 16621244611384550112,
    "title" : "test",
    "code" : "123",
    "description" : "test",
    "createdAt" : "2025-8-25 12:00:00",
    "createdBy" : "John Davis"
  }]
}
```

2.8 Get Combo List

Description

This API returns all active records of “education level” from the basic data to use in combo or list form components.

Request CURL Sample

```
curl --request GET \
--url 'https://[maindomain]/api/basic/educationLevel/getComboList' \
--header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
```

```
{
  "data" : [{
    "id" : 16621244611384550112,
    "title" : "test",
    "code" : "123"
  }]
}
```

3 Priority

3.1 Add

Description

This API adds a record of “priority” into the basic data.

Request CURL Sample

```
curl --request POST \
  --url 'https://[maindomain]/api/basic/priority' \
  --header 'Authorization: Bearer [token]' \
  --header 'content-type: application/json' \
  --data '{
    "code" : "[code]",
    "title" : "[title]",
    "color" : "[Color Hex Code]",
    "ordering" : 0,
    "decription" : "[description (optional)]"
  }'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is added successfully.",
  "errorCode": 0,
  "data": {
    "id": 123
  }
}
```

3.2 Update

Description

This API updates a specific record of “priority” in the basic data.

Request CURL Sample

```
curl --request POST \  
  --url 'https://[maindomian]/api/basic/priority' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json' \  
  --data '{  
    "code" : "[code]",  
    "title" : "[title]",  
    "color" : "[Color Hex Code]",  
    "ordering" : 0,  
    "decription" : "[description (optional)]"  
  }'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is updated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

3.3 Delete

Description

This API ***logically*** deletes a record of “priority” from the basic data.

Request CURL Sample

```
curl --request DELETE \  
  --url 'https://[maindomian]/api/basic/priority/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is deleted successfully."
  "errorCode" : 0,
  "data" : null
}
```

3.4 Active

Description

This API activates a specific record of “priority” in the basic data.

Request CURL Sample

```
curl --request PUT \
  --url 'https://[maindomain]/api/basic/priority/active/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is activated successfully."
  "errorCode" : 0,
  "data" : null
}
```

3.5 Inactive

Description

This API in-activates a specific record of “priority” in the basic data.

Request CURL Sample

```
curl --request PUT \
```

```
--url 'https://[maindomian]/api/basic/priority/active/[id]' \  
--header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is inactivated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

3.6 Fetch Specific Record

Description

This API returns a specific record of “priority” from the basic data.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomian]/api/basic/priority/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : {  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123",  
    "color" : "FFFFFF",  
    "ordering" : 1,  
    "description" : "test",  
    "createdAt" : "2025-8-25 12:00:00",  
    "createdBy" : "John Davis"  
  }  
}
```

```
}  
}
```

3.7 Get All Records

Description

This API returns all active records of “priority” from the basic data.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomain]/api/basic/priority/getAll?  
title=test&code=123&description=test&color=FFFFFF&ordering=1&offset=0&  
limit=15&sort_by=desc(fieldName)' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : [{  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123",  
    "color" : "FFFFFF",  
    "ordering" : 1,  
    "description" : "test",  
    "createdAt" : "2025-8-25 12:00:00",  
    "createdBy" : "John Davis"  
  }]  
}
```

3.8 Get Combo List

Description

This API returns all active records of “priority” from the basic data to use in combo or list form components.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomian]/api/basic/priority/getComboList' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : [{  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123"  
  }]  
}
```

4 Issue Type

4.1 Add

Description

This API adds a record of “issue type” into the basic data.

Request CURL Sample

```
curl --request POST \  
  --url 'https://[maindomian]/api/basic/issueType' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json' \  
  --data '{  
    "code" : "[code]",  
    "title" : "[title]",  
    "color" : "[Color Hex Code]",  
  }'
```

```
"iconAddress" : "[Icon URL]",
"decription" : "[description (optional)]"
}'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is added successfully."
  "errorCode": 0,
  "data": {
    "id": 123
  }
}
```

4.2 Update

Description

This API updates a specific record of “issue type” in the basic data.

Request CURL Sample

```
curl --request PUT \
  --url 'https://[maindomian]/api/basic/issueType/[id]' \
  --header 'Authorization: Bearer [token]' \
  --header 'content-type: application/json' \
  --data '{
    "code" : "[code]",
    "title" : "[title]",
    "color" : "[Color Hex Code]",
    "iconAddress" : "[Icon URL]",
    "decription" : "[description (optional)]"
  }'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
```



```
{
  "message" : "The record is updated successfully."
  "errorCode" : 0,
  "data" : null
}
```

4.3 Delete

Description

This API ***logically*** deletes a record of “issue type” from the basic data.

Request CURL Sample

```
curl --request DELETE \
  --url 'https://[maindomian]/api/basic/issueType/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is deleted successfully."
  "errorCode" : 0,
  "data" : null
}
```

4.4 Active

Description

This API activates a specific record of “issue type” in the basic data.

Request CURL Sample

```
curl --request DELETE \
  --url 'https://[maindomian]/api/basic/issueType/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is activated successfully."
  "errorCode" : 0,
  "data" : null
}
```

4.5 Inactive

Description

This API in-activates a specific record of “issue type” in the basic data.

Request CURL Sample

```
curl --request PUT \
  --url 'https://[maindomian]/api/basic/issueType/inactive/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is inactivated successfully."
  "errorCode" : 0,
  "data" : null
}
```

4.6 Fetch Specific Record

Description

This API returns a specific record of “issue type” from the basic data.

Request CURL Sample

```
curl --request GET \
  --url 'https://[maindomian]/api/basic/issueType/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
  "data" : {
    "id" : 16621244611384550112,
    "title" : "test",
    "code" : "123",
    "color" : "FFFFFF",
    "description" : "test",
    "createdAt" : "2025-8-25 12:00:00",
    "createdBy" : "John Davis"
  }
}
```

4.7 Get All Records

Description

This API returns all active records of “issue type” from the basic data.

Request CURL Sample

```
curl --request GET \
  --url 'https://[maindomain]/api/basic/issueType/getAll?
title=test&code=123&color=FFFFFF&description=test&offset=0&limit=15&so
rt_by=desc(fieldName)' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
  "data" : [{
```

```
        "id" : 16621244611384550112,  
        "title" : "test",  
        "code" : "123",  
        "color" : "FFFFFF",  
        "description" : "test",  
        "createdAt" : "2025-8-25 12:00:00",  
        "createdBy" : "John Davis"  
    }]  
}
```

4.8 Get Combo List

Description

This API returns all active records of “issue type” from the basic data to use in combo or list form components.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomian]/api/basic/issueType/getComboList' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : [{  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123"  
  }]  
}
```

5 Status

5.1 Add

Description

This API adds a record of “status” into the basic data.

Request CURL Sample

```
curl --request POST \  
  --url 'https://[maindomian]/api/basic/status' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json' \  
  --data '{  
    "code" : "[code]",  
    "title" : "[title]",  
    "color" : "[Color Hex Code]",  
    "statusEffect" : "[ENUM (To Do, In Progress, Done)]",  
    "decription" : "[description (optional)]"  
  }'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is added successfully."  
  "errorCode": 0,  
  "data": {  
    "id": 123  
  }  
}
```

5.2 Update

Description

This API updates a specific record of “status” in the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/status/[id]' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json' \  
  --data '{  
    "code" : "[code]",  
    "title" : "[title]",  
    "color" : "[Color Hex Code]",  
    "statusEffect" : "[ENUM (To Do, In Progress, Done)]",  
    "decription" : "[description (optional)]"  
  }'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is updated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

5.3 Delete

Description

This API ***logically*** deletes a record of “status” from the basic data.

Request CURL Sample

```
curl --request DELETE \  
  --url 'https://[maindomian]/api/basic/status/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is deleted successfully."  
  "errorCode" : 0,
```

```
{
  "data" : null
}
```

5.4 Active

Description

This API activates a specific record of “status” in the basic data.

Request CURL Sample

```
curl --request PUT \
  --url 'https://[maindomain]/api/basic/status/active/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is activated successfully."
  "errorCode" : 0,
  "data" : null
}
```

5.5 Inactive

Description

This API in-activates a specific record of “status” in the basic data.

Request CURL Sample

```
curl --request PUT \
  --url 'https://[maindomain]/api/basic/status/inactive/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
```

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is inactivated successfully."
  "errorCode" : 0,
  "data" : null
}
```

5.6 Fetch Specific Record

Description

This API returns a specific record of “status” from the basic data.

Request CURL Sample

```
curl --request GET \
  --url 'https://[maindomian]/api/basic/status/[id]' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
  "data" : {
    "id" : 16621244611384550112,
    "title" : "test",
    "code" : "123",
    "color" : "FFFFFF",
    "statusEffect" : "In Progress",
    "description" : "test",
    "createdAt" : "2025-8-25 12:00:00",
    "createdBy" : "John Davis"
  }
}
```


5.7 Get All Records

Description

This API returns all active records of “status” from the basic data.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomian]/api/basic/status/getAll?title=test&code=123&color=FFFFFF&statusEffect=To+Do%2FIn+Progress%2FDone&description=test&offset=0&limit=15&sort_by=desc(fieldName)' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : [{  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123",  
    "color" : "FFFFFF",  
    "statusEffect" : "In Progress",  
    "description" : "test",  
    "createdAt" : "2025-8-25 12:00:00",  
    "createdBy" : "John Davis"  
  }]  
}
```

5.8 Get Combo List

Description

This API returns all active records of “status” from the basic data to use in combo or list form components.

Request CURL Sample

```
curl --request GET \  

```

```
--url 'https://[maindomian]/api/basic/status/getComboList' \  
--header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : [{  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123"  
  }]  
}
```

6 Resolution

6.1 Add

Description

This API adds a record of “resolution” into the basic data.

Request CURL Sample

```
curl --request POST \  
  --url 'https://[maindomian]/api/basic/resolution' \  
  --header 'Authorization: Bearer [token]' \  
  --header 'content-type: application/json' \  
  --data '{  
    "code" : "[code]",  
    "title" : "[title]",  
    "color" : "[Color Hex Code]",  
    "isResolved" : true/false,  
    "decription" : "[description (optional)]"  
  }'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is added successfully."
  "errorCode": 0,
  "data": {
    "id": 123
  }
}
```

6.2 Update

Description

This API updates a specific record of “resolution” in the basic data.

Request CURL Sample

```
curl --request PUT \
  --url 'https://[maindomain]/api/basic/resolution/[id]' \
  --header 'Authorization: Bearer [token]' \
  --header 'content-type: application/json' \
  --data '{
    "code" : "[code]",
    "title" : "[title]",
    "color" : "[Color Hex Code]",
    "isResolved" : true/false,
    "decription" : "[description (optional)]"
  }'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : "The record is updated successfully."
  "errorCode" : 0,
  "data" : null
}
```

6.3 Delete

Description

This API *logically* deletes a record of “resolution” from the basic data.

Request CURL Sample

```
curl --request DELETE \  
  --url 'https://[maindomian]/api/basic/resolution/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is deleted successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

6.4 Active

Description

This API activates a specific record of “resolution” in the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/resolution/active/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is activated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

```
}
```

6.5 Inactive

Description

This API in-activates a specific record of “resolution” in the basic data.

Request CURL Sample

```
curl --request PUT \  
  --url 'https://[maindomian]/api/basic/resolution/active/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : "The record is inactivated successfully."  
  "errorCode" : 0,  
  "data" : null  
}
```

6.6 Fetch Specific Record

Description

This API returns a specific record of “resolution” from the basic data.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomian]/api/basic/resolution/[id]' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,
```

```
{
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
  "data" : {
    "id" : 16621244611384550112,
    "title" : "test",
    "code" : "123",
    "color" : "FFFFFF",
    "isResolved" : true,
    "description" : "test",
    "createdAt" : "2025-8-25 12:00:00",
    "createdBy" : "John Davis"
  }
}
```

6.7 Get All Records

Description

This API returns all active records of “resolution” from the basic data.

Request CURL Sample

```
curl --request GET \
  --url 'https://[maindomain]/api/basic/resolution/getAll?
title=test&code=123&color=FFFFFF&isResolved=true%2Ffalse&description=t
est&offset=0&limit=15&sort_by=desc(fieldName)' \
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{
  "statusCode" : 200,
  "status" : "success",
  "message" : null,
  "errorCode" : 0,
  "data" : [{
    "id" : 16621244611384550112,
    "title" : "test",
    "code" : "123",
    "color" : "FFFFFF",
```

```
        "isResolved" : true,  
        "description" : "test",  
        "createdAt" : "2025-8-25 12:00:00",  
        "createdBy" : "John Davis"  
    }]  
}
```

6.8 Get Combo List

Description

This API returns all active records of “resolution” from the basic data to use in combo or list form components.

Request CURL Sample

```
curl --request GET \  
  --url 'https://[maindomain]/api/basic/resolution/getComboList' \  
  --header 'Authorization: Bearer [token]'
```

Response Sample

```
{  
  "statusCode" : 200,  
  "status" : "success",  
  "message" : null,  
  "errorCode" : 0,  
  "data" : [{  
    "id" : 16621244611384550112,  
    "title" : "test",  
    "code" : "123"  
  }]  
}
```