

# PY0101EN-2-2-Lists

August 23, 2020

[!\[\]\(919a2cb85b99741a73c0c31a427236a8\_img.jpg\)](https://cocl.us/PY0101EN_edx_add_top)

## Lists in Python

Welcome! This notebook will teach you about the lists in the Python Programming Language. By the end of this lab, you'll know the basics list operations in Python, including indexing, list operations and copy/clone list.

### Table of Contents

- [About the Dataset](#dataset)
- [Lists](#list)
  - [Indexing](index)
  - [List Content](content)
  - [List Operations](op)
  - [Copy and Clone List](co)
- [Quiz on Lists](#quiz)

Estimated time needed: **15 min**

### About the Dataset

Imagine you received album recommendations from your friends and compiled all of the recommendations into a table, with specific information about each album.

The table has one row for each movie and several columns:

- **artist** - Name of the artist
- **album** - Name of the album
- **released\_\_year** - Year the album was released

- **length\_min\_sec** - Length of the album (hours,minutes,seconds)
- **genre** - Genre of the album
- **music\_recording\_sales\_millions** - Music recording sales (millions in USD) on [SONG://DATABASE](#)
- **claimed\_sales\_millions** - Album's claimed sales (millions in USD) on [SONG://DATABASE](#)
- **date\_released** - Date on which the album was released
- **soundtrack** - Indicates if the album is the movie soundtrack (Y) or (N)
- **rating\_of\_friends** - Indicates the rating from your friends from 1 to 10

The dataset can be seen below:

Artist

Album

Released

Length

Genre

Music recording sales (millions)

Claimed sales (millions)

Released

Soundtrack

Rating (friends)

Michael Jackson

Thriller

1982

00:42:19

Pop, rock, R&B

46

65

30-Nov-82

10.0

AC/DC

Back in Black

1980

00:42:11

Hard rock

26.1

50  
25-Jul-80  
8.5  
Pink Floyd  
The Dark Side of the Moon  
1973  
00:42:49  
Progressive rock  
24.2  
45  
01-Mar-73  
9.5  
Whitney Houston  
The Bodyguard  
1992  
00:57:44  
Soundtrack/R&B, soul, pop  
26.1  
50  
25-Jul-80  
Y  
7.0  
Meat Loaf  
Bat Out of Hell  
1977  
00:46:33  
Hard rock, progressive rock  
20.6  
43  
21-Oct-77  
7.0  
Eagles

Their Greatest Hits (1971-1975)

1976

00:43:08

Rock, soft rock, folk rock

32.2

42

17-Feb-76

9.5

Bee Gees

Saturday Night Fever

1977

1:15:54

Disco

20.6

40

15-Nov-77

Y

9.0

Fleetwood Mac

Rumours

1977

00:40:01

Soft rock

27.9

40

04-Feb-77

9.5

Lists

Indexing

We are going to take a look at lists in Python. A list is a sequenced collection of different objects such as integers, strings, and other lists as well. The address of each element within a list is called an index. An index is used to access and refer to items within a list.

To create a list, type the list within square brackets [ ], with your content inside the parenthesis and separated by commas. Let's try it!

```
[ ]: # Create a list

L = ["Michael Jackson", 10.1, 1982]
L
```

We can use negative and regular indexing with a list :

```
[ ]: # Print the elements on each index

print('the same element using negative and positive indexing:\n Postive:',L[0],
'\n Negative:' , L[-3] )
print('the same element using negative and positive indexing:\n Postive:',L[1],
'\n Negative:' , L[-2] )
print('the same element using negative and positive indexing:\n Postive:',L[2],
'\n Negative:' , L[-1] )
```

### List Content

Lists can contain strings, floats, and integers. We can nest other lists, and we can also nest tuples and other data structures. The same indexing conventions apply for nesting:

```
[ ]: # Sample List

["Michael Jackson", 10.1, 1982, [1, 2], ("A", 1)]
```

### List Operations

We can also perform slicing in lists. For example, if we want the last two elements, we use the following command:

```
[ ]: # Sample List

L = ["Michael Jackson", 10.1,1982,"MJ",1]
L
```

```
[ ]: # List slicing

L[3:5]
```

We can use the method extend to add new elements to the list:

```
[ ]: # Use extend to add elements to list

L = [ "Michael Jackson", 10.2]
L.extend(['pop', 10])
L
```

Another similar method is append. If we apply append instead of extend, we add one element to the list:

```
[ ]: # Use append to add elements to list

L = [ "Michael Jackson", 10.2]
L.append(['pop', 10])
L
```

Each time we apply a method, the list changes. If we apply extend we add two new elements to the list. The list L is then modified by adding two new elements:

```
[ ]: # Use extend to add elements to list

L = [ "Michael Jackson", 10.2]
L.extend(['pop', 10])
L
```

If we append the list ['a','b'] we have one new element consisting of a nested list:

```
[ ]: # Use append to add elements to list

L.append(['a', 'b'])
L
```

As lists are mutable, we can change them. For example, we can change the first element as follows:

```
[ ]: # Change the element based on the index

A = ["disco", 10, 1.2]
print('Before change:', A)
A[0] = 'hard rock'
print('After change:', A)
```

We can also delete an element of a list using the del command:

```
[ ]: # Delete the element based on the index

print('Before change:', A)
del(A[0])
print('After change:', A)
```

We can convert a string to a list using split. For example, the method split translates every group of characters separated by a space into an element in a list:

```
[ ]: # Split the string, default is by space

'hard rock'.split()
```

We can use the split function to separate strings on a specific character. We pass the character we would like to split on into the argument, which in this case is a comma. The result is a list, and each element corresponds to a set of characters that have been separated by a comma:

```
[ ]: # Split the string by comma

'A,B,C,D'.split(',')
```

### Copy and Clone List

When we set one variable B equal to A; both A and B are referencing the same list in memory:

```
[ ]: # Copy (copy by reference) the list A

A = ["hard rock", 10, 1.2]
B = A
print('A:', A)
print('B:', B)
```

Initially, the value of the first element in B is set as hard rock. If we change the first element in A to banana, we get an unexpected side effect. As A and B are referencing the same list, if we change list A, then list B also changes. If we check the first element of B we get banana instead of hard rock:

```
[ ]: # Examine the copy by reference

print('B[0]:', B[0])
A[0] = "banana"
print('B[0]:', B[0])
```

This is demonstrated in the following figure:

You can clone list **A** by using the following syntax:

```
[ ]: # Clone (clone by value) the list A

B = A[:]
B
```

Variable **B** references a new copy or clone of the original list; this is demonstrated in the following figure:

Now if you change A, B will not change:

```
[ ]: print('B[0]:', B[0])
A[0] = "hard rock"
print('B[0]:', B[0])
```

### Quiz on List

Create a list `a_list`, with the following elements 1, hello, [1,2,3] and True.

```
[4]: # Write your code below and press Shift+Enter to execute
a_list=[1, "hello", [1,2,3], True]
```

Double-click here for the solution.

Find the value stored at index 1 of a\_list.

```
[6]: # Write your code below and press Shift+Enter to execute
a_list[1]
```

```
[6]: 'hello'
```

Double-click here for the solution.

Retrieve the elements stored at index 1, 2 and 3 of a\_list.

```
[8]: # Write your code below and press Shift+Enter to execute
a_list[1:4]
```

```
[8]: ['hello', [1, 2, 3], True]
```

Double-click here for the solution.

Concatenate the following lists A = [1, 'a'] and B = [2, 1, 'd']:

```
[10]: # Write your code below and press Shift+Enter to execute
A=[1, "a"]
B=[2,1, 'd']
A+B
```

```
[10]: [1, 'a', 2, 1, 'd']
```

Double-click here for the solution.

The last exercise!

Congratulations, you have completed your first lesson and hands-on lab in Python. However, there is one more thing you need to do. The Data Science community encourages sharing work. The best way to share and showcase your work is to share it on GitHub. By sharing your notebook on GitHub you are not only building your reputation with fellow data scientists, but you can also show it off when applying for a job. Even though this was your first piece of work, it is never too early to start building good habits. So, please read and follow this article to learn how to share your work.

Get IBM Watson Studio free of charge!

[<p><a href="https://cocl.us/PY0101EN\\_edx\\_add\\_bbottom"><img src="https://s3-api.us-geo.objectst](https://cocl.us/PY0101EN_edx_add_bbottom)

About the Authors:

Joseph Santarcangelo is a Data Scientist at IBM, and holds a PhD in Electrical Engineering. His research focused on using Machine Learning, Signal Processing, and Computer Vision to determine



how videos impact human cognition. Joseph has been working for IBM since he completed his PhD.

Other contributors: Mavis Zhou

Copyright © 2018 IBM Developer Skills Network. This notebook and its source code are released under the terms of the MIT License.