

UTILIZANDO ESPRESSO E UIAUTOMATOR

Eduardo Carrara

Developer Evangelist - Intel Developers Relations Division

#ANDROIDONINTEL



https://www.facebook.com/ducarrara



@DuCarrara



br.linkedin.com/in/eduardocarrara/



+EduardoCarraraDeAraujo



ecarrara-araujo



"I choose a lazy person to do a hard job.
Because a lazy person will find an easy way to do it."
- Bill Gates



Problemas?

Automação de Testes
Testes de Integração
Fragmentação e Testes







System Testing





UI Automator



Integration Testing



Unit Testing











Android Testing Framework



- Special TestCases, Asserts e Mocks
- MoreAsserts
- ViewAsserts
- MockApplication
- MockContext
- MockContentProvider



- AndroidTestCase
- ActivityInstrumentationTestCase2
- ActivityUnitTestCase
- ApplicationTestCase
- InstrumentationTestCase
- ProviderTestCase
- ServiceTestCase
- SingleLaunchActivityTestCase



Instrumentation

- Android Components Context Access;
- Components Lifecycle Control;
- Component Loading Control;
- System Events (e.g.: Broadcasts)
- InstrumentationTestRunner
 - AndroidJUnitRunner
 - GoogleInstrumentationTestRunner



Espresso

- Simplifies the UI Test Process within your App
- Methods for:
 - View matching
 - Checks
 - UI Events



Espresso - Configuração

build.gradle

```
dependencies {
    androidTestCompile 'com.android.support.test:runner:0.3'
    androidTestCompile 'com.android.support.test:rules:0.3'
    androidTestCompile 'com.android.support.test.espresso:espresso-core:2.2'
}
```


Desabilitar nas opções do desenvolvedor (no device):

- Window Animation Scale
- Transition Animation Scale
- Animator Duration Scale

Espresso – Primeiro Test Case

- 1. Crie uma subclasse de ActivityInstrumentationTestCase2
- 2. Identique o(s) componente(s) de UI que você quer testar.
- 3. Simule a interação do usuário com o componente.
- 4. Repita os passos utilizando assertions para verificar se a UI reflete o estado esperado depois das interações.

- Bibliotecário Virtual
- Ajudar a lembrar os livros emprestados.
- Nesta caso como automatizar o teste da visualização de detalhes de um empréstimo?
- Classe: TestViewLendedBookDetailFlow



```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
    public TestViewLendedBookDetailFlow() {
         super(BookListActivity.class);
```

intel

```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
   @Before
   public void setUp() throws Exception {
       super.setUp();
       injectInstrumentation(InstrumentationRegistry.getInstrumentation());
       mBookListActivity = getActivity();
       prepareTestData();
```

```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
    @After
    public void tearDown() throws Exception {
        clearTestData();
```

```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
  @Test
  public void testViewLendedBookDetailFlow() {
     onData(CursorMatchers.withRowString(
                    VilibraContract.BookEntry.COLUMN TITLE,
                    mBookTitle))
             .inAdapterView(withId(R.id.lended book list view))
             .perform(click());
```

```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
  @Test
  public void testViewLendedBookDetailFlow() {
     // check data in the detail screen
     onView(withId(R.id.book title text view))
             .check(matches(withText(mBookTitle)));
     onView(withId(R.id.book subtitle text view))
             .check(matches(withText(mBookSubtitle)));
```


```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
  @Test
  public void testViewLendedBookDetailFlow() {
     onView(withId(R.id.book authors text view))
             .check(matches(withText(mBookAuthors)));
     onView(withId(R.id.book publisher edition text view))
             .check(matches(withText(mBookPublisher)));
                                                              continua
```

```
public class TestViewLendedBookDetailFlow
        extends ActivityInstrumentationTestCase2<BookListActivity> {
  @Test
  public void testViewLendedBookDetailFlow() {
    pressBack();
                                                             Fim ©
```

(intel[®])

UI Automator

- Testes Cross App
- Baseado em Instrumentação
- Interage com elementos visíveis utilizando descritores convenientes (como texto).



UlAutomator - Configuração

build.gradle

```
dependencies {
    androidTestCompile 'com.android.support.test:runner:0.3'
    androidTestCompile 'com.android.support.test:rules:0.3'
    androidTestCompile 'com.android.support.test.uiautomator:uiautomator-v18:2.1.1'
}
```

É necessário inspecionar os componentes visuais das apps alvo para garantir que o UIAutomator consiga localizá-los.


Isso significa ter labels de texto visíveis, a propriedade android:contentDescription preenchida, ou ainda a propriedade android:hint (para EditTexts)

UlAutomator – Primeiro Test Case

- 1. Crie uma subclasse de InstrumentationTestCase
- 2. Obtenha uma instância de **UIDevice**.
- 3. Utilize o método **UIDevice.findObject()** para obter **UIObjects** e executar **ações**.
- 4. Utilize asserts para verificar os resultados.




UIAutomator - uiautomatorviewer



Intel Software and Services Group

- Novo caso: automatizando o registro de um empréstimo.
- Classe: TestLendBookFlow



```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Before
  public void setUp() throws UiObjectNotFoundException {
      clearTestData();
     mUiDevice = UiDevice.getInstance(getInstrumentation());
      // Should start from the home screen
     mUiDevice.pressHome();
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Before
  public void setUp() throws UiObjectNotFoundException {
      UiObject allAppsButton = mUiDevice.findObject(new UiSelector()
              .description("Apps"));
      assertTrue(allAppsButton.exists());
      allAppsButton.clickAndWaitForNewWindow();
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
  . . .
  @Before
  public void setUp() throws UiObjectNotFoundException {
      UiObject appsTab = mUiDevice.findObject(new UiSelector()
              .text("Apps"));
      assertTrue(appsTab.exists());
      appsTab.click();
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Before
  public void setUp() throws UiObjectNotFoundException {
      // find the scrollable list of apps
      UiScrollable appsList = new UiScrollable(new UiSelector()
              .scrollable(true));
      appsList.setAsHorizontalList();
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Before
  public void setUp() throws UiObjectNotFoundException {
     UiObject vilibraApp = appsList.getChildByText(new UiSelector()
             .className("android.widget.TextView"), "ViLibra");
     vilibraApp.click();
     mUiDevice.wait (Until. hasObject (By.pkg("ecarrara.eng.vilibra")),
             5000L);
                                                        Fim! Do setup...
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
   @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
     UiObject lendBookButton = mUiDevice.findObject(new UiSelector()
             .resourceId("ecarrara.eng.vilibra:id/add lending action button")
             .className("android.widget.ImageButton"));
     lendBookButton.clickAndWaitForNewWindow();
                                                                  continua
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
     UiObject isbnEditText = mUiDevice.findObject(new UiSelector()
             .text("ISBN")
             .className("android.widget.EditText"));
     isbnEditText.setText(BOOK ISBN);
                                                             continua
```

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
    UiObject confirmButton = mUiDevice.findObject(new UiSelector()
            .text("Confirm")
            .className("android.widget.Button"));
    confirmButton.clickAndWaitForNewWindow();
                                                             continua
```

(intel²)

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
     UiObject isbnTextView = mUiDevice.findObject(new UiSelector()
             .className("android.widget.TextView")
             .resourceId("ecarrara.eng.vilibra:id/book isbn10 text view"));
     Assert.assertTrue(isbnTextView.getText().contains(BOOK ISBN));
```

continua

intel

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
     UiObject lendButton = mUiDevice.findObject(new UiSelector()
              .className("android.widget.Button")
              .text("Lend this Book"));
     lendButton.clickAndWaitForNewWindow();
```


```
public class TestLendBookFlow extends InstrumentationTestCase {
   @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
     UiObject contactView = mUiDevice.findObject(new UiSelector()
              .className("android.widget.TextView")
              .text("Meu Irmao"));
     contactView.click();
     mUiDevice.wait (Until. hasObject (By.pkg ("ecarrara.eng.vilibra")),
             500L);
```

UIAutomator – Caso Vilibra

```
public class TestLendBookFlow extends InstrumentationTestCase {
  @Test
  public void testLendBookFlow() throws UiObjectNotFoundException {
     UiObject bookTitleTextView = mUiDevice.findObject(new UiSelector()
             .className("android.widget.TextView")
             .resourceId("ecarrara.eng.vilibra:id/book name text view")
             .text(BOOK TITLE));
     Assert.assertTrue(bookTitleTextView.exists());
```




(intel[®])




Fragmentação


Variedade de tamanhos de tela Arquiteturas Diferentes Versões diferentes de OS















What is next?

- Experimente automatizar os testes de sua app!
- Como fazer Integração e Entrega Contínua com Android?
- Cobertura de Código
- Mocking



Intel Developer Zone



https://software.intel.com/en-us/android/app-testing

Nos Avalie!

http://bit.ly/IntelPesquisa



THANKS!



https://www.facebook.com/ducarrara



@DuCarrara



br.linkedin.com/in/eduardocarrara/



+EduardoCarraraDeAraujo



ecarrara-araujo/vilibra

References

- Android Testing: https://developer.android.com/tools/testing/testing_android.html
- Android Unit Testing Support: http://tools.android.com/tech-docs/unit-testing-support
- UI Testing: https://developer.android.com/training/testing/ui-testing/index.html
- Android Testing Support Library: https://developer.android.com/tools/testing-support-library
- Android Instrumentation: <u>http://developer.android.com/tools/testing/testing_android.html#Instrumentation</u>
- Junit: http://junit.org
- Testdroid: http://testdroid.com
- Intel App Testing Page: https://software.intel.com/en-us/android/app-testing

(intel)

