

C-Sections

These sections are generally used as framed opening jambs and headers. As required by design single or double C back to back may be used. These are also used as top and bottom girt in secondary framing of fascias. Single or double C-sections can also be used as end wall rafters and columns, but at MBS these are not used due to various municipality requirements of minimum thickness of primary framing members. 120 mm deep sections are used as framing members of sliding doors.

Framing

Most commonly simply supported flush connection.

Connection Bolts

All bolts used for connection are 12 mm diameter HSB Gr. 8.8. Grade of bolt is subject to change based on availability and management decision.

General

1. We are now using the TMCP roll forming machine to produce 200 & 250 mm deep 'C' sections. We are using 2 coil widths for fabricating C-sections, 345 mm coil for 200C15, and 394 mm coil for 200C20, 200C25, 250C20 & 250C25. The flanges and webs of this 'C' section are stiffened with longitudinal ribs. 200C15 may be used for small framed openings for windows, louvers etc up to a maximum of 3000 mm long.
2. 250 mm deep C-Sections may be used for framed openings for jambs and header, when the purlin or girt sections are 250 mm deep. A 394 mm coil is also used to produce 250 mm deep Z-Sections.
3. 'C' sections of any profile can be produced on the TMCP machine, with following limitations, but these will require stocks of different coil widths.

Table 16.4 Section Profile on TMCP Machine

Dimension	Minimum (mm)	Maximum (mm)
Web depth	92	356
Flange width	41	76
Lip length	NA	25
Thickness	0.8	2.5
Minimum length = 900 mm		
NA - Denotes that sections may be without lip (Open C or Stud)		