

SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

LINER PANELS			
1	Roof Liner	Area (m ²)	Roof is fully lined.
		Flange braces	Rafter flange braces will be kept .
		Location	Liner panel is located under purlins .
2	Wall Liner	Area (m ²)	Not Applicable.
		Flange braces	Not Applicable.
		Location	Not Applicable.

MEZZANINES								
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's " MEZZANINES " brochure for more details of standard Mezzanine.								
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:							No	
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:							No	
• 1.10 m high industrial handrail is provided at free ends of mezzanine:							No	
Spacing of Mezzanine columns:								
Sr. No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	0.25	605	A (120)	3.353	None	None
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)								

Note: Given Concrete thickness is inclusive of floor finishes.

ROOF ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	No's
1	Roof Insulation. Type: Fiberglass Insulation Thick(mm): 100 ; Density(Kg/m ³) = 12 Facing: FRK	Full Covered Area