



SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

(AREA-01 & 02)

WALL ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	No's
1	Fiberglass Insulation , Facing: WMSK Thickness (mm)= 100, Density (kg/m ³) =12	Full Sheeting Area
2	Frame Opening for Double Sliding Door (by others) at NSW. Width= 6096mm, Height = 6096mm	02
ROOF ACCESSORIES		For Basic Price Only
		Quantity per Area
No.	Description	No's
1	Fiberglass Insulation , Facing: WMSK Thickness (mm)= 100, Density (kg/m ³) =12	Full Sheeting Area

STAIRS									
Stair treads can be red oxide primed checkered plate, painted "U" shaped pans or galvanized Grat Handrails are fabricated from pipe sections; these may be primed or painted.									
Sr.	Located at	Qty	Stair Type	Out to Out width of staircase (mm)	1.1m High Handrails Included	Qty of Top Landing	Qty of Mid Landing	Stair Height (m)	Type of Treads
1	FSW	01	Double Flight (U-Shape)	1219	No	Yes (1)	Yes (1)	5.912	Pan Type

FASCIA							
The height of the fascia, the fascia projection and optional fascia features greatly affect the fascia price. Optional fascia features include soffit panels, back up panels and valley gutters. Cap flashing is always a standard supply item.							
Type of fascia: Parapet/Bracket Mounted (Top & Bottom Curved/Bottom Curved/Standard Vertical)							
#	Location	Height (m)	Length (m)	Projection FASCIAS (m)	Optional Fascia Features		Gutter Type
					Soffit Panel included	Backup Panel included	
1	Left End wall	1.281	12.192	-	No	No	Transition trim
2	Right End wall	1.281	12.192	-	No	No	Transition trim

***Note: Stair is in Area-01 & Fascia in Area-02. Refer to Drawings.**