

SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

AREA NO.01

MEZZANINES									
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's " MEZZANINES " brochure for more details of standard Mezzanine.									
B. Mezzanine with Precast slab or hollow core slab supplied by others: No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.									
• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:								No	
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:								No	
• 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
Spacing of Mezzanine columns:									
Sr. No	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	3	3	None	None		A	3.658	0.100	3.758
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)									

Note:

Mezzanine is designed by taking 3 KN/m² live load as per client requirements.