

SECTION 1: SCOPE OF WORKS

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's **"MEZZANINES"** brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:	Yes
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:	Yes

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per design	3	0.00	0.00	32	A-50mm	-	-	4.305

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

STAIRS (Maimaar Standard Stair is 1.2m wide and 3.6m high with one intermediate landing).

Stair treads can be red oxide primed checkered plate, painted "U" shaped pans or galvanized Grating.

Handrails are fabricated from pipe sections; these may be primed or painted.

Sr. No.	Located in Mezz. No.	Qty	Stair Type	Out to Out width of staircase (mm)	1.1m High Handrails Included	Qty of Top Landing	Qty of Mid Landing	Stair Height (m)	Type of Treads
1	01	01	Single	1200	Yes	No	No	4.305	Checkered
2	01	01	Single	1200	Yes	No	No	4.305	Checkered

ROOF PANELS

Single Skin Panel	Profile	Standard
	Material	0.50mm PPGI + 100mm Fiberglass Insulation + 0.50mm PPGI Liner Panels
	Finish	Polyester Pre-Painted
	Color	TBE