

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01**

MEZZANINES									
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.									
B. Mezzanine with Precast slab or hollow core slab supplied by others: No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.									
- Exterior Mezzanine joists and beams in this area are designed to support blockwall loads: - Interior Mezzanine joists and beams in this area are designed to support blockwall loads: 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
								No	
								Yes	
Spacing of Mezzanine columns:									
Sr. No.	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per design	5.00	0.10	0.00	543.70	A (120mm)	6.096	-	-
* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)									

*Steel Cladding is to be provided all around the mezzanine structure along with 0.5mm PPGI Liner panels and 100mm Fiberglass Insulation, to act as walls.

*The mezzanine floor is designed to support the load of Bhan Stitching Hall Structure that is to be installed over the top of mezzanine.

*The structure of Bhan Stitching Hall is to be slightly rehabilitated (Strengthened) in order to Install it atop mezzanine floor.

*4 Feet brickwall at Bhan Stitching Unit is to be removed in order to make the mezzanine structure more stable and economic. Additional Sheeting is to be installed in replacement of brickwall.

*Steel Walls along mezzanine are open up to 1.220m for blockwall (by others), rest height is sheeted.

OPEN WALL CONDITIONS			Please refer to section "2" for roof & wall panel description.
1	Near Side Wall	Open up to 1.220m for block wall. (By others), rest height is sheeted	
2	Far Side Wall	Open up to 1.220m for block wall. (By others), rest height is sheeted	
3	Left End wall	Open up to 1.220m for block wall. (By others), rest height is sheeted	
4	Right End wall	Open up to 1.220m for block wall. (By others), rest height is sheeted	