

SECTION 1: BUILDING DESCRIPTION

1.1 BUILDING NO. 01

1.1.1 BUILDING NO. 01

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s **“MEZZANINES”** brochure for more details of standard Mezzanine.

B. Mezzanine Floor With 3mm Chaqured Plates

C. Mezzanine Floor With Pre-Cast or Hollow Core Concrete Slabs

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:

• Interior Mezzanine joists and beams in this area are designed to support block wall loads:

• 1.10 m high industrial handrail is provided at free ends of mezzanine:

No

No

No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m²)				Area (m²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.00	None	0.00	96.57	A (100mm)	2.134	-	-

* - Dead Load includes the Self Weight of Hollow Core Slabs