



SECTION 1: BUILDING DESCRIPTION

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s **“MEZZANINES”** brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:	No

Spacing of Mezzanine columns:

Sr. No	Mezzanine Loads (kN/m²)				Area (m²)	Type of Floor &Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter	From FFL to Top of Concrete Slab
1	As Per Design	6.0	0.15	None.	2,155	A(120)	4.267	4.267	As per design

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

Notes:

1. Mezzanine is designed to support Live Load= 6.0 KN/m² (Dynamic) i.e. 9 KN/m² (Static).