

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01**

BUILDING PARAMETERS			
1	Type	MS-1, Multi Slope	
2	No. of Interior columns	One	
3	Width Module (m)	2@16.764	
4	Roof Slope(mm)	1:20	
5	Width (m)	33.528	Out to Out of Steel line
6	Length (m)	41.148 @GL-A 51.816 @GL-G	Out to Out of Steel line (Refer Drawings)
7	Exterior Columns Base Condition	Pinned	
8	Interior Columns Base Condition	Pinned	
9	Height (m) from FFL	7.010	Clear Height from FFL@ Lower Eave
10	Bay Spacing (m)	2@5.334m + 6@6.858m Out to Out of Steel Line	
11	End walls	Left End wall	Frame Type: Main Girts: By framed Column Spacing : 4@5.588m out to out of steel line
		Right End wall	Frame Type: Bearing Girts: By frame Column Spacing : 6@5.588m out to out of steel line
12	Bracing Type	At Exterior Walls	Diagonal (Cable)
		Between Interior Walls	Diagonal (Cable)
13	Type of Eave	Eave Gutters & Downspouts	
14	Type of Gable	Gable Trim	
15	Exterior Rigid Frame Columns	Tapered Web	
16	Fillet Weld of Built up Sections	Single Side Welding for all Built up sections	

OPEN WALL CONDITIONS			Please refer to section "2" for roof & wall panel description.
1	Near Side Wall	Open up to 3.05m for blockwall. (By others), rest height is sheeted	
2	Far Side Wall	Open up to 3.05m for blockwall. (By others), rest height is sheeted	
3	Left End wall	Open up to 3.05m for blockwall. (By others), rest height is sheeted	
4	Right End wall	Open up to 3.05m for blockwall. (By others), rest height is sheeted	

Note:

The building is chamfered @ **Grid 1A** b/w **1C and 3A**. This portion holds a single sliding door 7.543m wide and 4.572m high.