



SECTION 1: BUILDING DESCRIPTION

1.2 BUILDING NO. 01

MEZZANINES

A. Maimaar standard mezzanine:

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "**MEZZANINES**" brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:	No

Spacing of Mezzanine columns:

No.	Mezzanine Loads (kN/m ²)			Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	5.0	None	334.44	A (100)	3.658	As per Design	As per Design

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)