

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's "**MEZZANINES**" brochure for more details of standard Mezzanine.

B. Mezzanine with hollow core slab supplied by Maimaar:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

• Exterior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• Interior Mezzanine joists and beams in this area are designed to support block wall loads:	No
• 1.10 m high industrial handrail is provided at free ends of mezzanine:	No

Spacing of Mezzanine columns:

Sr. No.	Mezzanine Loads (KN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	**Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From of FFL to Top of RCC Slab	From FFL to Top of Concrete Slab

Ground Floor – Phase-01- (Refer Drawings for Dimensions) Completed Except Area b/w I2-13 is left for Phase-02

1	As per Design	5.0	0.12	0.00	222.70	B	2.895	As per Design	As per design-
---	---------------	-----	------	------	--------	---	-------	---------------	----------------

Basement, Ground and First Floor – Phase-02- (Refer Drawings for Dimensions)

2 (Ground)	As per Design	5.0	0.12	0.00	274	B	2.895	As per Design	As per design
3 (First floor)	As per Design	5.0	0.12	00	364	A	2.590	As per Design	AS per design

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

****Note:**

- The live load for mezzanine floors is taken as **5 KN/M²**.
- Ground floor mezzanine is designed for 250mm Hollow core slabs as deck (by others) on top of Mezzanine beams.
- 0.12 KN/Sq. M load is considered for False Ceiling
- First Floor mezzanine is designed for 100mm Concrete for Dead Load. Decking Panels of 0.70mm thickness will be laid on Beams & Joists for Concrete Pouring.
- An opening approximately 2440mm x2440mm (8ft by 8ft) is provided in the ground floor and first floor mezzanine for lift.