

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01****AREA NO. 01****MEZZANINES****A. Maimaar standard mezzanine:**

Supply normally includes support **columns**, primary **beams**, secondary **joists** and a **0.7mm galvanized steel deck** that supports a **reinforced** concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar's **"MEZZANINES"** brochure for more details of standard Mezzanine.

B. Mezzanine with Precast slab or hollow core slab supplied by others:

No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.

- Exterior Mezzanine joists and beams in this area are designed to support block wall loads:
- Interior Mezzanine joists and beams in this area are designed to support block wall loads:
- 1.10 m high industrial handrail is provided at free ends of mezzanine:

No**No****Yes****Spacing of Mezzanine columns:**

Sr. No.	Mezzanine Loads (kN/m ²)				Area (m ²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	**Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From Top of Concrete Slab to bottom of Rafter / Beam	From FFL to Top of Concrete Slab
1	As per Design	3.0	0.00	0.00	47.00	B	-	2.743	-
2	As per Design	3.0	0.00	0.00	47.00	B	-	2.743	-

* - Dead Load includes the Self Weight of (Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)

****Note:**

- Please note that the live load for mezzanine floors is taken as **3 KN/m²**.
- 2' Extended platform is provided at the end wall for accommodation of spiral stairs and doors.