

## SECTION 1: BUILDING DESCRIPTION

### 1.1 BUILDING NO. 01

#### 1.1.1 BUILDING NO. 01

#### AREA NO. 01

| MEZZANINES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                      |        |            |       |                        |                          |                                  |                                                      |                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--------|------------|-------|------------------------|--------------------------|----------------------------------|------------------------------------------------------|----------------------------------|
| <b>A. Maimaar standard mezzanine:</b><br>Supply normally includes support <b>columns</b> , primary <b>beams</b> , secondary <b>joists</b> and a <b>0.7mm galvanized steel deck</b> that supports a <b>reinforced</b> concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s <b>“MEZZANINES”</b> brochure for more details of standard Mezzanine. |                                      |        |            |       |                        |                          |                                  |                                                      |                                  |
| <b>B. Mezzanine with Precast slab or hollow core slab supplied by others:</b><br>No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.                                                                                                                                                                                                                                                                                                                                                                                                                 |                                      |        |            |       |                        |                          |                                  |                                                      |                                  |
| • Exterior Mezzanine joists and beams in this area are designed to support block wall loads:<br>• Interior Mezzanine joists and beams in this area are designed to support block wall loads:<br>• 1.10 m high industrial handrail is provided at free ends of mezzanine:                                                                                                                                                                                                                                                                                                                                   |                                      |        |            |       |                        |                          |                                  | No                                                   |                                  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                      |        |            |       |                        |                          |                                  | No                                                   |                                  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                      |        |            |       |                        |                          |                                  | Yes                                                  |                                  |
| Spacing of Mezzanine columns:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                      |        |            |       |                        |                          |                                  |                                                      |                                  |
| Sr. No.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Mezzanine Loads (kN/m <sup>2</sup> ) |        |            |       | Area (m <sup>2</sup> ) | Type of Floor &Thk. (mm) | Minimum Clear Heights (m)        |                                                      |                                  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Dead*                                | **Live | Collateral | Other |                        |                          | From FFL to Bottom of Mezz. Beam | From Top of Concrete Slab to bottom of Rafter / Beam | From FFL to Top of Concrete Slab |
| 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | As per Design                        | 5.0    | 0.00       | 0.00  | ≈189                   | A                        | 3.354                            | -                                                    | -                                |
| 2<br>(Option 01)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | As per Design                        | 5.0    | 0.00       | 0.00  | ≈114                   | A                        | 3.354                            | -                                                    | -                                |
| 3<br>(Option 02)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | As per Design                        | 5.0    | 0.00       | 0.00  | ≈217                   | A                        | 3.354                            | -                                                    | -                                |
| * - Dead Load includes the Self Weight of ( Floor + Floor Finish + Steel Deck Panel, if applicable + Joist)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                      |        |            |       |                        |                          |                                  |                                                      |                                  |

#### \*\*Note:

- Please note that the live load for mezzanine floors is taken as **5 KN/m<sup>2</sup>**.
- A cantilever shade is provided along GL-D to provide shade for the buses parked under it.  
(Option No. 01)
- Second floor mezzanine is extended 12 feet away from the existing building to increase the area of top floor and provide shade to the busses parked under. (Option No. 02)
- Only 2 supporting columns are provided at GL-1 & 2 along GL-E to support load of second floor mezzanine whereas the column at GL-6 is slanted to clear space for turnings of busses.  
(Option No. 02)
- Near Side Wall consists of Fascia to support the sign board of **Sania Express**.
- For mezzanine area between GL 7-10, existing steel shade (Light gauge) is to be used as first floor roof and the walls are to be covered with glass (By others).
- Existing steel structure (adjacent to the washrooms) is to be removed and the material will be used construction of new structure.
- Please refer to drawings and 3D Views for better understanding of the structure.