

**SECTION 1: BUILDING DESCRIPTION****1.1 BUILDING NO. 01****1.1.1 BUILDING NO. 01**

MEZZANINES									
A. Maimaar standard mezzanine: Supply normally includes support columns , primary beams , secondary joists and a 0.7mm galvanized steel deck that supports a reinforced concrete slab (slab by others). The steel deck acts as a shuttering that carries the weight of the slab during construction only. The concrete slab must contain steel reinforcements and must be designed by a structural engineer to support all the applied loads on the mezzanine. Please refer to Maimaar’s “MEZZANINES” brochure for more details of standard Mezzanine.									
B. Mezzanine with Precast slab or hollow core slab supplied by Maimaar: No deck is supplied in this option. Steel columns, primary beams and some connecting joists are supplied.									
• Exterior Mezzanine joists and beams in this area are designed to support Block wall loads: • Interior Mezzanine joists and beams in this area are designed to support Block wall loads: • 1.10 m high industrial handrail is provided at free ends of mezzanine:								No	
								No	
								No	
Spacing of Mezzanine columns:									
Sr. No.	Mezzanine Loads (KN/m²)				Area (m²)	Type of Floor & Thk. (mm)	Minimum Clear Heights (m)		
	Dead*	Live	Collateral	Other			From FFL to Bottom of Mezz. Beam	From of FFL to Top of RCC Slab	From FFL to Top of Concrete Slab
10 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	401.14	A (120mm)	-	~3.05	-
9 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	393.52	A (120mm)	-	~3.05	-
8 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	512.59	A (120mm)	-	~3.05	-
7 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	406.77	A (120mm)	-	~3.05	-
6 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	406.77	A (120mm)	-	~3.05	-
5 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	406.77	A (120mm)	-	~3.05	-
4 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	712.84	A (120mm)	-	~3.05	-
3 th Lower	As Per Design	AS Per Design	As Per Design	As Per Design	712.84	A (120mm)	-	~3.05	-
2 nd Lower	As Per Design	AS Per Design	As Per Design	As Per Design	1626.91	A (120mm)	-	~3.05	-
1 st Lower	As Per Design	AS Per Design	As Per Design	As Per Design	1628.09	A (120mm)	-	~2.44	-